



PX-501 Clock Oscillator

Helping Customers Innovate, Improve & Grow



Features

*Reflow Process Compatible
Surface Mount Package
AT-Cut Crystal
SONET Minimum Clock Specification
Low Phase Noise
Tight Tolerances*

Typical Applications

*Base Stations
Test Equipment
Synthesizers*

Previous Vectron Model Number	C1310
Frequency Range	10 MHz – 1200 MHz
Standard frequencies	10; 20; 24.705; 30.720; 32.768; 50; 68.768; 76.8; 77.76MHz; 100; 125; 150; 155.52; 156.25; 175; 200; 250; 280; 312.5MHz; 340; 400; 622,08 MHz

Frequency stabilities¹ [Standard]

Parameter	Min	Typ	Max	Units	Operating temp range
vs. operating temperature range (Referenced to +25°C)	-10.0		+10.0	ppm	-20 ... +70°C
Parameter	Min		Max	Units	Condition
Initial tolerance	-5.0		+5.0	ppm	V _s ± 5% Load ± 5%
vs. supply voltage change	-1.0		+1.0	ppm	
vs. load change	-1.0		+1.0	ppm	
vs. aging /1. Year	-3.0		+3.0	ppm	
vs. aging / year (following Years)	-1.0		+1.0	ppm	

Frequency stabilities¹ [meets SONET Minimum Clock Specification-Option]

Parameter	Min	Typ	Max	Units	Operating temp range
vs. operating temperature range					-40 ... +85°C
Parameter	Min		Max	Units	Condition
overall tolerance	-20.0		+20.0	ppm	(15 Years aging, temp, initial, supply, load)

Supply Voltage (Vs)

Parameter	Min	Typ	Max	Units	Condition
Supply voltage (Vs)	4.75	5.0	5.25	VDC	@ HCMOS < 155 MHz
Current consumption			40	mA	
Current consumption			90	mA	
Supply voltage (Vs)	3.135	3.3	3.465	VDC	@ LVHCMOS < 155 MHz
Current consumption			30	mA	
Current consumption			80	mA	
Current consumption			25	mA	@ LVDS < 155 MHz

RF Output

Parameter	Min	Typ	Max	Units	Condition
Signal	HCMOS				
Load		15.0		pF	@15 pF 10 to 90%
Rise and Fall Time			5	ns	
Duty cycle	40		60	%	
Signal	PECL				
Load		50		Ω	Vs-2V
Rise and Fall Time			1	ns	20-80%
Duty cycle	45		55	%	
Signal	LVDS				
Load		100		Ω	10 to 90 %
Rise and Fall time			1	ns	
Duty cycle	40		60	%	
Signal	Sinewave				
Load		50		Ω	
Output Power	-3	0	3	dBm	

Additional Parameters

Parameter	Min	Typ	Max	Units	Condition
Phase Noise		-85		dBc/Hz	10 Hz @49,408 MHz
		-120		dBc/Hz	100 Hz HCMOS
		-145		dBc/Hz	1 kHz 3,3V
		-155		dBc/Hz	10 kHz
		-160		dBc/Hz	100 kHz
Jitter		0,2		ps RMS	@ 12 kHz to 20 MHz

Additional Parameters

Parameter	Min	Typ	Max	Units	Condition		
Phase Noise		-76		dBc/Hz	10	Hz	@416 MHz
		-108		dBc/Hz	100	Hz	LVPECL
		-134		dBc/Hz	1	kHz	3,3V
		-147		dBc/Hz	10	kHz	
		-154		dBc/Hz	100	kHz	
		-159		dBc/Hz	1	MHz	
Jitter		0,018		ps RMS	@ 12 kHz to 20 MHz		
Weight				2	g		
Processing & Packing	handling & processing note						

Enclosure

Type G223A for HCMOS and LVHCMOS Version		Type G218B for HCMOS; PECL; LVPECL and LVDS Version	
Height "H" 5,9	Pin Length "L" NA	Height "H" 5,9	Pin Length "L" NA
<p style="text-align: center;">Dimensions: mm</p>		<p style="text-align: center;">Dimensions: mm</p>	

Pin Connections		Pin Connections				
1	NC / Enable (optional)	1	N/C			
2	Ground (Case)	2	N/C / Enable (optional)			
3	RF Output	3	Ground (Case)			
4	Supply Voltage Input (Vs)	4	RF Output			
		5	Complementary RF Output / (N/C: HCMOS only)			
		6	Supply Voltage Input (Vs)			
	Outline Drawing: G223B		Outline Drawing: G218B			
		Enable true table	HCMOS		LVPECL / LVDS	
		Pin 2	Pin 4	Pin 5	Pin 4	Pin 5
		High	Data	N/C	No Data	No Data
		Open	Data	N/C	Data	compl. Data
		Low	High Tristate	N/C	Data	compl. Data


Enclosure

Marking PX-501-xxxx frequency * VI AYYWW


Absolute Maximum Ratings

Parameter	Min	Typ	Max.	Units	Condition
Supply voltage (Vs)			7	V	
Operable temperature range	-40		+85	°C	
Storage temperature range	-40		+95	°C	

Typical Phase Noise and Jitter




Standard Shipping Methode



Enclosure Type	Tape width W [mm]	Quantity per meter	Quantity per reel	Dimension P
G218B / G223B	24	83,3	850	12

Recomanded Reflow Profile



Profile Feature	Pb-Free Assembly/ Sn.Pb Assembly	Profile Feature	Pb-Free Assembly/ Sn.Pb Assembly
Average ramp-up rate (T_L to T_p)	3°C/second max.	Time 25°C to Peak Temperature	8 minutes max.
Preheat -Temperature Min $T_{s_{min}}$ -Temperature Min $T_{s_{max}}$ -Time (min to max) (t_s)	150°C 200°C 60-180 seconds	Time maintained above -Temperature (T_L) -Time (t_l)	217°C 60-150 seconds

T_{Smax} to T_L -Ramp-up Rate	3°C/second max	Time within 5°C of actual Peak Temperature (t_p)	20-40 seconds
Peak Temperature (T_p)	max 260°C	Ramp-down Rate	6°C/ second max

Note: All temperatures refer to topside of the package, measured on the package body surface.
SMD oscillators must be on the top side of the PCB during the reflow process.

How to order this product:

Use this worksheet to forward the following information to your factory representative:									
Model	Height	-	Supply Voltage Code	RF Output Code	Temperature Range	-	Stability	-	Frequency
PX-501	1	-	E	A	J	-	105	-	10MHz

Height: _____
1: 5,9 mm

Supply Voltage Code:

E: 3,3 V

D: 5 V

RF Output Code:

A: HCMOS

C: PECL

D: LVDS

E: Sinewave

Temperature Range/Stability Code:

J-105: -20...+70°C ±10ppm

J-205: -20...+70°C ±20ppm

Notes:

- 1 Contact factory for improved stabilities or additional product options. Not all options and codes are available at all frequencies.
- 2 Unless otherwise stated all values are valid after warm-up time and refer to typical conditions for supply voltage, frequency control voltage, load, temperature (25°C)
- 3 Phase noise degrades with increasing output frequency.
- 4 Subject to technical modification.
- 5 Contact factory for availability.