


IEC Connector C21, for very hot conditions 155°C, Rewireable, Straight



Rewireable connector



Example with assembled cable



Description

- Cord Connector
- Connector , Pin temperature 155 °C , Protection class I
- Cable diameter 6.5 - 16 mm
- Min. wire size 16AWG / 1.0 mm²
- Max. wire size 10AWG / 1.5 mm²

Approvals

- ENEC File Number: 40039959
- UL File Number: E96454
- CCC File Number: 2014010204701246

Characteristics

- Suitable for use in equipment according to IEC/UL 60950


Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Distributor-Stock-Check](#), [Accessories](#), [Detailed request for product](#)

Technical Data

| | | | |
|---------------------------|---|-------------------------|---|
| Ratings IEC | 16A / 250VAC; 50Hz | appliance inlet/-outlet | C21 acc. to IEC 60320-1, UL 498, CSA C22.2 no. 42 (for very hot conditions) pin-temperature 155 °C, 16A, Protection Class I |
| Ratings UL/CSA | 20A / 250VAC; 60Hz | | |
| Dielectric Strength | > 1.5 kVAC between L-N > 1.5 kVAC between L/N-PE (1 min/50Hz) | | |
| Allowable Operation Temp. | -25 °C to 155 °C | | |
| Insulation cover | Suitable for appliances with protection class I acc. to IEC 61140 | | |
| Terminal | Cable | | |
| Material: Housing | Thermoplastic, black, UL 94V-0 | | |

Dimensions



1) Cutting points for 10/12/14/16 mm cable diameter

All Variants

| Color | Max. cable diameter | Max. wire size | Order Number |
|-------|---------------------|--------------------------------------|--------------|
| black | 16 mm | 3 x 1.5 mm ² / 3 x 10 AWG | 1658.0000 |

Most Popular.

Availability for all products can be searched real-time: <http://www.schurter.com/Stock-Check/Stock-Check-SCHURTER>

Max. torque for screws: Terminals: 0.8 Nm, Cable clamp: 0.4 Nm, Cover: 0.4 Nm

Packaging unit 50 Pcs

Mating Inlets/Plugs

Category / Description



[Appliance Inlet Overview complete](#)

IEC Appliance Inlet C22, for very hot conditions 155°C, Screw-on or Snap-in Mounting, Front Side

1681

[Appliance Inlet further types to 1658](#)



[Power Entry Module with line filter Overview complete](#)

C20F, 20 A, prewired, Standard and Medical Version, Solder, quick connect or wires (stranded), Capacitor: X2, Screw, Mounting Front-/Rear-Side, Power Entry Modules with Filter

C22F

[Power Entry Module with line filter further types to 1658](#)