

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1715767234](#)
Status: **Active**
Overview: [Impact™ Backplane Connectors and Cable Assemblies](#)
Description: Impact™ 100 Ohm 6-Pair Right-Angle Orthogonal Direct Header, Top Guided, with Outtrigger, 12 Column, 72 Differential Pair, 270#Mate Position, Pin Length 4.90mm, Plated Through-Hole Dimension 0.46mm, Lead Free

Documents:

| | |
|---|--|
| Drawing (PDF) | Application Specification AS-76850-990-001 (PDF) |
| Product Specification PS-45499-002-001 (PDF) | Packaging Specification PK-70873-8024 (PDF) |
| Product Specification PS-76060-999-001 (PDF) | RoHS Certificate of Compliance (PDF) |
| Application Specification AS-76060-9999-001 (PDF) | |

Agency Certification

UL E29179

General

| | |
|-------------------------------|---|
| Product Family | Backplane Connectors |
| Series | 171576 |
| Application | Orthogonal Direct |
| Application Tooling Documents | TM-622018799 |
| Component Type | PCB Header |
| Overview | Impact™ Backplane Connectors and Cable Assemblies |
| Product Name | Impact™ |
| Style | N/A |
| UPC | 887191724201 |

Physical

| | |
|--------------------------------|--------------------------------|
| Circuits (Loaded) | 216 |
| Circuits (maximum) | 216 |
| Color - Resin | Black |
| Durability (mating cycles max) | 200 |
| First Mate / Last Break | No |
| Guide to Mating Part | Yes |
| Keying to Mating Part | None |
| Material - Metal | High Performance Alloy (HPA) |
| Material - Plating Mating | Gold |
| Material - Plating Termination | Tin |
| Material - Resin | High Temperature Thermoplastic |
| Net Weight | 46.003/g |
| Number of Columns | 12 |
| Number of Pairs | 6 |
| Number of Rows | 18 |
| Orientation | Right Angle |
| PC Tail Length | 1.40mm |
| PCB Locator | No |
| PCB Retention | Yes |
| PCB Thickness - Recommended | 1.00mm |
| Packaging Type | Tray |
| Pitch - Mating Interface | 1.90mm |
| Pitch - Termination Interface | 1.90mm |
| Plating min - Mating | 0.762µm |
| Polarized to PCB | Yes |
| Stackable | No |
| Temperature Range - Operating | -55°C to +85°C |
| Termination Interface: Style | Through Hole - Compliant Pin |



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

REACH SVHC

Not Contained Per -
ED/21/2016 (20 June
2016)

Halogen-Free

Status

Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any non-product compliance questions.

China ROHS

ELV

RoHS Phthalates

Green Image

Not Relevant

Not Contained

Search Parts in this Series

[171576](#) Series

Mates With

[76290](#) Impact™ 100 Ohm Right Angle Orthogonal Daughtercard

Electrical

| | |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A |
| Data Rate | 25.0 Gbps |
| Impedance | 100Ω |
| Shield Type | N/A |
| Shielded | No |
| Voltage - Maximum | 30V AC (RMS)/DC |

Solder Process Data

| | |
|-----------------------------|-----|
| Lead-freeProcess Capability | N/A |
|-----------------------------|-----|

Material Info**Reference - Drawing Numbers**

| | |
|---------------------------|-------------------------------------|
| Application Specification | AS-76060-9999-001, AS-76850-990-001 |
| Packaging Specification | PK-70873-8024 |
| Product Specification | PS-45499-002-001, PS-76060-999-001 |
| Sales Drawing | SD-171576-0002 |

This document was generated on 12/05/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION