

Consumer Memory

Product Guide

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein is provided on an "AS IS" basis, without warranties of any kind.

This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppel or otherwise.


Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply.

For updates or additional information about Samsung products, contact your nearest Samsung office.

All brand names, trademarks and registered trademarks belong to their respective owners.

© 2010 Samsung Electronics Co., Ltd. All rights reserved.

1. CONSUMER MEMORY ORDERING INFORMATION



1. SAMSUNG Memory : K

2. DRAM : 4

3. Product

- S : SDRAM
- H : DDR SDRAM
- T : DDR2 SDRAM
- B : DDR3 SDRAM
- D : GDDR
- J : GDDR3

4. Density & Refresh

- 64 : 64Mb, 4K/64ms
- 28 : 128Mb, 4K/64ms
- 56 : 256Mb, 8K/64ms
- 51 : 512Mb, 8K/64ms
- 1G : 1Gb, 8K/64ms
- 2G : 2Gb, 8K/64ms
- 10 : 1Gb, 8K/32ms

5. Organization

- 04 : x4
- 08 : x8
- 16 : x16
- 32 : x32
- 31 : x32 (2CS)

6. Bank

- 2 : 2 Banks
- 3 : 4 Banks
- 4 : 8 Banks

7. Interface (VDD, VDDQ)

- 2 : LVTTTL (3.3V, 3.3V)
- 8 : SSTL_2 (2.5V, 2.5V)
- Q : SSTL_18 (1.8V, 1.8V)
- 6 : SSTL_15 (1.5V, 1.5V)
- K : POD_18 (1.8V, 1.8V)

8. Revision


- | | |
|--------------|---------------|
| M : 1st Gen. | H : 9th Gen. |
| A : 2nd Gen. | I : 10th Gen. |
| B : 3rd Gen. | J : 11th Gen. |
| C : 4th Gen. | K : 12th Gen. |
| D : 5th Gen. | L : 13th Gen. |
| E : 6th Gen. | N : 14th Gen. |
| F : 7th Gen. | O : 15th Gen. |
| G : 8th Gen. | S : 19th Gen. |

9. Package Type

- U : TSOP118 (Lead-free)
- U : 100TQFP(Lead-free) only for 128Mb GDDR
- Z : FBGA (Lead-free)
- V : 144FBGA (Lead-free) only for 128Mb GDDR
- L : TSOP118 (Lead-free & Halogen-free)
- H : FBGA (Lead-free & Halogen-free)
- F : FBGA(Lead-free & Halogen-free) for 64Mb DDR, 128Mb GDDR
- M : FBGA DDP (Lead-free & Halogen-free)
- B : FBGA FLIP-CHIP (Lead-free & Halogen-free)

10. Temperature & Power

- C : Commercial Temp. & Normal Power
- L : Commercial Temp. & Low Power
- I : Industrial Temp. & Normal Power
- P : Industrial Temp. & Low Power
- D : Industrial Temp. & Super Low Power
- Q : Commercial Temp. DDR3+ (Gapless, BL4)



11. Speed

- 75 : 7.5ns, PC133 (133MHz CL=3)
- 60 : 6.0ns (166MHz CL=3)
- 50 : 5.0ns (200MHz CL=3)
- 40 : 4.0ns (250MHz CL=3)
- B0 : DDR266 (133MHz @ CL=2.5, tRCD=3, tRP=3)
- B3 : DDR333 (166MHz @ CL=2.5, tRCD=3, tRP=3)
- CC : DDR400 (200MHz @ CL=3, tRCD=3, tRP=3)
- E6 : DDR2-667 (333MHz @ CL=5, tRCD=5, tRP=5)
- E7 : DDR2-800 (400MHz @ CL=5, tRCD=5, tRP=5)
- F7 : DDR2/3-800 (400MHz @ CL=6, tRCD=6, tRP=6)
- F8 : DDR2/3-1066 (533MHz @ CL=7, tRCD=7, tRP=7)
- H9 : DDR3-1333 (667MHz @ CL=9, tRCD=9, tRP=9)
- K0 : DDR3-1600 (800MHz @ CL=11, tRCD=11, tRP=11)
- 7A : GDDR3-2.6Gbps (0.77ns)
- 08 : GDDR3-2.4Gbps (0.8ns)
- 1A : GDDR3-2.0Gbps (1.0ns)
- 12 : GDDR3-1.6Gbps (1.25ns)
- 14 : GDDR3-1.4Gbps (1.4ns)

2. Commercial Temperature Consumer DRAM Component Product Guide

2.1 SDRAM

Density	Bank	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
64Mb N-die	4Banks	K4S640832N	LC(L)75	8M x 8	LVTTL	4K/64ms	3.3±0.3V	54pin TSOP(II)	Now
		K4S641632N	LC(L)50/C(L)60/C(L)75	4M x 16					
128Mb K-die	4Banks	K4S280832K	U ¹ C(L)75	16M x 8	LVTTL	4K/64ms	3.3±0.3V	54pin TSOP(II) ^{*1}	Now
		K4S281632K	UC(L)50/C(L)60/C(L)75	8M x 16					
128Mb O-die	4Banks	K4S280832O	LC(L)75	16M x 8	LVTTL	4K/64ms	3.3±0.3V	54pin TSOP(II)	3Q'10
		K4S281632O	LC(L)50/C(L)60/C(L)75	8M x 16					
256Mb J-die	4Banks	K4S560432J	U ¹ C(L)75	64M x 4	LVTTL	8K/64ms	3.3±0.3V	54pin TSOP(II) ^{*1}	Now
		K4S560832J	UC(L)75	32M x 8					
		K4S561632J	UC(L)60/C(L)75	16M x 16					
256Mb N-die	4Banks	K4S560432N	LC(L)75	64M x 4	LVTTL	8K/64ms	3.3±0.3V	54pin TSOP(II)	Now
		K4S560832N	LC(L)75	32M x 8					
		K4S561632N	LC(L)60/C(L)75	16M x 16					

NOTE : 1. 128Mb K-die SDR and 256Mb J-die SDR DRAMs support Lead-free & Halogen-free package with Lead-free package code(-U)

2.2 DDR SDRAM

Density	Bank	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
64Mb N-die	4Banks	K4H641638N	LC(L)CC	4M x 16	SSTL_2	4K/64m	2.5±0.2V	66pinTSOPII	Now
			FC(L)CC					60ball FBGA	
64Mb Q-die	4Banks	K4H641638Q	LC(L)CC	4M x 16	SSTL_2	4K/64m	2.5±0.2V	66pinTSOPII	2Q'10
128Mb L-die	4Banks	K4H281638L	LC(L)/C(L)CC	8M x 16	SSTL_2	4K/64m	2.5±0.2V ^{*1}	66pinTSOPII	Now
128Mb O-die	4Banks	K4H281638O	LC(L)CC/C(L)B3	8M x 16	SSTL_2	4K/64m	2.5±0.2V ^{*1}	66pinTSOPII	2Q'10
256Mb J-die	4Banks	K4H560438J	LC(L)B3/C(L)B0	64M x 4	SSTL_2	8K/64m	2.5±0.2V ^{*2}	66pinTSOPII	Now
		K4H560838J	LC(L)CC/C(L)B3	32M x 8					
		K4H561638J	LC(L)CC/C(L)B3	16M x 16					
256Mb N-die	4Banks	K4H560438N	LC(L)B3/C(L)B0	64M x 4	SSTL_2	8K/64m	2.5±0.2V ^{*2}	66pinTSOPII	Now
		K4H560838N	LC(L)CC/C(L)B3	32M x 8					
		K4H561638N	LC(L)CC/C(L)B3	16M x 16					
512Mb F-die	4Banks	K4H510438F	LC(L)B3/C(L)B0	128M x 4	SSTL_2	8K/64m	2.5±0.2V ^{*2}	66pinTSOPII	Now
			HC(L)CC/C(L)B3					60ball FBGA	
		K4H510838F	LC(L)CC/C(L)B3	64M x 8				66pinTSOPII	
			HC(L)CC/C(L)B3					60ball FBGA	
		K4H511638F	LC(L)CC/C(L)B3	32M x 16				66pinTSOPII	
			HC(L)CC/C(L)B3					60ball FBGA	
512Mb G-die	4Banks	K4H510438G	LC(L)B3/C(L)B0	128M x 4	SSTL_2	8K/64m	2.5±0.2V ^{*2}	66pinTSOPII	Now
			HC(L)CC/C(L)B3					60ball FBGA	
		K4H510838G	LC(L)CC/C(L)B3	64M x 8				66pinTSOPII	
			HC(L)CC/C(L)B3					60ball FBGA	
		K4H511638G	LC(L)CC/C(L)B3	32M x 16				66pinTSOPII	
			HC(L)CC/C(L)B3					60ball FBGA	

NOTE : 1. V_{DD}/V_{DDQ} SPEC for 128Mb DDR L-die

	DDR500	DDR400
V _{DD} /V _{DDQ}	2.5V ± 0.125V	2.5V ± 0.2V

2. V_{DD}/V_{DDQ} SPEC for 256/512Mb DDR

	DDR400	DDR333/266
V _{DD} /V _{DDQ}	2.6V ± 0.1V	2.5V ± 0.2V

2.3 DDR2 SDRAM

Density	Banks	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
128Mb O-die	4Banks	K4T28163QO	HCF8/E7/F7/E6	8M x 16	SSTL_18	4K/64m	1.8V±0.1V	84ball FBGA	Now
256Mb I-die	4Banks	K4T56163QI	Z ¹ C(L)E7/F7/E6/D5/CC	16M x 16	SSTL_18	8K/64m	1.8V±0.1V	84ball FBGA	Now
256Mb N-die	4Banks	K4T56163QN	HCF8/E7/F7/E6	16M x 16	SSTL_18	8K/64m	1.8V±0.1V	84ball FBGA	Now
512Mb G-die	4Banks	K4T51083QG	HC(L)F8/E7/F7/E6	64M x 8	SSTL_18	8K/64m	1.8V±0.1V	60ball FBGA	Now
		K4T51163QG	HC(L)F8/E7/F7/E6	32M x 16				84ball FBGA	
512Mb I-die	4Banks	K4T51043QI	HC(L)E7/F7/E6	128M x 4	SSTL_18	8K/64m	1.8V±0.1V	60ball FBGA	Now
		K4T51083QI	HC(L)E7/F7/E6	64M x 8				84ball FBGA	Now
		K4T51163QI	HC(L)F8/E7/F7/E6	32M x 16				84ball FBGA	Now
1Gb E-die	8Banks	K4T1G084QE	HC(L)F8/E7/F7/E6	128M x 8	SSTL_18	8K/64m	1.8V±0.1V	60ball FBGA	Now
		K4T1G164QE	HC(L)F8/E7/F7/E6	64M x 16				84ball FBGA	
1Gb F-die	8Banks	K4T1G084QF	BC(L)F8/E7/F7/E6	128M x 8	SSTL_18	8K/64m	1.8V±0.1V	60ball FBGA	Now
		K4T1G164QF	BC(L)F8/E7/F7/E6	64M x 16				84ball FBGA	

NOTE : 1. 128Mb I-die DDR2 84ball FBGA supports Halogen-free package

2.4 DDR3 SDRAM

Density	Banks	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	PKG	Avail.
1Gb E-die	8Banks	K4B1G0846E	HC(L)F7/F8/H9/K0	128M x 8	SSTL_15	8K/64m	1.5V±0.075V	78ball FBGA	Now
		K4B1G1646E	HC(L)F7/F8/H9/K0	64M x 16				96ball FBGA	
2Gb B-die	8Banks	K4B2G0846B	HC(L)F7/F8/H9/K0	256M x 8	SSTL_15	8K/64m	1.5V±0.075V	78ball FBGA	Now
		K4B2G1646B	HC(L)F7/F8/H9/K0	128M x 16				96ball FBGA	
2Gb C-die	8Banks	K4B2G0846C	HC(L)F8/H9/K0	256M x 8	SSTL_15	8K/64m	1.5V±0.075V	78ball FBGA	Now
		K4B2G1646C	HC(L)F8/H9/K0	128M x 16				96ball FBGA	

2.5 DDR3+ SDRAM

Density	Banks	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	PKG	Avail.
1Gb E-die	8Banks	K4B1G1646E	HQH9	64M x 16	SSTL_15	8K/64m	1.5V±0.075V	96ball FBGA	Now
2Gb C-die	8Banks	K4B2G1646C	HQH9	128M x 16	SSTL_15	8K/64m	1.5V±0.075V	96ball FBGA	Now

NOTE : For more details about product specifications or technical files, please contact us "semiconductor@samsung.com"

2.6 GDDR SDRAM

Density	Banks	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	PKG	Avail.
128Mb K-die	4Banks	K4D263238K	FC40/50	4M x 32	SSTL_2	4K/32m	2.5V±5%	Lead-free & Halogen-free 144ball FBGA	3Q. '10 EOL
			VC40/50					Lead-free 144ball FBGA	
			U ^{*1} C40/50					Lead-free & Halogen-free 100pin TQFP ^{*1}	

NOTE : 1. 128Mb K-die GDDR TQFP supports Lead-free & Halogen-free package with Lead-free package code(-U)

2.7 GDDR3 SDRAM

Density	Banks	Part Number	Package & Power, Temp. (-C/-L) & Speed	Org.	Interface	Refresh	Power (V)	PKG	Avail.
1Gb E-die	8Banks	K4J10324KE	HC7A/08/1A/12/14	32M x 32	SSTL_2	8K/32m	1.8V±0.1V	136ball FBGA	Now

3. Industrial Temperature Consumer DRAM Component Product Guide

3.1 SDRAM

Density	Bank	Part Number	Package & Power, Temp. & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
64Mb N-die	4Banks	KS641632N	LI(P)60I(P)75	4M x 16	LVTTTL	4K/64ms	3.3±0.3V	54pin TSOP(II)	Now
128Mb K-die	4Banks	K4S281632K	U ^{†1} I(P)60I(P)75	8M x 16	LVTTTL	4K/64ms	3.3±0.3V	54pin TSOP(II) ^{†1}	Now
128Mb O-die	4Banks	K4S281632O	LI(P)60I(P)75	8M x 16	LVTTTL	4K/64ms	3.3±0.3V	54pin TSOP(II)	3Q '10
256Mb J-die	4Banks	K4S561632J	U ^{†1} I(P)60I(P)75	16M x 16	LVTTTL	8K/64ms	3.3±0.3V	54pin TSOP(II) ^{†1}	Now
256Mb N-die	4Banks	K4S561632N	LI(P)60I(P)75	16M x 16	LVTTTL	8K/64ms	3.3±0.3V	54pin TSOP(II)	2Q '10

NOTE : 1. 128Mb K-die SDR and 256Mb J-die SDR DRAMs support Lead-free & Halogen-free package with Lead-free package code(-U)

3.2 DDR SDRAM

Density	Bank	Part Number	Package & Power, Temp. & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
512Mb F-die	4Banks	K4H510838F	LI(P)B3	64M x 8	SSTL_2	8K/64m	2.5±0.2V ^{†1}	66pinTSOPII	Now
		K4H511638F	LI(P)B3	32M x 16				66pinTSOPII	
			HI(P)B3					60ball FBGA	
512Mb G-die	4Banks	K4H511638G	LI(P)CC/B3	32M x 16	SSTL_2	8K/64m	2.5±0.2V ^{†1}	66pinTSOPII	Now
			HI(P)CC/B3					60ball FBGA	

NOTE : 1. V_{DD}/V_{DDQ} SPEC for 256/512Mb DDR

	DDR400	DDR333/266
V _{DD} /V _{DDQ}	2.6V ± 0.1V	2.5V ± 0.2V

3.3 DDR2 SDRAM

Density	Bank	Part Number	Package & Power, Temp. & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
512Mb G-die	4Banks	K4T51163QG	HI(P)F7I(P)E6I(P)D5/ I(P)CC	32M x 16	SSTL_18	8K/64m	1.8V±0.1V	84ball FBGA	Now
		K4T51163QG	HDE6						
512Mb I-die	4Banks	K4T51163QI	HI(P)E7I(P)F7I(P)E6	32M x 16	SSTL_18	8K/64m	1.8V±0.1V	84ball FBGA	Now
		K4T51163QI	HDE7/E6						
1Gb E-die	8Banks	K4T1G084QE	HI(P)F7I(P)E6	128M x 8	SSTL_18	8K/64m	1.8V ± 0.1V	60ball FBGA	Now
		K4T1G164QE	HI(P)F7I(P)E6	64M x 16				84ball FBGA	Now
1Gb F-die	8Banks	K4T1G084QF	BI(P)F7I(P)E6	128M x 8	SSTL_18	8K/64m	1.8V ± 0.1V	60ball FBGA	2Q '10
		K4T1G164QF	BI(P)F7I(P)E6	64M x 16				84ball FBGA	


3.4 DDR3 SDRAM

Density	Bank	Part Number	Package & Power, Temp. & Speed	Org.	Interface	Refresh	Power (V)	Package	Avail.
1Gb E-die	8Banks	K4B1G1646E	HI(P)H9	64M x 16	SSTL_15	8K/64m	1.5V±0.075V	96ball FBGA	Now
2Gb B-die	8Banks	K4B2G1646B	HI(P)H9	128M x 16	SSTL_15	8K/64m	1.5V±0.075V	96ball FBGA	Now
2Gb C-die	8Banks	K4B2G1646C	HI(P)H9	128M x 16	SSTL_15	8K/64m	1.5V±0.075V	96ball FBGA	2Q '10

4. Package Dimension


54Pin TSOP(II) (for SDRAM)

Units : Millimeters




66Pin TSOP(II) (for DDR)

Units : Millimeters




60Ball FBGA (For DDR 64Mb N-die)

Units : Millimeters




60Ball FBGA (For DDR 512Mb F-die, 512Mb G-die)

Units : Millimeters




60Ball FBGA (For DDR2 x8)

Units : Millimeters




84Ball FBGA (For DDR2 128Mb O-die/256Mb N-die/512Mb G-die, I-die/1Gb E-die)

Units : Millimeters




60Ball FBGA (for DDR2 1Gb F-die x8)

Units : Millimeters




84Ball FBGA (for DDR2 1Gb F-die x16)

Units : Millimeters




84Ball FBGA (For DDR2 256Mb I-die)

Units : Millimeters




78Ball FBGA (for DDR3 1Gb x8 E-die / DDR3 2Gb x8 C-die)

Units : Millimeters




96Ball FBGA (for DDR3 1Gb x16 E-die / DDR3+ 1Gb x16 E-die / DDR3 2Gb x16 C-die)

Units : Millimeters




78Ball FBGA (for DDR3 2Gb x8 B-die)

Units : Millimeters




96Ball FBGA (for DDR3 2Gb x16 B-die)

Units : Millimeters



136Ball FBGA (for GDDR3 1Gb E-die)

Units : Millimeters



For further information,

semiconductor@samsung.com