



**VOLTAGE RANGE: 20 - 100V**  
**CURRENT: 1.0 A**

### Features

- Schottky Barrier Chip
- Ideally Suited for Automatic Assembly
- Low Power Loss, High Efficiency
- For Use in Low Voltage Application
- Guard Ring Die Construction
- Plastic Case Material has UL Flammability Classification Rating 94V-O

### Mechanical Data

- Case: SMA/DO-214AC, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.064 grams (approx.)



SMA(DO-214AC)		
Dim	Min	Max
A	2.29	2.92
B	4.00	4.60
C	1.27	1.63
D	0.15	0.31
E	4.80	5.59
G	0.10	0.20
H	0.76	1.52
J	2.01	2.62
All Dimensions in mm		

### Maximum Ratings and Electrical Characteristics T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	B120A	B130A	B140A	B150A	B160A	B180A	B190A	B1100A	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>									V
Working Peak Reverse Voltage	V <sub>RWM</sub>	20	30	40	50	60	80	90	100	
DC Blocking Voltage	V <sub>R</sub>									
RMS Reverse Voltage	V <sub>R(RMS)</sub>	14	21	28	35	42	56	64	71	V
Average Rectified Output Current @T <sub>L</sub> = 75°C	I <sub>O</sub>	1.0								A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	30								A
Forward Voltage @I <sub>F</sub> = 1.0A	V <sub>FM</sub>	0.50			0.70		0.85			V
Peak Reverse Current @T <sub>A</sub> = 25°C At Rated DC Blocking Voltage @T <sub>A</sub> = 100°C	I <sub>RM</sub>	0.5 20								mA
Typical Thermal Resistance (Note 1)	R <sub>θJL</sub> R <sub>θJA</sub>	28 88								°C/W
Operating Temperature Range	T <sub>J</sub>	-65 to +125								°C
Storage Temperature Range	T <sub>STG</sub>	-65 to +150								°C

Note: 1. Mounted on P.C. Board with 5.0mm<sup>2</sup> copper pad area.

## RATINGS AND CHARACTERISTIC CURVES B120A THRU B1100A

