

**VOLTAGE RANGE: 8.0KV**  
**CURRENT: 60mA**

### Features

- High speed switching
- High Current
- High surge resistivity for CRT discharge
- High reliability design
- High Voltage

### Applications

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power



### Maximum Ratings and Electrical Characteristics T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbols	2CL2FF		Units
Repetitive Peak Reverse Voltage	V <sub>RRM</sub>	8		kV
Average Output Current T <sub>A</sub> =25°C, Resistive Load	I <sub>O</sub>	60		mA
Surge Current	I <sub>FSM</sub>	10		A
Maximum Forward Voltage Drop at 25°C, I <sub>F</sub> = I <sub>F(AV)</sub>	V <sub>F</sub>	16		V
Maximum Reverse Current at 25°C at 100°C	V <sub>RRM</sub>	2.0		uA
Maximum Reverse Recovery Time at 25°C	T <sub>rr</sub>	150		nS
Junction Capacitance at 25°C, V <sub>R</sub> =0V, f=1MHz	C <sub>j</sub>	15		pF
Junction Temperature	T <sub>j</sub>	125		°C
Allowable Operation Case Temperature	T <sub>c</sub>	125		°C
Storage Temperature	T <sub>stg</sub>	-40 to +125		°C

### Outline Drawings : mm

