



PC Board Layout
Component Side Shown

NOTES:
MATERIAL: 1. HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
2. CONTACT MATERIAL : PHOSPHOR BRONZE t=0.30mm.
3. PLATING : SELECTING GOLD PLATING 1u"~50u" OVER NICKEL IN CONTACT AREA. 150u" TIN PLATING OVER NICKEL IN SOLDER AREA

4. SHIELD : 0.20mm THICKNESS COPPER ALLY WITH NICKEL PLATE
ELECTRICAL: 1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 30 MILLIOHMS MAX.
4. INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC .
5. DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50Hz. 1MIN.

MECHANICAL: 1. DURRABILITY : 750 CYCLES MIN.
2. PCB RETENTION PRE-SOLDER : 1 LB MIN.
ENVIRONMENTAL: 1. STORAGE : -40° C TO 85° C.
2. OPERATION : 0° C TO 70° C.

电话(TEL) : 0755-84679842		http://www.minghui.com	
单位 (units)	MM	设计 (draw)	凌志成
比例 (scale)	1 : 1	审核 (ch'k)	朱建华
版次 (rev.)	A / 1	核准 (app'd)	朱建华
视图 (view)		日期 (date)	2008.08.12
		PIN	Qsn6, 5-0, 1
		材料 (mt'l)	UNIT:mm xxx +/-0.13
		图名 (name)	RJ45-180度插座 8P8C 双口屏蔽
深圳市铭辉电子有限公司 Shenzhen Minghui Electronic Co., Ltd		料号 (part number)	MHJ5222S-8P8C-1X2
		图档 (file Name)	E:\工程图