

贴片电阻选择指南

■ 通用贴片电阻

SERIES	SIZE/ mm	POWER RATING	MAX WORKING VOLTAGE	TOLERANCE	RESISTANCE RANGE
CR0402	0402 1.00*0.50	1/16W	50V	1%	1Ω-10MΩ
				5%	1Ω-10MΩ
CR0603	0603 1.60*0.80	1/10W	50V	0.5%	10Ω-1MΩ
				1%	1Ω-10MΩ
				5%	1Ω-22MΩ
CR0805	0805 2.00*1.25	1/8W	150V	0.5%	10Ω-1MΩ
				1%	1Ω-10MΩ
				5%	1Ω-22MΩ
CR1206	1206 3.10*1.60	1/4W	200V	0.5%	10Ω-1MΩ
				1%	1Ω-10MΩ
				5%	1Ω-22MΩ
CR1210	1210 3.10*2.50	1/2W	200V	1%	1Ω-10MΩ
				5%	1Ω-22MΩ
CR2010	2010 5.00*2.50	3/4W	200V	1%	1Ω-10MΩ
				5%	1Ω-22MΩ
CR2512	2512 6.25*3.10	1/W	200V	1%	1Ω-10MΩ
				5%	1Ω-22MΩ

■ 零欧姆电阻跳线

SERIES	SIZE	RATED CURRENT	TOLERANCE	RESISTANCE RANGE
CR0402	0402	1A	<0.05Ω	0Ω
CR0603	0603	1A		
CR0805	0805	1.5A		
CR1206	1206	1.9A		
CR1210	1210	2.2A		
CR2010	2010	3A		
CR2512	2512	3A		

■ 贴片电阻阵列

SERIES	SIZE/mm	POWER RATING	MAX WORKING VOLTAGE	TOLERANCE	RESISTANCE RANGE
CA022A	0404 1.00*1.00	1/16W	50V	1%	10Ω-1MΩ
				5%	1Ω-1MΩ
CA024A	0804 2.00*1.00	1/16W	50V	1%	10Ω-1MΩ
				5%	1Ω-1MΩ
CA034A	1206 3.20*1.50	1/10W	50V	1%	10Ω-1MΩ
				5%	1Ω-1MΩ



型号

贴片电阻、贴片电阻阵列

CR	0805	J	8	0472	G
产品系列 CR: 贴片电阻 CA: 贴片电阻阵列	Size Code 0402 0603 0805 1206 1210 2010 2512 022A: 0402x2 024A: 0402x4 034A: 0603x4	Tolerance B: $\pm 0.1\%$ C: $\pm 0.25\%$ D: $\pm 0.5\%$ F: $\pm 1\%$ G: $\pm 2\%$ J: $\pm 5\%$ K: $\pm 10\%$ O: 0 Ω Jumper	Power Rating 1: 1W 2: 1/2W 3: 1/3W 4: 1/4W 8: 1/8W A: 1/10W F: 1/16W H: 1/32W -: Ignore	Resistance Value 49R9=49.9 0472=4K7 0103=10K 0564=560K	Special Code G: Reel V: Bulk D: Special Req