

Shielded Power Inductors—MSS1260



- 12.3 × 12.3 mm footprint; 6 mm high shielded inductors
- Low DCR and excellent current handling

Designer's Kit C360 contains 3 each of all values.

Core material Ferrite

Core and winding loss See www.coilcraft.com/coreloss

Terminations RoHS compliant matte tin over nickel over phos bronze. Other terminations available at additional cost.

Weight: 2.8–3.3 g

Ambient temperature –40°C to +85°C with (40°C rise) Irms current.

Maximum part temperature +125°C (ambient + temp rise). [Derating](#).

Storage temperature Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Failures in Time (FIT) / Mean Time Between Failures (MTBF)

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

Packaging 500/13" reel; Plastic tape: 24 mm wide, 0.35 mm thick, 16 mm pocket spacing, 6.3 mm pocket depth

PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787_PCB_Washing.pdf](#).

Part number ¹	Inductance ² (μH)	DCR ³ (mOhms)		SRF typ ⁴ (MHz)	Isat (A) ⁵			Irms (A) ⁶	
		typ	max		10% drop	20% drop	30% drop	20°C rise	40°C rise
MSS1260-102NL	1.0±30%	5.8	6.5	100	19.1	21.4	22.7	6.00	8.00
MSS1260-152NL	1.5±30%	8.8	9.8	80.0	15.0	16.6	17.6	6.00	7.50
MSS1260-222NL	2.2±30%	11.5	12.8	55.0	11.7	13.0	13.9	5.50	7.00
MSS1260-332NL	3.3±30%	12.6	14.0	42.0	10.4	11.7	12.5	5.00	7.00
MSS1260-472ML	4.7±20%	13.9	15.5	33.0	9.22	10.1	10.8	4.50	7.00
MSS1260-562ML	5.6±20%	14.9	16.6	30.0	7.86	9.02	9.74	4.00	6.40
MSS1260-682ML	6.8±20%	16.6	18.5	27.0	7.40	8.26	8.80	3.80	5.90
MSS1260-822ML	8.2±20%	17.0	20.0	26.0	7.10	7.96	8.50	3.40	4.80
MSS1260-103ML	10±20%	21.5	23.9	22.0	6.18	6.92	7.40	3.00	4.00
MSS1260-123ML	12±20%	24.5	27.3	20.0	5.18	5.94	6.42	2.80	3.70
MSS1260-153ML	15±20%	27.0	32.0	18.0	4.80	5.40	5.78	2.60	3.50
MSS1260-183ML	18±20%	30.0	33.0	16.0	4.58	5.22	5.62	2.50	3.30
MSS1260-223ML	22±20%	36.6	40.7	15.0	4.06	4.64	4.96	2.30	3.10
MSS1260-273ML	27±20%	48.0	52.0	13.0	3.52	3.96	4.28	2.10	2.90
MSS1260-333ML	33±20%	54.0	57.0	12.4	3.22	3.74	4.02	2.00	2.70
MSS1260-393ML	39±20%	58.0	64.5	12.0	3.08	3.56	3.80	1.90	2.60
MSS1260-473ML	47±20%	75.0	82.0	11.6	2.66	3.04	3.30	1.85	2.50
MSS1260-563ML	56±20%	85.0	89.0	10.5	2.54	2.96	3.14	1.75	2.40
MSS1260-683ML	68±20%	94.5	105	10.0	2.40	2.70	2.94	1.70	2.30
MSS1260-823ML	82±20%	120	129	8.6	2.16	2.46	2.64	1.60	2.20
MSS1260-104ML	100±20%	139	146	7.8	1.88	2.16	2.32	1.50	2.10
MSS1260-124KL	120±10%	193	195	6.8	1.70	1.92	2.10	1.38	1.85
MSS1260-154KL	150±10%	209	216	6.4	1.58	1.80	1.98	1.20	1.66
MSS1260-184KL	180±10%	234	246	6.1	1.40	1.60	1.72	1.14	1.58
MSS1260-224KL	220±10%	306	335	5.5	1.28	1.44	1.56	1.00	1.42
MSS1260-274KL	270±10%	349	355	4.3	1.10	1.26	1.38	0.90	1.45
MSS1260-334KL	330±10%	482	494	4.0	1.00	1.14	1.24	0.84	1.16
MSS1260-394KL	390±10%	515	533	3.6	0.93	1.06	1.15	0.78	1.08
MSS1260-474KL	470±10%	705	733	3.0	0.87	0.99	1.06	0.70	0.96
MSS1260-564KL	560±10%	776	800	2.8	0.81	0.92	1.00	0.64	0.88
MSS1260-684KL	680±10%	887	910	2.6	0.74	0.85	0.92	0.58	0.80
MSS1260-824KL	820±10%	1130	1152	2.5	0.66	0.76	0.81	0.53	0.73
MSS1260-105KL	1000±10%	1295	1335	2.4	0.60	0.69	0.74	0.48	0.68

- Please specify **termination** and **packaging** codes:

MSS1260-184KLD

Termination: L=RoHS compliant matte tin over nickel over phos bronze.
Special order:
T=RoHS tin-silver-copper (95.5/4/0.5) or S=non-RoHS tin-lead (63/37).

Packaging: D=13" machine-ready reel. EIA-481 embossed plastic tape (500 parts per full reel).

B=Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter D instead.

- Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc using an Agilent/HP 4263B LCR meter or equivalent.
 - DCR measured on a micro-ohmmeter and a Coilcraft CCF858 test fixture.
 - SRF measured using Agilent/HP 4191A or equivalent.
 - DC current at 25°C that causes the specified inductance drop from its value without current. [Click for temperature derating information.](#)
 - Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)
 - Electrical specifications at 25°C.
- Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

SPICE models ON OUR WEB SITE



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com
UK +44-1236-730595 sales@coilcraft-europe.com
Taiwan +886-2-2264 3646 sales@coilcraft.com.tw
China +86-21-6218 8074 sales@coilcraft.com.cn
Singapore + 65-6484 8412 sales@coilcraft.com.sg

Document 281-1 Revised 09/02/15


© Coilcraft Inc. 2015

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





Shielded Power Inductors – MSS1260

Typical L vs Current



Typical L vs Frequency



* For optional tin-lead and tin-silver-copper terminations, dimensions are for the mounted part. Dimensions before mounting can be an additional 0.012 inch (0.3 mm).

Dimensions are in $\frac{\text{inches}}{\text{mm}}$

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Coilcraft:

[MSS1260-684KLD](#) [MSS1260-124KLB](#) [MSS1260-332NLB](#) [MSS1260-184KLB](#) [MSS1260-224KLD](#) [MSS1260-564KLB](#)
[MSS1260-273MLB](#) [MSS1260-824KLD](#) [MSS1260-394KLB](#) [MSS1260-822MLB](#) [MSS1260-473MLB](#) [MSS1260-](#)
[472MLD](#) [MSS1260-472MLB](#) [MSS1260-683MLB](#) [MSS1260-103MLD](#) [MSS1260-183MLD](#) [MSS1260-563MLD](#)
[MSS1260-682MLD](#) [MSS1260-103MLB](#) [MSS1260-823MLD](#) [MSS1260-153MLB](#) [MSS1260-223MLB](#) [MSS1260-334KLB](#)
[MSS1260-104MLD](#) [MSS1260-562MLD](#) [MSS1260-154KLD](#) [MSS1260-123MLB](#) [MSS1260-183MLB](#) [MSS1260-](#)
[684KLB](#) [MSS1260-474KLD](#) [MSS1260-102NLD](#) [MSS1260-562MLB](#) [MSS1260-333MLB](#) [MSS1260-394KLD](#)
[MSS1260-153MLD](#) [MSS1260-274KLD](#) [MSS1260-393MLD](#) [MSS1260-222NLD](#) [MSS1260-152NLB](#) [MSS1260-563MLB](#)
[MSS1260-223MLD](#) [MSS1260-123MLD](#) [MSS1260-474KLB](#) [MSS1260-273MLD](#) [MSS1260-473MLD](#) [MSS1260-](#)
[224KLB](#) [MSS1260-824KLB](#) [MSS1260-393MLB](#) [MSS1260-105KLB](#) [MSS1260-104MLB](#) [MSS1260-102NLB](#)
[MSS1260-222NLB](#) [MSS1260-152NLD](#) [MSS1260-184KLD](#) [MSS1260-332NLD](#) [MSS1260-124KLD](#) [MSS1260-334KLD](#)
[MSS1260-683MLD](#) [MSS1260-822MLD](#) [MSS1260-274KLB](#) [MSS1260-105KLD](#) [MSS1260-564KLD](#) [MSS1260-](#)
[333MLD](#) [MSS1260-682MLB](#) [MSS1260-823MLB](#) [MSS1260-154KLB](#)