

# 8000 series

## Momentary or alternate action pushbutton switches

*Distinctive features and specifications*

UG1410A



Bushing  $\varnothing$  6,35 (1/4) and  $\varnothing$  11,9 (15/32)

UL approved

### ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :
  - silver contacts : 4A 30VDC
  - gold plated contacts : 0,4VA max. 20VAC or DC
- Initial contact resistance : 10 m $\Omega$  max.
- Insulation resistance : 1.000 M $\Omega$  min. at 500VDC
- Dielectric strength :
  - 1.000 Vrms 50 Hz min. between terminals
  - 2.000 Vrms 50 Hz min. between terminals and frame
- Electrical life : 30.000 cycles at full load

### MATERIALS

- Case : diallylphthalate (DAP)
- Actuator : brass, nickel plated
- Bushing : brass, nickel plated
- Housing : stainless steel
- Contacts
  - A** : silver
  - AD** : silver, gold plated
  - CD** : brass, gold plated
- Terminal seal : epoxy

### GENERAL SPECIFICATIONS

- Torque : 1,25 Nm (.922 Ft.lb) max. applied to nut
- Total travel : 2,70 mm (.106)
- Operating temperature : -40°C to +85°C

### AGENCY APPROVAL

 3A 250VAC, 6A 125VAC


**Availability** : consult factory for details of approved models.

**Marking** : to order switches marked UL, complete appropriate box of ordering format.

# 8000 series

## Momentary or alternate action pushbutton switches

Overview



B2

### ABOUT THIS SERIES

On the following pages, you will find successively :

- model structure of switches
- options in the same order as in above chart

**Dimensions** : first dimensions are in mm while inches are shown as bracketed numbers.



**Sealing boots** are available to protect the switches against dust and water. They are presented in section H.



**Mounting accessories** : standard hardware supplied with all models : 2 hex nuts 8 mm (.314) across flats, 1 locking ring and 1 lockwasher.  
Standard and special hardware available are presented in section I.





**Packaging unit** : 50 pieces, except 8000W (25 pieces).


# 8000 series

## Momentary or alternate action pushbutton switches


Threaded bushing  $\varnothing 6,35 (1/4)$



- Solder lug, straight PC or right angle terminals
- 1 and 2 pole configurations
- Button returns in upper position after actuation.



### MODEL STRUCTURE





Shown with standard plunger

### Solder lug terminals : 8600



Single pole  
**8632**  
**8636**

Double pole  
**8642**  
**8646**





### Straight PC terminals : 8400



Single pole  
**8432**  
**8436**

Double pole  
**8442**  
**8446**





### Right angle terminals - horizontal : 8400W



Single pole  
**8432W**  
**8436W**


Double pole  
**8442W**  
**8446W**





# 8000 series

## Momentary or alternate action pushbutton switches



### CONTACT MATERIALS




- A** Silver
- AD** Silver, gold plated
- CD** Brass, gold plated

### SEALING



- Blank** No sealing
  - B** Epoxy sealed terminals
  - K** Front panel sealing by one O-ring and sealing washer. Protects the switch against water and dust. Panel seal withstands 1 bar pressure.
  - KB** Combined sealings
- Sealing boot : see section H.



- ① O-ring
- ② Sealing washer

# 8000 series

## Momentary or alternate action pushbutton switches




### PLUNGERS




For  $\varnothing 6,35$  (1/4) bushing

Dash compulsory before plunger code.




Blank

Standard




-9

For  $\varnothing 11,9$  (15/32) bushing (X718 models)




Blank



-6


### SPECIAL OPTIONS



**X601 Silver plated brass contacts**

Current/voltage rating for an electrical life of 20.000 cycles : 0,5A 30VDC.  
Minimum quantity : 5.000 pieces per model and shipment.


**X718 Bushing  $\varnothing 11,9$  (15/32)**  
For all basic models (solder lug straight PC or right angle terminals)  
Available with plungers 13 and 6.  
K sealing option available.



**X718**

**X748 Snap-in mounting.** Consult factory  
Panel cut-out 15 x 12,5 (.59 x .492)

**X934 Flatted bushing  $\varnothing 11,9$  (15/32) + sealing by two O-rings**  
(for plunger -6 only). Epoxy sealed terminals.




**X934**



# 8000 series

## Momentary or alternate action pushbutton switches

### APPROVAL







### UL

**Availability** : consult factory for details of approved models.  
**Marking** : to order switches marked UL, complete above box with "UL".


### CAPS

Order separately.


The caps below are for Ø 4 mm plungers (standard and -9), except U2600.




Standard




Cap colours	
Replace last "0" by number	
1	blue
1/4	dark blue
2	black
3	green
4	grey
5	yellow
6	red
7	ivory
7/1	white
9	orange



Square




Square




For large plunger -6 only.

### DRESS NUTS


Chrome plated. Order separately.



For cap U1140



For cap U630



For cap U480