



Electrical Data:

Current rating: 3A
 Dielectric Withstanding Voltage: 1000V AC for one minute
 Contact Resistance: < 20 mΩ
 Insulation Resistance: > 1000 MΩ
 Operating Temperature: -40°C ~ +105°C

Construction:

Insulator: Black Glass Filled Polyester
 Flammability Rating: UL 94V-0
 Contacts: Phosphor Bronze of copper alloy
 Contacts plating: Selective gold on surface contact area
 □四方针的规格: 0.64x11.6mm

301 NN 0 1 XX X 0

Pitch:(Unit:mm)

- 1-2.54x2.54, 2-2.00x2.00
- 3-1.27x1.27, 4-1.27x2.54

Number of Contact:

- 10 ~ 64 PIN

Type of terminations:

- 1 - Straight DIP Type
- 2 - Right Angle RA Type
- 3 - S.M.T Type
- 5 - Flat Cable-IDC Type / IDC

Insulator Color:

- 1-Black 2-Grey 3-White
- 4-Blue 5-Red 6-Yellow

Insulator Material:

- 0-PPS 1-PBT 2-LCP
- 3-PA46 5-PA6T 6-PA9T

Contact Plated:

- 0-Tin 1-Gold Flash 2-Gold 3u"
- 3-Gold 5u" 4-Gold 10u" 5-Gold 15u"
- 6-Gold 30u" A-Gold 0.8u"



联益康电子内部文件
未经许可，不得影印

E		Units	mm	Scale	2:1	Drawing By	Date	Leyconn 深圳市联益康电子有限公司		TEL:+86-755-26078616 FAX:26070522
D		Tolerance Unless otherwise Specified				LLIU	2011/08/16	Http://www.leyconn.com		
C		.X ~ ±0.30				Reviewed By	Date	Date	2011/08/16	BOX Header Connector
B		.XX ~ ±0.25				Sandy	2011/08/16	Sheet	1 of 1	Pitch:2.54mm DIP Type
A	RELEASED	.XXX ~ ±0.20				Approval By	Date	Third Angle Projection		Drawing No. 301NN01XXX0
REV	ECN.NO.	Angle ~ ±3°				Jon Chuo	2011/08/16	⊕		F/Name