











Contents

YAGEO *Phycomp*

	Multilayer Ceramic Chip Capacitors	04
	SMD Ceramic EMI Filter Capacitors - X2Y®	05
	Chip Resistors	06
	Arrays	06-07
	Network	08
	Application Specific Resistors	08
	Chip Resistors RF Attenuator	08
	High Frequency Antenna	09-12
	High Frequency Filter	12-13
	High Frequency Combo	13
	High Frequency Balun	13-14
	High Frequency Diplexer	14
	MLV	15
YAGEO		
	Aluminum Electrolytic Capacitors	16-18
	Leaded Resistors	19-23
	SMD Chip Beads	24
	SMD Multilayer Chip Inductors	24-25
	SMD Wire Wound Chip Inductors	25-27
	SMD Power Inductors	27-28
	DIP Power Inductors	28-29
	Global Directory	30-31





MLCC

NP0 Ceramic Chips Series

GENERAL PURPOSE
MEDIUM VOLTAGE
HIGH VOLTAGE
MICROWAVE
Surface Mount Chip



Size _ 0201 to 1812
Capacitance Range _ 0.22pF to 33nF
Capacitance Tolerance _
C < 10pF: 0.1pF, 0.25pF, 0.5pF
C ≥ 10pF: ±1%, ±2%, ±5%

Rated Working Voltage _ 16Vdc to 4,000Vdc
Operating Temp. Range _ -55°C to +125°C
Packaging _ Reel, Bulk

X5R Ceramic Chips Series

GENERAL PURPOSE
MEDIUM VOLTAGE
HIGH CAPACITANCE
Surface Mount Chip



Size _ 0201 to 1812
Capacitance Range _ 10nF to 100µF
Capacitance Tolerance _ ±10%, ±20%

Rated Working Voltage _ 6.3Vdc to 25Vdc
Operating Temp. Range _ -55°C to +85°C
Packaging _ Reel, Bulk

X7R Ceramic Chips Series

GENERAL PURPOSE
MEDIUM VOLTAGE
HIGH VOLTAGE
LOW INDUCTANCE
HIGH CAPACITANCE
Surface Mount Chip



Size _ 0201 to 1812
Capacitance Range _ 100pF to 22µF
Capacitance Tolerance _ ±5%, ±10%, ±20%

Rated Working Voltage _
6.3Vdc to 3,000Vdc
Operating Temp. Range _ -55°C to +125°C
Packaging _ Reel, Bulk

Y5V Ceramic Chips Series

GENERAL PURPOSE
HIGH CAPACITANCE
Surface Mount Chip



Size _ 0201 to 1210
Capacitance Range _ 10nF to 47µF
Capacitance Tolerance _ ±20%, -20% to +80%

Rated Working Voltage _ 6.3Vdc, 50Vdc
Operating Temp. Range _ -25°C to +85°C
Packaging _ Reel, Bulk

Arrays Series

NP0, X7R, Y5V CERAMIC CHIPS
MULTI-VALUE CAPACITORS ARRAY
Surface Mount Chip



Size _ 0405, 0508, 0612
Capacitance Range _ 10pF to 100nF
Capacitance Tolerance _
NP0: ±5%, ±10%
X7R: ±10%, ±20%
Y5V: -20% to +80%

Rated Working Voltage _ 16Vdc to 50Vdc
Packaging _ Reel

Safety Certification Series

NP0, X7R CERAMIC CHIPS
Surface Mount Chip



Size _ 1808 to 1812
Capacitance Range _ 2pF to 1.5nF
Capacitance Tolerance _
NP0: ±5%
X7R: ±10%

Rated Working Voltage _ X1 / Y2, X2 / Y3
Operating Temp. Range _ -55°C to +125°C
Packaging _ Reel, Bulk

High Frequency Series

NP0 CERAMIC CHIPS
Surface Mount Chip



Size _ 0402 to 0603
Capacitance Range _ 0.22pF to 47pF
Capacitance Tolerance _
C < 10pF: ±0.1pF, ±0.25pF, ±0.5pF
C = 10pF: ±1%, ±2%, ±5%

Rated Working Voltage _ 50Vdc
Operating Temp. Range _ -55°C to +125°C
Packaging _ Reel



X2Y

X5R X2Y Series

HIGH CAPACITANCE
Surface Mount Chip



Size _ 0603
Capacitance Range _ 220nF to 470nF
Capacitance Tolerance _ $\pm 20\%$
Insulation Resistance _
 $R_{ins} \times C > 500\text{sec}$ or $R_{ins} > 10\text{G}\Omega$

Rated Working Voltage _ 6Vdc, 10Vdc
Operating Temp. Range _ -55°C to $+85^\circ\text{C}$
Packaging _ Reel

X7R X2Y Series

GENERAL PURPOSE
Surface Mount Chip



Size _ 0603 to 1410
Capacitance Range _ 1nF to 1 μF
Capacitance Tolerance _ $\pm 20\%$
Insulation Resistance _
 $R_{ins} \times C > 500\text{sec}$ or $R_{ins} > 10\text{G}\Omega$

Rated Working Voltage _ 10Vdc to 100Vdc
Operating Temp. Range _ -55°C to $+125^\circ\text{C}$
Packaging _ Reel


NP0 X2Y Series

GENERAL PURPOSE
Surface Mount Chip



Size _ 0805
Capacitance Range _ 22pF and 47pF
Capacitance Tolerance _ $\pm 20\%$
Insulation Resistance _
 $R_{ins} \times C > 500\text{sec}$ or $R_{ins} > 10\text{G}\Omega$

Rated Working Voltage _ 53Vdc, 63Vdc
Operating Temp. Range _ -55°C to $+125^\circ\text{C}$
Packaging _ Reel



Chip Resistors

General Purpose

RC SERIES
THICK FILM CHIP



Case Sizes _ 01005 to 2512
Resistance Range (E24/E96) _ 1Ω to 100MΩ / Jumper
Rated Power @ 70°C _ 1/32W to 2W
Temp. Coefficient _
±100, ±200, ±250, ±300, ± 350ppm/°C

Resistance Tolerance _
±0.5%, ±1%, ±5%, ±10%, ±20%
Max. Working Voltage _ 15Vdc to 200Vdc
Max. Overload Voltage _ 30Vdc to 500Vdc
Packaging _ Reel, Bulk

Precision Grade Series

RE SERIES
THICK FILM CHIP



Case Sizes _ 0402 to 1206
Resistance Range (E24/E96) _ 10Ω to 1MΩ
Rated Power @ 70°C _ 1/16W to 1/4W
Temp. Coefficient _ ±50ppm/°C

Resistance Tolerance _ ±0.5%, ±1%
Packaging _ Reel

Low Ohmic

RL SERIES
THICK FILM CHIP
Current Sensing Applications



Case Sizes _ 0402 to 2512
Resistance Range (E24) _ 0.01Ω to 1Ω
Rated Power @ 70°C _ 1/16W to 1W
Temp. Coefficient _ 200ppm/°C to 1,500ppm/°C

Resistance Tolerance _ ±1%, ±2%, ±5%
Packaging _ Reel

Current Sensor Low TCR

PR / PF / PH / PT SERIES
METAL TECHNOLOGY
Current Sensing Applications



Case Sizes _ 0402 to 2512
Resistance Range (E24) _ 0.001Ω to 0.91Ω
Rated Power @ 70°C _ 1/16W to 2W
Temp. Coefficient _ ±75, ±100, ±150, ±200ppm/°C

Resistance Tolerance _ ±1%, ±2%, ±5%
Packaging _ Reel

High Precision High Stability Series

RT SERIES
THIN FILM CHIP



Case Sizes _ 0402 to 2512
Resistance Range (E24/E96) _ 5.1Ω to 1.5MΩ
Rated Power @ 70°C _ 1/16W to 3/4W
Temp. Coefficient _ ±10, ±15, ±25, ±50ppm/°C

Resistance Tolerance _
±0.05%, ±0.1%, ±0.25%, ±0.5%, ±1%
Max. Working Voltage _ 50Vdc to 200Vdc
Max. Overload Voltage _ 100Vdc to 400Vdc
Packaging _ Reel

General Purpose Thin Film Series

RJ SERIES
THIN FILM CHIP



Case Sizes _ 0402 to 2512
Resistance Range (E24/E96) _ 5.1Ω to 1.5MΩ
Rated Power @ 70°C _ 1/16W to 3/4W
Temp. Coefficient _ ±50ppm/°C

Resistance Tolerance _ ±1%
Max. Working Voltage _ 25Vdc to 150Vdc
Max. Overload Voltage _ 100Vdc to 400Vdc
Packaging _ Reel

Arrays

0201 * 2 Series

YC102 SERIES
THICK FILM ARRAY
Convex 0202



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 1MΩ / Jumper
Number of Resistance _ 2
Rated Power Per Element _ 1/32W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 15Vdc
Max. Overload Voltage _ 30Vdc
Packaging _ Reel

0402 * 2 Series 0402 * 4 Series

YC122 SERIES
YC124 SERIES
THICK FILM ARRAY
Convex 0404 / 0408



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 1Ω to 1MΩ / Jumper
Number of Resistance _ 2 and 4
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 50Vdc
Max. Overload Voltage _ 100Vdc
Packaging _ Reel



Arrays

0402 * 2 Series 0402 * 4 Series

TC122 SERIES
TC124 SERIES
THICK FILM ARRAY
Concave 0404 / 0408



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 1MΩ / Jumper
Number of Resistance _ 2 and 4
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 50Vdc
Max. Overload Voltage _ 100Vdc
Packaging _ Reel

0603 * 2 Series

YC162 SERIES
THICK FILM ARRAY
Convex 0606



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 1MΩ / Jumper
Number of Resistance _ 2
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±5%
Max. Working Voltage _ 50Vdc
Max. Overload Voltage _ 100Vdc
Packaging _ Reel

0603 * 4 Series

YC164 SERIES
THICK FILM ARRAY
Convex 0612



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 1Ω to 1MΩ / Jumper
Number of Resistance _ 4
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 50Vdc
Max. Overload Voltage _ 100Vdc
Packaging _ Reel

0603 * 4 Series

TC164 SERIES
THICK FILM ARRAY
Concave 0612



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 1MΩ / Jumper
Number of Resistance _ 4
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 50Vdc
Max. Overload Voltage _ 100Vdc
Packaging _ Reel

0603 * 4 Series

TA164 SERIES
THIN FILM ARRAY
Convex 0612



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 330KΩ
Number of Resistance _ 4
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±25, ±50ppm/°C

Resistance Tolerance _ ±0.1%, ±0.5%, ±1%
Max. Working Voltage _ 75Vdc
Max. Overload Voltage _ 150Vdc
Packaging _ Reel

0603 * 4 Series

TD164 SERIES
THIN FILM MULTI VALUE
Convex 0612



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 330KΩ
Number of Resistance _ 4
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±25, ±50ppm/°C

Resistance Tolerance _ ±0.1%, ±0.5%, ±1%
Max. Working Voltage _ 75Vdc
Max. Overload Voltage _ 150Vdc
Packaging _ Reel

0602 * 8 Series

YC248 SERIES
THICK FILM ARRAY
Convex 0616



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 1MΩ / Jumper
Number of Resistors _ 8
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 50Vdc
Max. Overload Voltage _ 100Vdc
Packaging _ Reel

1206 * 4 Series

YC324 SERIES
THICK FILM ARRAY
Convex 2012



Circuit Types _ Isolated
Resistance Range (E24/E96) _ 10Ω to 1MΩ
Number of Resistors _ 4
Rated Power Per Element _ 1/8W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 200Vdc
Max. Overload Voltage _ 500Vdc
Packaging _ Reel



Network

10P8R Series

YC158 SERIES
YC358 SERIES
THICK FILM ARRAY
Convex 0612 / 1225



Circuit Types _ Dual Common
Resistance Range (E24) _ 10Ω to 330KΩ
Number of Resistors _ 8
Rated Power Per Element _ 1/16W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±5%
Max. Working Voltage _ 25Vdc to 50Vdc
Max. Overload Voltage _ 50Vdc to 100Vdc
Packaging _ Reel

Application
Specific Resistors

NiAu-termination Series

AR SERIES
THICK FILM CHIP



Case Sizes _ 0402 to 1206
Resistance Range (E24) _ 1Ω to 10M / Jumper
Rated Power @ 70°C _ 1/16W to 1/4W
Temp. Coefficient _ ±100, ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 50Vdc to 200Vdc
Max. Overload Voltage _ 100Vdc to 500Vdc
Packaging _ Reel

High Voltage Series

RV SERIES
THICK FILM CHIP



Case Sizes _ 0805, 1206, 2512
Resistance Range (E24) _ 100KΩ to 27MΩ
Rated Power @ 70°C _ 1/8W to 1W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±1%, ±5%
Max. Working Voltage _ 400Vdc to 500Vdc
Max. Overload Voltage _ 800Vdc to 1,000Vdc
Packaging _ Reel

Trimmable Series

TR SERIES
THICK FILM CHIP



Case Sizes _ 0402 to 1206
Resistance Range (E24) _ 1Ω to 10MΩ
Rated Power @ 70°C _ 1/16W to 1/4W
Temp. Coefficient _ ±100, ±200ppm/°C

Resistance Tolerance _
0/-10%, 0/-20%, 0/-30%
Max. Working Voltage _ 50Vdc to 200Vdc
Max. Overload Voltage _ 100Vdc to 500Vdc
Packaging _ Reel

Surge Series

SR SERIES
THICK FILM CHIP




Case Sizes _ 0805 to 2512
Resistance Range (E24) _ 1Ω to 100KΩ
Rated Power @ 70°C _ 1/8W to 1W
Temp. Coefficient _ ±200ppm/°C

Resistance Tolerance _ ±5%, ±10%, ±20%
Max. Working Voltage _ 150Vdc to 200Vdc
Max. Overload Voltage _ 300Vdc to 400Vdc
Packaging _ Reel

Chip Resistors
RF Attenuator


Attenuator

ATV321 SERIES
THICK FILM CHIP



Case Size _ 0404
Attenuation Range _ 1DB to 20DB
Attenuation Tolerance _ 1DB to 5DB: ±0.3dB
6DB to 10DB: ±0.5dB
15DB: ±1dB
20DB: ±2dB

Frequency Range _
1DB to 10DB: DC to 2.5GHz
15DB and 20DB: DC to 2.0GHz
Max. Permissible Voltage _ 50V
Power Rating _ 40mW
Temp. Range _ -55°C to +125°C
Packaging _ Reel



High Frequency
Antenna

Ceramic Antenna

UHF



Size (mm) _ 37.5 x 6.8 x 0.9
Frequency Range* _ 400MHz to 500MHz
Band Width _ > 20MHz
Gain (Max.)* _ 0.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.0
Temp. Range _ -55°C to +125°C
Packaging _ Bulk

Ceramic Antenna

UHF




Size (mm) _ 4 x 12 x 1.5
Frequency Range* _ 400MHz to 500MHz
Band Width _ > 20MHz
Gain (Max.)* _ 0.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 3.0
Temp. Range _ -40°C to +125°C
Packaging _ Reel

Ceramic Antenna

TDMA



Size (mm) _ 16.5 x 14 x 0.9
Frequency Range* _ 850MHz to 950MHz
Band Width _ > 100MHz
Gain (Max.)* _ 1.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.0
Temp. Range _ -55°C to +125°C
Packaging _ Bulk, Reel

Ceramic Antenna

TDMA



Size (mm) _ 12 x 4 x 0.9
Frequency Range* _ 850MHz to 950MHz
Band Width _ > 20MHz
Gain (Max.)* _ 0.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.0
Temp. Range _ -55°C to +125°C
Packaging _ Reel

Ceramic Antenna

DUAL BAND
900 / 1800 MHz



Size (mm) _ 21 x 12 x 0.9
Frequency Range* _ 880MHz to 960MHz, 1,710MHz to 1,880MHz
Band Width _ > 30MHz, > 170MHz
Gain (Max.)* _ 0.5dB to 1dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.7
Temp. Range _ -55°C to +125°C
Packaging _ Bulk

Ceramic Antenna

DUAL BAND
2.45 / 5.2 GHz



Size (mm) _ 8.7 x 8.0 x 0.9
Frequency Range* _ 2.45 / 5.20 GHz
Band Width _ > 100MHz
Gain (Max.)* _ 3.5dB / 1.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.5
Temp. Range _ -55°C to +85°C
Packaging _ Reel

Tripleband Antenna

PCB VERTICAL
900 / 1800 / 1900 MHz



Size (mm) _ 30 x 9.4 x 0.8
Frequency Range* _ 880MHz to 960MHz, 1,710MHz to 1,880MHz
Band Width _ > 80MHz, > 280MHz
Gain (Max.)* _ 1dB to 1.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.5
Temp. Range _ -55°C to +125°C
Packaging _ Bulk

Tripleband Antenna

WITH CABLE & CONNECTOR
900 / 1800 / 1900 MHz



Size (mm) _ 35 x 6.0 x 0.4
Frequency Range* _ 880MHz to 960MHz, 1,710MHz to 1,880MHz, 1,850MHz to 1,990MHz
Band Width _ > 80MHz, > 170MHz
Gain (Max.)* _ 0dB to 0.5dB, 0.5dB to 1dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 3.5
Temp. Range _ -40°C to +85°C
Packaging _ Bulk


* Depends on the Yageo demoboard



High Frequency Antenna

Ceramic Antenna

DECT / WCDMA



Size (mm) _ 8.8 x 6.8 x 0.9
 Frequency Range* _ 1.88GHz to 2.1GHz
 Band Width _ W > 100MHz
 Gain (Max.)* _ 2.0dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.0
 Temp. Range _ -55°C to +125°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH



Size (mm) _ 8.0 x 1.0 x 1.0
 Center Frequency _ 2.10GHz, 2.20GHz, 2.30GHz,
 2.45GHz, 2.50GHz, 2.60GHz,
 2.70GHz, 2.80GHz

Azimuth _ Omni-Directional
 VSWR* _ < 2.5
 Temp. Range _ -55°C to +125°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH
 LONG SHAPE



Size (mm) _ 7.8 x 3.6 x 0.9
 Frequency Range* _ 2.45GHz, 2.60GHz, 2.70GHz
 Band Width _ > 100MHz
 Gain (Max.)* _ 4.1dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.5
 Temp. Range _ -55°C to +85°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH



Size (mm) _ 7.3 x 5.5 x 1.3
 Frequency Range* _ 2.45GHz, 2.60GHz,
 2.70GHz, 2.80GHz
 Band Width _ > 100MHz
 Gain (Max.)* _ 1.2dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.0
 Temp. Range _ -55°C to +125°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH



Size (mm) _ 5.3 x 2.0 x 1.3
 Frequency Range* _ 2.00GHz, 2.10GHz, 2.20GHz,
 2.30GHz, 2.40GHz, 2.45GHz,
 2.50GHz
 Band Width _ > 100MHz
 Gain (Max.)* _ 4.0dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.5
 Temp. Range _ -55°C to +85°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH



Size (mm) _ 5.0 x 1.0 x 1.0
 Frequency Range* _ 2.30GHz, 2.40GHz, 2.80GHz,
 3.10GHz, 3.30GHz, 3.70GHz
 Band Width _ > 100MHz
 Gain (Max.)* _ 2.45dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.0
 Temp. Range _ -55°C to +85°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH / WLAN



Size (mm) _ 3.2 x 1.6 x 1.2
 Center Frequency _ 2.20GHz, 2.30GHz, 2.40GHz,
 2.45GHz, 2.50GHz, 2.60GHz,
 2.70GHz, 2.80GHz, 2.90GHz
 Band Width _ > 100MHz
 Gain (Max.) _ 3.1dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.5
 Temp. Range _ -25°C to +85°C
 Packaging _ Reel

Ceramic Antenna

BLUETOOTH



Size (mm) _ 2.0 x 1.25 x 1.0
 Frequency Range* _ 2.45 GHz
 Band Width _ > 100MHz
 Gain (Max.)* _ 2.1dB
 Polarization _ Linear

Azimuth _ Omni-Directional
 VSWR* _ < 2.5
 Temp. Range _ -25°C to +85°C
 Packaging _ Reel



High Frequency
Antenna

GPS Antenna

LP MODE
CHIP-SMD



Size (mm) _ 12.5 x 6.6 x 0.9
Frequency Range* _ 1.575GHz
Band Width _ > 100MHz
Gain (Max.)* _ 1.5dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.0
Temp. Range _ -55°C to +125°C
Packaging _ Bulk

GPS Antenna

LP MODE
CHIP-SMD



Size (mm) _ 6.15 x 3.0 x 1.25
Frequency Range* _ 1.575GHz, 1.675GHz
Band Width _ > 100MHz
Gain (Max.)* _ 1dB
Polarization _ Linear

Azimuth _ Omni-Directional
VSWR* _ < 2.0
Temp. Range _ -55°C to +85°C
Packaging _ Reel

GPS Antenna

LP MODE
PIN



Size (mm) _ 15 x 10 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 8MHz
Gain (Max.)* _ 1 (linear)
Polarization _ Linear

Azimuth _ Pin
VSWR* _ < 2.5
Temp. Range _ -25°C to +125°C
Packaging _ Bulk

GPS Antenna

LP MODE
PIN



Size (mm) _ 16 x 6 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 8MHz
Gain (Max.)* _ 1 (linear)
Polarization _ Linear

Azimuth _ Pin
VSWR* _ < 2.5
Temp. Range _ -25°C to +125°C
Packaging _ Bulk

GPS Antenna

CP MODE
SMD



Size (mm) _ 12 x 12 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ SMD
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
PIN



Size (mm) _ 12 x 12 x 4, 12 x 12 x 2
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ Pin
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
SMD



Size (mm) _ 15 x 15 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ SMD
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
PIN



Size (mm) _ 15 x 15 x 4, 15 X 15 X 2
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ Pin
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

* Depends on the Yageo demoboard



High Frequency Antenna

GPS Antenna

CP MODE
SMD



Size (mm) _ 18 x 18 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ SMD
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
PIN



Size (mm) _ 18 x 18 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ Pin
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
PIN



Size (mm) _ 18 x 18 x 2
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ Pin
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
SMD



Size (mm) _ 25 x 25 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ SMD
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Antenna

CP MODE
PIN



Size (mm) _ 25 x 25 x 2, 25 x 25 x 4
Frequency Range* _ 1.575GHz
Band Width _ > 10MHz
Gain (Max.)* _ 1dB
Polarization _ Right Hand Circular Polarization

Azimuth _ Pin
Axis Ratio _ 3dB
VSWR* _ < 2.0
Temp. Range _ -25°C to +85°C
Packaging _ Bulk

GPS Active Antenna

CABLE + IPEX CONNECTOR



Size (mm) _ 13 x 13 x 5, 13 x 13 x 7,
16 x 16 x 5, 16 x 16 x 7,
19 x 19 x 5, 19 x 19 x 7,
21 x 15 x 5.5, 28 x 28 x 5.5,
30 x 30 x 5.5, 35 x 28 x 5.5
Frequency Range* _ 1.575GHz
Gain* _ 17 ± 1dB (at fc, without SAW filter)

Noise Figure _ 1.5dB typ (at fc, 1.8dB Max)
Output VSWR _ 2.0 (at fc)
Supply Voltage _ 3.3 ± 5% V
Current Consumption _ 6mA
Output Impedance* _ 50Ω
Packaging _ Bulk

High Frequency Filter

Low Pass Filter



Size (mm) _ 1.6 x 0.8 x 0.65
Frequency Range _ 2.45GHz
Pass Band _ 2,400MHz to 2,500MHz
Impedance _ 50Ω
Insertion Loss (Max.) _ 0.45dB
Ripple (Max.) _ 0.6dB

VSWR* _ 1.8
Attenuation _ 25dB Min @ 2 fo
18dB Min @ 3 fo
Packaging _ Reel

Low Pass Filter



Size (mm) _ 2.0 x 1.25 x 0.8
Frequency Range _ 2.45GHz
Pass Band _ 2,400MHz to 2,500MHz
Impedance _ 50Ω
Insertion Loss (Max.) _ 0.5dB
Ripple (Max.) _ 0.6dB

VSWR* _ 1.8
Attenuation _ 27dB Min @ 5,000MHz
25dB Min @ 7,500MHz
Packaging _ Reel



High Frequency Filter

Band Pass Filter



Size (mm) _ 1.6 x 0.8 x 0.65
 Frequency Range _ 2.45GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50Ω
 Insertion Loss (Max.) _ 2.2dB
 Ripple (Max.) _ 0.6dB
 VSWR* _ 2.0

Attenuation _
 30dB Min @ 880MHz to 960MHz
 25dB Min @ 1,710MHz to 1,910MHz
 15dB Min @ 2,000MHz
 8.5dB Min @ 2,100MHz
 20dB Min @ 4,800MHz to 5,000MHz
 30dB Min @ 7,200MHz to 7,500MHz
 Packaging _ Reel

Band Pass Filter



Size (mm) _ 2.0 x 1.25 x 0.6 to 1.0
 Frequency Range _ 2.45GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50Ω
 Insertion Loss (Max.) _ 2.0dB
 Ripple (Max.) _ 0.6dB
 VSWR* _ 2.0

Attenuation _
 40dB Min @ 1,000MHz to 1,600MHz
 40dB Min @ 4,900MHz
 20dB Min @ 7,500MHz
 Packaging _ Reel

Band Pass Filter



Size (mm) _ 2.5 x 2.0 x 0.95 to 1.2
 Frequency Range _ 2.45GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50Ω
 Insertion Loss (Max.) _ 1.5dB
 Ripple (Max.) _ 0.6dB
 VSWR* _ 2.0

Attenuation _
 30dB Min @ 1,600MHz
 35dB Min @ 3,200MHz
 25dB Min @ 4,800MHz to 5,000MHz
 30dB Min @ 7,200MHz to 7,500MHz
 Packaging _ Reel

High Frequency Combo

Balanced Filter

COMBO



Size (mm) _ 2.0 x 1.25 x 1.0
 Frequency Range _ 2.40GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50 / 100Ω
 Insertion Loss (Max.) _ 2.0dB
 Ripple (Max.) _ 0.5dB
 Amplitude Balance (Max) _ 10dB
 Phase Differential _ 180 ± 10 degree

Attenuation _
 40dB Min @ 880MHz to 960MHz
 25dB Min @ 1,300MHz to 1,600MHz
 35dB Min @ 4,800MHz to 5,000MHz
 30dB Min @ 7,200MHz to 7,500MHz
 Packaging _ Reel

Balanced Filter

COMBO



Size (mm) _ 2.0 x 1.25 x 1.0
 Frequency Range _ 2.40GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50 / 100Ω
 Insertion Loss (Max.) _ 2.0dB
 Ripple (Max.) _ 0.5dB
 Amplitude Balance (Max) _ 10dB
 Phase Differential _ 180 ± 10 degree

Attenuation _
 40dB Min @ 880MHz to 960MHz
 25dB Min @ 1,300MHz to 1,600MHz
 35dB Min @ 4,800MHz to 5,000MHz
 25dB Min @ 7,200MHz to 7,500MHz
 Packaging _ Reel
 Color _ White

Balanced Filter

COMBO



Size (mm) _ 2.5 x 2.0 x 1.2
 Frequency Range _ 2.40GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50 / 100Ω
 Insertion Loss (Max.) _ 2.0dB
 Ripple (Max.) _ 0.5dB
 Amplitude Balance (Max) _ 10dB
 Phase Differential _ 180 ± 10 degree

Attenuation _
 48dB Min @ 880MHz to 960MHz
 48dB Min @ 1,710MHz to 1,910MHz
 40dB Min @ 1,880MHz to 1,990MHz
 20dB Min @ 2,110MHz to 2,170MHz
 20dB Min @ 4,800MHz to 5,000MHz
 20dB Min @ 7,200MHz to 7,500MHz
 Packaging _ Reel

High Frequency Balun

Balun



Size (mm) _ 1.6 x 0.8 x 0.65
 Frequency Range _ 5.0GHz
 Pass Band _ 4,900MHz to 5,950MHz
 Impedance _ 50 / 100Ω
 Insertion Loss (Max.) _ 1.2dB
 Ripple (Max.) _ 0.6dB

VSWR* _ 2.0
 Amplitude Balance (Max.) _ 1.5dB
 Phase Differential _ 180 ± 10 degree
 Packaging _ Reel

Balun



Size (mm) _ 2.0 x 1.25 x 0.8
 Frequency Range _ 2.40GHz
 Pass Band _ 2,400MHz to 2,500MHz
 Impedance _ 50 / 50Ω, 50 / 100Ω, 50 / 200Ω
 Insertion Loss (Max.) _ 1.0dB
 Ripple (Max.) _ 0.6dB

VSWR* _ 2.0
 Amplitude Balance (Max) _ 2.0dB
 Phase Differential _ 180 ± 10 degree
 Packaging _ Reel

* Depends on the Yageo demoboard



High Frequency
Balun

Balun



Size (mm) _ 2.0 x 1.25 x 0.8
Frequency Range _ 5.0GHz
Pass Band _ 4,900MHz to 5,900MHz
Impedance _ 50 / 100Ω
Insertion Loss (Max.) _ 1.2dB
Ripple (Max.) _ 0.6dB

VSWR* _ 2.0
Amplitude Balance (Max.) _ 2.0dB
Phase Differential _ 180 ± 10 degree
Packaging _ Reel

High Frequency
Diplexer

Diplexer



Size (mm) _ 2.0 x 1.25 x 0.75
Frequency Range _ 2.4 / 5.0GHz
Pass Band _ 2,400GHz to 2,500GHz
Insertion Loss (Max.) _ 0.6dB
VSWR* (Max.) _ 2.0
Attenuation _
 18dB Min @ 4,800MHz to 6,000MHz
 20dB Min @ 7,200MHz to 7,500MHz

Pass Band _ 4,900GHz to 5,900GHz
Insertion Loss (Max.) _ 1.1dB
VSWR* (Max.) _ 2.0
Attenuation _
 18dB Min @ 1,800MHz to 2,500MHz
 15dB Ref @ 10,300MHz to 10,700MHz
Packaging _ Reel

Diplexer



Size (mm) _ 2.0 x 1.25 x 0.75
Frequency Range _ 2.4 / 5.0GHz
Pass Band _ 2,400GHz to 2,500GHz
Insertion Loss (Max.) _ 0.6dB
VSWR* (Max.) _ 2.0
Attenuation _
 17dB Min @ 4,800MHz to 6,000MHz
 20dB Min @ 7,200MHz to 7,500MHz

Pass Band _ 4,900GHz to 5,900GHz
Insertion Loss (Max.) _ 1.1dB
VSWR* (Max.) _ 2.0
Attenuation _
 17dB Min @ 1,800MHz to 2,500MHz
 20dB Ref @ 10,300MHz to 10,700MHz
Packaging _ Reel

Diplexer



Size (mm) _ 2.0 x 1.25 x 0.85
Frequency Range _ 2.4 / 5.0GHz
Pass Band _ 2,400GHz to 2,500GHz
Insertion Loss (Max.) _ 0.7dB
VSWR* (Max.) _ 2.0
Attenuation _
 20dB Min @ 4,900MHz to 5,900MHz

Pass Band _ 4,900GHz to 5,900GHz
Insertion Loss (Max.) _ 0.9dB
VSWR* (Max.) _ 2.0
Attenuation _
 20dB Min @ 2,400MHz to 2,500MHz
Packaging _ Reel



MLV

MLV Series

**SURGE SUPPRESSOR
ESD PROTECTION**

Meet IEC 61000 - 4 - 2 (level 4)



Size _ 0402 to 1206

Capacitance Range _ 3pF to 1600pF

Capacitance Tolerance _ $\pm 10\%$, $\pm 15\%$, $\pm 20\%$, $\pm 30\%$

Rated Working Voltage _ 5.5Vdc to 110Vdc

Operating Temp. Range _ -55°C to $+85^{\circ}\text{C}$

Packaging _ Reel



Aluminum Electrolytic Caps.

S5/SS Series

MINIATURE
5mm and 7mm Height Radial



Capacitance Range _ 0.1 μ F to 470 μ F
Rated Working Voltage _ 4Vdc to 63Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.01CV or 3 μ A
Load Life _ 1,000Hr. @ 105°C
Packaging _ Bulk / Tape

SK Series

GENERAL PURPOSE
Radial



Capacitance Range _ 0.1 μ F to 22,000 μ F
Rated Working Voltage _ 6.3Vdc to 450Vdc
Operating Temp. Range _ -40°C to +85°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.01CV + 3 μ A \leq 100Vdc
= 0.03CV + 10 μ A \geq 160Vdc
Load Life _ 2,000Hr. @ 85°C
Packaging _ Bulk / Tape

SEK Series

GENERAL PURPOSE
Radial



Capacitance Range _ 0.47 μ F to 15,000 μ F
Rated Working Voltage _ 6.3Vdc to 450Vdc
Operating Temp. Range _
V \leq 250 -40°C to +105°C
V \geq 350 -25°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.01CV + 3 μ A \leq 100Vdc
= 0.03CV + 10 μ A \geq 160Vdc
Load Life _ 1,000Hr. @ 105°C
Packaging _ Bulk / Tape

SH Series

GENERAL PURPOSE
Radial



Capacitance Range _ 0.47 μ F to 15,000 μ F
Rated Working Voltage _ 6.3Vdc to 450Vdc
Operating Temp. Range _
V \leq 100 -40°C to +105°C
V \geq 160 -25°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.01CV + 3 μ A \leq 100Vdc
= 0.03CV + 10 μ A \geq 160Vdc
Load Life _ 2,000Hr. @ 105°C
Packaging _ Bulk / Tape

SG Series

MINIATURE AND LONG LIFE
Radial



Capacitance Range _ 3.3 μ F to 330 μ F
Rated Working Voltage _ 160Vdc to 450Vdc
Operating Temp. Range _ -40°C to +105°C
V \leq 400 -40°C to +105°C
V \geq 450 -25°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.06CV + 10 μ A
Load Life _ 5,000Hr. @ 105°C
Packaging _ Bulk / Tape

SP Series

LONG LIFE
Radial



Capacitance Range _ 3.3 μ F to 330 μ F
Rated Working Voltage _ 160Vdc to 450Vdc
Operating Temp. Range _
V \leq 400 -40°C to +105°C
V \geq 450 -25°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.04CV + 100 μ A
Load Life _ 8,000Hr. to 10,000Hr. @ 105°C
Packaging _ Bulk / Tape

SQ Series

HIGH VOLTAGE AND LOW IMPEDANCE
Radial



Capacitance Range _ 2.2 μ F to 220 μ F
Rated Working Voltage _ 160Vdc to 450Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.03CV + 10 μ A
Load Life _ 2,000Hr. @ 105°C
Packaging _ Bulk / Tape

SC Series

LOW IMPEDANCE
Radial



Capacitance Range _ 4.7 μ F to 15,000 μ F
Rated Working Voltage _ 6.3Vdc to 100Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.01CV or 3 μ A
Load Life _ 3,000Hr. @ 105°C
Packaging _ Bulk / Tape



Aluminum Electrolytic Caps.

SZ Series

ULTRA LOW IMPEDANCE AND HIGH RIPPLE
Radial



Capacitance Range _ 470 μ F to 3,300 μ F
Rated Working Voltage _ 6.3Vdc to 16Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.03CV
Load Life _ 2,000Hr. @ 105°C
Packaging _ Bulk / Tape

SY Series

LOW IMPEDANCE AND LONG LIFE
Radial



Capacitance Range _ 2.2 μ F to 15,000 μ F
Rated Working Voltage _ 6.3Vdc to 100Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.01CV or 3 μ A
Load Life _ 3,000Hr. to 6,000Hr. @ 105°C
Packaging _ Bulk / Tape

SN Series

NON-POLAR
Radial



Capacitance Range _ 0.22 μ F to 2,200 μ F
Rated Working Voltage _ 6.3Vdc to 100Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.03CV + 3 μ A
Load Life _ 1,000Hr. @ 105°C
Packaging _ Bulk / Tape

SB Series

LOW LEAKAGE CURRENT
Radial



Capacitance Range _ 0.1 μ F to 4,700 μ F
Rated Working Voltage _ 6.3Vdc to 100Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.002CV or 0.4 μ A
Load Life _ 1,000Hr. @ 105°C
Packaging _ Bulk / Tape

SR Series

BI-POLAR
Radial




Capacitance Range _ 2.2 μ F to 47 μ F
Rated Working Voltage _ 25Vdc to 50Vdc
Operating Temp. Range _ -40°C to +85°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ 100 μ A (after 2Min. both direction)
Load Life _ 1,000Hr. @ 85°C
Packaging _ Bulk / Tape

SJ Series

LOW IMPEDANCE AND LONG LIFE
Radial



Capacitance Range _ 5.6 μ F to 6,800 μ F
Rated Working Voltage _ 6.3V to 100Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.01CV or 3 μ A
Load Life _ 1,000Hr. to 5,000Hr. @ 105°C
Packaging _ Bulk / Tape

LH Series

GENERAL PURPOSE
Snap-In



Capacitance Range _ 56 μ F to 120,000 μ F
Rated Working Voltage _ 6.3Vdc to 450Vdc
Operating Temp. Range _ 6.3Vdc to 100Vdc: -40°C to +85°C
160Vdc to 450Vdc: -25°C to +85°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ = 0.02CV or 3mA
Load Life _ 2,000Hr. @ 85°C
Packaging _ Bulk

LG Series

GENERAL PURPOSE
Snap-In



Capacitance Range _ 47 μ F to 82,000 μ F
Rated Working Voltage _ 6.3Vdc to 450Vdc
Operating Temp. Range _ 6.3Vdc to 100Vdc: -40°C to +105°C
160Vdc to 450Vdc: -25°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ I = 0.02CV, L = 20 m/m
I = 0.03CV or 3mA
Load Life _ 2,000Hr. @ 105°C
Packaging _ Bulk



Aluminum Electrolytic Caps.

LV Series

LONG LIFE
Snap-In



Capacitance Range _ 270 μ F to 68,000 μ F
Rated Working Voltage _ 10Vdc to 450Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.02VC or 3mA
Load Life _ 3,000Hr. @ 105°C
Packaging _ Bulk

CA Series

LOW PROFILE
SMD V-Chip



Capacitance Range _ 0.1 μ F to 1,000 μ F
Rated Working Voltage _ 4Vdc to 50Vdc
Operating Temp. Range _ -40°C to +85°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.01CV or 3 μ A
Load Life _ 2,000Hr. @ 85°C
Packaging _ Reel

CB Series

LOW PROFILE
SMD V-Chip



Capacitance Range _ 0.1 μ F to 1,000 μ F
Rated Working Voltage _ 4Vdc to 50Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.01CV or 3 μ A
Load Life _ 1,000Hr. @ 105°C
Packaging _ Reel

CD Series

ULTRA LOW IMPEDANCE
SMD V-Chip



Capacitance Range _ 4.7 μ F to 1,500 μ F
Rated Working Voltage _ 6.3Vdc to 35Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.01CV or 3 μ A
Load Life _ 2,000Hr. @ 105°C
Packaging _ Reel

CE Series

LONG LIFE
SMD V-Chip



Capacitance Range _ 0.1 μ F to 1,000 μ F
Rated Working Voltage _ 6.3Vdc to 50Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.01CV or 3 μ A
Load Life _ 2,000Hr. @ 105°C
Packaging _ Reel

CZ Series

LOW IMPEDANCE
SMD V-Chip



Capacitance Range _ 0.1 μ F to 1,000 μ F
Rated Working Voltage _ 4Vdc to 50Vdc
Operating Temp. Range _ -40°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.01CV or 3 μ A
Load Life _ 1,000Hr. @ 105°C
Packaging _ Reel

CP Series

ULTRA LOW IMPEDANCE
8mm Height Radial
Conductive Polymer Capacitor



Capacitance Range _ 470 μ F to 820 μ F
Rated Working Voltage _ 2.5Vdc to 6.3Vdc
Operating Temp. Range _ -55°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.2CV
Load Life _ 2,000Hr. @ 105°C
Packaging _ Bulk / Tape


CG Series

ULTRA LOW IMPEDANCE
Conductive Polymer Capacitor



Capacitance Range _ 270 μ F to 1,500 μ F
Rated Working Voltage _ 2.5Vdc to 16Vdc
Operating Temp. Range _ -55°C to +105°C
Capacitance Tolerance _ \pm 20%

Max. Leakage Current _ \leq 0.2CV
Load Life _ 2,000Hr. @ 105°C
Packaging _ Bulk / Tape



Leaded Resistors

MFR Series

METAL FILM
Normal & Miniature Style



Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 1/6W to 3W
Temp. Coefficient _
±15, ±25, ±50, ±100ppm/°C
Resistance Tolerance _ ±0.5%, ±1%

Max. Working Voltage _ 200Vdc to 500Vdc
Max. Overload Voltage _ 400Vdc to 1KVdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

MFP Series

PRECISION METAL FILM
Normal & Miniature Style




Resistance Range _ 10Ω to 1MΩ
Rated Power @ 70°C _ 1/6W to 3W
Temp. Coefficient _ ±15, ±25ppm/°C
Resistance Tolerance _ ±0.1%, ±0.25%

Max. Working Voltage _ 150Vdc to 500Vdc
Max. Overload Voltage _ 300Vdc to 1KVdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

MHP Series

HIGH PRECISION METAL FILM
Normal Style




Resistance Range _ 100Ω to 500KΩ
Rated Power @ 70°C _ 1/4W & 1/2W
Temp. Coefficient _ ±5, ±10ppm/°C
Resistance Tolerance _ ±0.02%, ±0.05%

Max. Working Voltage _ 200Vdc to 250Vdc
Max. Overload Voltage _ 400Vdc to 500Vdc
Packaging _ Bulk
Meets _ JIS-C-5202

MFO Series

PROFESSIONAL METAL FILM
Miniature Style




Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 0.4W & 0.6W
Temp. Coefficient _ ±50, ±100ppm/°C
Resistance Tolerance _ ±1%

Max. Working Voltage _ 250Vdc to 350Vdc
Max. Overload Voltage _ 500Vdc to 700Vdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FMF Series

METAL FILM FLAME-PROOF
Normal & Miniature Style



Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 1/4W to 3W
Temp. Coefficient _ ±50, ±100ppm/°C
Resistance Tolerance _ ±1%

Max. Working Voltage _ 250Vdc to 500Vdc
Max. Overload Voltage _ 500Vdc to 1KVdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FM0 Series

PROFESSIONAL METAL FILM FLAME-PROOF
Miniature Style




Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 0.4W & 0.6W
Temp. Coefficient _ ±50, ±100ppm/°C
Resistance Tolerance _ ±1%

Max. Working Voltage _ 200Vdc to 300Vdc
Max. Overload Voltage _ 400Vdc to 600Vdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FMP Series

HIGH POWER FLAME-PROOF METAL FILM
Ultra Miniature Style



Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 1/4W to 3W
Temp. Coefficient _ ±100ppm/°C
Resistance Tolerance _ ±1%, ±5%

Max. Working Voltage _ 200Vdc to 750Vdc
Max. Overload Voltage _ 400Vdc to 1KVdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

RSF Series

METAL OXIDE FILM
Normal & Miniature Style



Resistance Range _ 1Ω to 1MΩ & 0Ω
Rated Power @ 70°C _ 1/4W to 5W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 200Vdc to 750Vdc
Max. Overload Voltage _ 300Vdc to 1KVdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202



Leaded Resistors

LIR Series

METAL OXIDE FILM
Normal & Miniature Style




Resistance Range _ 1Ω to 100KΩ & 0Ω
Rated Power @ 70°C _ 1/4W to 3W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±5%, ±10%

Max. Working Voltage _ 200Vdc to 350Vdc
Max. Overload Voltage _ 300Vdc to 600Vdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FRM Series

FUSIBLE METAL FILM
Normal & Miniature Style



Resistance Range _ 4.7Ω to 560Ω (±2%)
2.2Ω to 560Ω (±5%)
Rated Power @ 70°C _ 1/4W to 3W
Temp. Coefficient _ ±200ppm/°C
Resistance Tolerance _ ±2%, ±5%

Fusing Characteristics _
Fusing time within 30 seconds at 16 times of rated power.
Fusing residual resistive value at least 100 times rated resistance.
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

MMF Series

SMD MELF RESISTORS
Normal & Miniature Style



Resistance Range _ 1Ω to 1MΩ & 0Ω
Rated Power @ 70°C _ 1W & 2W
Temp. Coefficient _ ±15, ±25, ±50, ±100, ±200ppm/°C
Resistance Tolerance _ ±0.1%, ±0.25%, ±0.5%, ±1%

Max. Working Voltage _ 150Vdc to 350Vdc
Max. Overload Voltage _ 300Vdc to 700Vdc
Packaging _ Tape / Reel
Meets _ JIS-C-5202

MMP Series

SMD MELF RESISTORS
Ultra Miniature Style



Resistance Range _ 1Ω to 1MΩ & 0Ω
Rated Power @ 70°C _ 1W & 2W
Temp. Coefficient _ ±50, ±100, ±200ppm/°C
Resistance Tolerance _ ±1%, ±2%, ±5%

Max. Working Voltage _ 350Vdc
Max. Overload Voltage _ 700Vdc
Packaging _ Tape / Reel
Meets _ JIS-C-5202

CFR Series

CARBON FILM
Normal & Miniature Style



Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 1/6W to 3W
Temp. Coefficient _ -1,500ppm/°C to +350ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 150Vdc to 500Vdc
Max. Overload Voltage _ 300Vdc to 1KVdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

CF0 Series

PROFESSIONAL CARBON FILM
Miniature Style




Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 0.4W & 0.6W
Temp. Coefficient _ -1,500ppm/°C to +350ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 200Vdc to 300Vdc
Max. Overload Voltage _ 400Vdc to 600Vdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FCR Series

CARBON FILM FLAME-PROOF
Normal & Miniature Style



Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 1/4W to 3W
Temp. Coefficient _ -1,500ppm/°C to +350ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 250Vdc to 500Vdc
Max. Overload Voltage _ 400Vdc to 1KVdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FC0 Series

PROFESSIONAL CARBON FILM FLAME-PROOF
Miniature Style



Resistance Range _ 1Ω to 10MΩ & 0Ω
Rated Power @ 70°C _ 0.4W & 0.6W
Temp. Coefficient _ -1,500ppm/°C to +350ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 200Vdc to 300Vdc
Max. Overload Voltage _ 400Vdc to 600Vdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202



Leaded Resistors

NCR Series

NON-INDUCTIVE CARBON FILM
Normal & Miniature Style



Resistance Range _ 2.2Ω to 10KΩ
Rated Power @ 70°C _ 1/4W to 3W
Temp. Coefficient _ -800ppm/°C to -500ppm/°C
Resistance Tolerance _ ±5%, ±10%

Max. Working Voltage _ 250Vdc to 500Vdc
Max. Overload Voltage _ 500Vdc to 1KVdc
Flameproof Silicone Coating Meet _ UL94V-0
Inductance _ < 1μH
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

MCF Series

SMD MELF RESISTORS
Normal & Miniature Style



Resistance Range _ 1Ω to 1MΩ & 0Ω
Rated Power @ 70°C _ 1/6W to 1W
Temp. Coefficient _ -1,500ppm/°C to +350ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 200Vdc to 350Vdc
Max. Overload Voltage _ 400Vdc to 700Vdc
Packaging _ Tape / Reel
Meets _ JIS-C-5202

MCP Series

SMD MELF RESISTORS
Ultra Miniature Style



Resistance Range _ 1Ω to 1MΩ & 0Ω
Rated Power @ 70°C _ 1W & 2W
Temp. Coefficient _ -1,500ppm/°C to +350ppm/°C
Resistance Tolerance _ ±2%, ±5%

Max. Working Voltage _ 350Vdc
Max. Overload Voltage _ 700Vdc
Packaging _ Tape / Reel
Meets _ JIS-C-5202

HHV Series

**HIGH VOLTAGE &
HIGH OHMIC RESISTORS**
Normal Style



Resistance Range _ 100KΩ to 68MΩ
Rated Power @ 70°C _ 1/4W to 1W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±1%, ±5%

Max. Working Voltage _ 1.6KVdc to 10KVdc
Max. Overload Voltage _ 3KVdc to 20KVdc
Packaging _ Tape / Box
Meets _ JIS-C-5202

APR Series

PULSE-LOADING RESISTORS
Normal & Miniature Style



Resistance Range _ 100KΩ to 10MΩ
Rated Power @ 70°C _ 1/4W to 2W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±5%

Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

ZOR Series

ZERO OHM RESISTORS
Normal Style



Max. Resistance Value _ 0.005Ω
Rated Power _ 1/6W & 1/4W
Temp. Coefficient _ ±100ppm/°C
Resistance Tolerance _ ±1%, ±5%

Rated Current _
15AMPS @ 70°C for 1/4W
10AMPS @ 70°C for 1/6W
Packaging _ Bulk, Tape / Box, Tape / Reel

JPW Series

JUMPER WIRES
Normal Style



Material _ Soft Copper Wire with Tin Plating
Conductor Resistance _ 0.54mΩ / cm
Wire Diameter _
Φ0.5mm to Φ0.8mm & Φ1.0mm (±0.05mm)

Conductivity _
Φ0.5mm: Min. 94%
Φ0.6mm to 1.0mm: Min. 96%
Thickness of Plating _ 4μm ± 1μm
Packaging _ Tape / Box, Tape / Reel

KNP Series

WIREWOUND RESISTORS
Normal & Miniature Style



Resistance Range _ 0.1Ω to 1KΩ
Rated Power @ 70°C _ 1/4W to 7W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±1%, ±5%

Dielectric Withstanding Voltage _
200Vdc to 400Vdc
Flameproof Silicone Coating Meet _
UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202



Leaded Resistors

NKN Series

NON-INDUCTIVE WIREWOUND RESISTORS
Normal & Miniature Style




Resistance Range _ 0.1Ω to 330Ω
Rated Power @ 70°C _ 1/2W to 7W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±5%

Dielectric Withstanding Voltage _ 250Vdc to 400Vdc
Flameproof Silicone Coating Meet _ UL94V-0
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

FKN Series

FUSIBLE WIREWOUND FLAME-PROOF TYPE
Normal & Miniature Style



Resistance Range _ 0.1Ω to 390Ω
Rated Power @ 70°C _ 1/4W to 7W
Temp. Coefficient _ ±350ppm/°C
Resistance Tolerance _ ±1%, ±5%

Dielectric Withstanding Voltage _ 200Vdc to 300Vdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

PNP Series

POWER WIREWOUND RESISTORS
Ultra Miniature Style



Resistance Range _ 0.1Ω to 330Ω
Rated Power @ 70°C _ 1W to 4W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±1%, ±5%

Dielectric Withstanding Voltage _ 300Vdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

PNP V Series

POWER WIREWOUND RESISTORS
High Power Style



Resistance Range _ 0.1Ω to 8.2KΩ
Rated Power @ 70°C _ 1W to 10W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±1%, ±5%

Dielectric Withstanding Voltage _ 300Vdc
Packaging _ Bulk, Tape / Box, Tape / Reel
Meets _ JIS-C-5202

SQP & NSP Series

CEMENT RESISTORS
Axial Lead Style



Resistance Range _ 0.1Ω to 200KΩ
Rated Power @ 70°C _ 2W to 10W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±5%

Load Life _ ±5.0% + 0.05Ω
Insulation Resistance _ > 1,000MΩ
Packaging _ Bulk
Meets _ JIS-C-5202

SQM & NSM Series

CEMENT RESISTORS
Vertical Lead Style



Resistance Range _ 0.1Ω to 200KΩ
Rated Power @ 70°C _ 2W to 10W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±5%

Load Life _ ±5.0% + 0.05Ω
Insulation Resistance _ > 1,000MΩ
Packaging _ Bulk
Meets _ JIS-C-5202

SQZ & NSZ Series

CEMENT RESISTORS
Radial Terminals Style



Resistance Range _ 0.1Ω to 200KΩ
Rated Power @ 70°C _ 3W to 20W
Temp. Coefficient _ ±300ppm/°C
Resistance Tolerance _ ±5%

Load Life _ ±5.0% + 0.05Ω
Insulation Resistance _ > 1,000MΩ
Packaging _ Bulk
Meets _ JIS-C-5202

PSP Series

CEMENT RESISTORS AXIAL LEAD TYPE
Power Wirewound Style



Resistance Range _ 0.1Ω to 3.9KΩ
Rated Power @ 70°C _ 4W to 9W
Temp. Coefficient _ ±400ppm/°C
Resistance Tolerance _ ±5%, ±10%

Load Life _ ±5.0% + 0.1Ω
Insulation Resistance _ ≥ 1,000MΩ
Packaging _ Bulk
Meets _ JIS-C-5202



Leaded Resistors

PSM Series

**CEMENT RESISTORS
VERTICAL LEAD TYPE**
Power Wirewound Style



Resistance Range _ 0.1Ω to 3.9KΩ
Rated Power @ 70°C _ 4W to 9W
Temp. Coefficient _ ±400ppm/°C
Resistance Tolerance _ ±5%, ±10%

Load Life _ ±5.0% + 0.1Ω
Insulation Resistance _ ≥ 1,000MΩ
Packaging _ Bulk
Meets _ JIS-C-5202

FTR Series

**CEMENT RESISTORS
VERTICAL LEAD TYPE**
Fusible Thermal Style



Resistance Range _ 1Ω to 10KΩ
Rated Current _ 2A to 10A
Temp. Coefficient _ ±250ppm/°C
Resistance Tolerance _ ±5%, ±10%

Standard Voltage _ 250Vdc
Packaging _ Bulk
Meets _ JIS-C-5202

SLR Series

CERAMIC METAL PLATE RESISTORS
Normal Style



Resistance Range _ 0.05Ω to 3.3Ω
Rated Power @ 70°C _ 2W to 10W
Temp. Coefficient _ ±250ppm/°C
Resistance Tolerance _ ±5%, ±10%

Max. Working Voltage _ 250Vdc to 500Vdc
Max. Overload Voltage _ 500Vdc to 1KVdc
Packaging _ Bulk
Meets _ JIS-C-5202


AHA & AHP Series

ALUMINUM HOUSED RESISTORS
Power Wirewound Style



Resistance Range _ 0.1Ω to 3KΩ
Rated Power @ 70°C _ 5W to 250W
Temp. Coefficient _ ±200ppm/°C
Resistance Tolerance _ ±0.25% to ±10%

Dielectric Withstanding Voltage _
1KVdc to 4.5KVdc
Packaging _ Bulk
Meets _ JIS-C-5202



SMD Chip Beads

SB Series

MULTILAYER FERRITE
General Applications



Size _ 100505, 160808, 201209, 321611, 321616, 322513, 451616, 453215
Impedance Range _ 6Ω to 2,700Ω
Test Frequency _ 30MHz to 100MHz
Tolerance _ ±25%

DC Resistance _ 0.05Ω to 1.4Ω
Rated Current _ 100mA to 600mA
Packaging _ Tape, Reel

NB Series

MULTILAYER FERRITE
Data Line / Digital Signals



Size _ 100505, 160808, 201209, 321611
Impedance Range _ 6Ω to 2,700Ω
Test Frequency _ 100MHz
Tolerance _ ±25%

DC Resistance _ 0.05Ω to 1.0Ω
Rated Current _ 50mA to 800mA
Packaging _ Tape, Reel

HF Series



Size _ 100505, 160808
Impedance Range _ 120Ω to 1,800Ω
Test Frequency _ 100MHz & 1,000MHz
Tolerance _ ±25%, ±40%

DC Resistance _ 0.095Ω to 2.2Ω
Rated Current _ 50mA to 1,500mA
Packaging _ Tape, Reel

GB Series

MULTILAYER FERRITE
Medium Current Applications



Size _ 160808, 201209, 321611, 321616, 322513, 451616, 453215
Impedance Range _ 7Ω to 2,000Ω
Test Frequency _ 30MHz to 100MHz
Tolerance _ ±25%

DC Resistance _ 0.03Ω to 0.55Ω
Rated Current _ 300mA to 1,000mA
Packaging _ Tape, Reel

PB Series

MULTILAYER FERRITE
Large Current Applications



Size _ 100505, 160808, 201209, 321611, 322513, 451616, 453215
Impedance Range _ 10Ω to 1,500Ω
Test Frequency _ 50MHz to 100MHz
Tolerance _ ±25%

DC Resistance _ 0.01Ω to 0.25Ω
Rated Current _ 800mA to 6,000mA
Packaging _ Tape, Reel

UPB Series

MULTILAYER FERRITE
Ultra Current Applications



Size _ 160808, 201209, 201212, 321611, 451616, 453215
Impedance Range _ 11Ω to 150Ω
Test Frequency _ 100MHz
Tolerance _ ±25%

DC Resistance _ 0.01Ω to 0.025Ω
Rated Current _ 4,500mA to 9,000mA
Packaging _ Tape, Reel

FB Series

SHIELDED BEADS
Surface Mount



Size _ 423226, 784729, 863226, 865626
Impedance Range _ 24Ω to 72Ω
Test Frequency _ 25MHz & 100MHz
Tolerance _ ±20%

DC Resistance _ 0.6Ω to 0.9Ω
Packaging _ Tape, Reel

SMD Multilayer Chip Inductors

CL Series

MULTILAYER FERRITE
Monolithic Structure For Signals



Size _ 160808, 201209, 201212, 321611
Inductance Range _ 0.01μH to 33μH
Test Frequency _ 1MHz to 50MHz
Tolerance _ ±10%, ±20%

DC Resistance _ 0.15Ω to 2.2Ω
IDC _ 5mA to 300mA
Packaging _ Tape, Reel



SMD Multilayer
Chip Inductors

CLH Series

MULTILAYER HIGH FREQUENCY



Size _ 1005, 1608, 2012
Inductance Range _ 1nH to 470nH
Test Frequency _ 50MHz to 800MHz
Tolerance _ ± 0.3 , $\pm 5\%$, $\pm 10\%$
SRF _ 300MHz to 10,000MHz

DC Resistance _ 0.1 Ω to 4 Ω
IDC _ 100mA to 600mA
Packaging _ Tape, Reel

SMD Wire Wound
Chip Inductors

SQV Series

WOUND FERRITE

High Q & F / Low DC Resistance



Size _ 322520, 453226
Inductance Range _ 0.1 μ H to 2,200 μ H
Test Frequency _ 1KHz to 1MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$, $\pm 20\%$
SRF _ 1.3MHz to 200MHz

DC Resistance _ 0.025 Ω to 50 Ω
RC _ 30mA to 700mA
Packaging _ Tape, Reel

SQC Series

WOUND FERRITE

Low DC Resistance / High Current



Size _ 321618, 322520, 453226, 575047
Inductance Range _ 0.12 μ H to 10,000 μ H
Test Frequency _ 0.001MHz to 1MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$, $\pm 20\%$
SRF _ 0.5MHz to 450MHz

DC Resistance _ 0.0098 Ω to 140 Ω
RC _ 50mA to 6,000mA
Packaging _ Tape, Reel

NL Series

WOUND FERRITE

Open Wire



Size _ 201614, 252018
Inductance Range _ 0.005 μ H to 100 μ H
Test Frequency _ 0.0796MHz to 25.2MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$
SRF _ 12MHz to 3,000MHz

DC Resistance _ 0.2 Ω to 21 Ω
IDC _ 70mA to 2,000mA
Packaging _ Tape, Reel

NLC Series

WOUND FERRITE

Open for High Current



Size _ 252018, 322522
Inductance Range _ 0.47 μ H to 680 μ H
Test Frequency _ 0.796MHz to 25.2MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$
SRF _ 2MHz to 450MHz

DC Resistance _ 0.07 Ω to 28 Ω
IDC _ 65mA to 1,800mA
Packaging _ Tape, Reel

NLV Series



Size _ 322522
Inductance Range _ 0.01 μ H to 470 μ H
Test Frequency _ 0.796MHz to 100MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$
SRF _ 4MHz to 2,500MHz

DC Resistance _ 0.13 Ω to 40 Ω
IDC _ 25mA to 450mA
Packaging _ Tape, Reel

NLCV Series



Size _ 453232
Inductance Range _ 1 μ H to 330 μ H
Test Frequency _ 0.796MHz to 7.96MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$
SRF _ 4MHz to 200MHz

DC Resistance _ 0.11 Ω to 13 Ω
IDC _ 90mA to 1,050mA
Packaging _ Tape, Reel

LS Series

WOUND HIGH FREQUENCY



Size _ 0603, 0805, 1008
Inductance Range _ 1.2nH to 47,000nH
Test Frequency _ 2.5MHz to 7.9MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$
SRF _ 15MHz to 1,700MHz

RDC _ 0.06 Ω to 14.5 Ω
IDC _ 180mA to 2,000mA
Packaging _ Tape, Reel



SMD Wire Wound
Chip Inductors

LT Series



Size _ 0805, 1210
Inductance Range _ 120nH to 39,000nH
Test Frequency _ 2.52MHz to 25.2MHz
Tolerance _ $\pm 5\%$, $\pm 10\%$
SRF _ 15MHz to 1,500MHz

RDC _ 0.33 Ω to 16 Ω
IDC _ 190mA to 1,500mA
Packaging _ Tape, Reel

LD Series



Size _ 0805
Inductance Range _ 1.0 μ H to 100 μ H
Test Frequency _ 1MHz to 7.96MHz
Tolerance _ $\pm 10\%$, $\pm 20\%$
SRF _ 9MHz to 100MHz

RDC _ 0.1 Ω to 9 Ω
IDC _ 70mA to 800mA
Packaging _ Tape, Reel

PS Series



Size _ 1008
Inductance Range _ 1.0 μ H to 1,000 μ H
Test Frequency _ 100KHz
Tolerance _ $\pm 10\%$, $\pm 20\%$
SRF _ 1.5MHz to 344MHz

RDC _ 0.05 Ω to 29.2 Ω
IDC _ 0.1A to 3A
Packaging _ Tape, Reel

CS Series

WOUND HIGH FREQUENCY



Size _ 0402, 0603, 0805, 1008
Inductance Range _ 1.0nH to 10,000nH
Test Frequency _ 7.9MHz to 250MHz
Tolerance _ $\pm 2\%$, $\pm 5\%$, $\pm 10\%$
SRF _ 25MHz to 12,500MHz

RDC _ 0.03 Ω to 8 Ω
I_{rms} _ 30mA to 1,360mA
Packaging _ Tape, Reel

CT Series



Size _ 0805
Inductance Range _ 1.8nH to 1,000nH
Test Frequency _ 25MHz to 250MHz
Tolerance _ $\pm 2\%$, $\pm 5\%$, $\pm 10\%$
SRF _ 330MHz to 9,400MHz

RDC _ 0.03 Ω to 3.1 Ω
I_{rms} _ 300mA to 800mA
Packaging _ Tape, Reel

HC Series



Size _ 0603
Inductance Range _ 1.6nH to 24nH
Test Frequency _ 25MHz
Tolerance _ $\pm 2\%$, $\pm 5\%$, $\pm 10\%$
SRF _ 2,400MHz to 12,500MHz

RDC _ 0.03 Ω to 0.105 Ω
I_{rms} _ 1,800mA to 2,400mA
Packaging _ Tape, Reel

HQ Series



Size _ 0805, 1008
Inductance Range _ 2.5nH to 390nH
Test Frequency _ 25MHz to 250MHz
Tolerance _ $\pm 2\%$, $\pm 5\%$, $\pm 10\%$
SRF _ 530MHz to 6,000MHz

RDC _ 0.02 Ω to 0.7 Ω
I_{rms} _ 900mA to 1,600mA
Packaging _ Tape, Reel

LCN Series

WOUND HIGH FREQUENCY



Size _ 0603, 0805, 1008
Inductance Range _ 1.6nH to 8,200nH
Test Frequency _ 7.9MHz to 250MHz
Tolerance _ $\pm 2\%$, $\pm 5\%$, $\pm 10\%$
SRF _ 25MHz to 12,500MHz

RDC _ 0.03 Ω to 6 Ω
I_{rms} _ 170mA to 1,000mA
Packaging _ Tape, Reel



SMD Wire Wound
Chip Inductors

CMM Series

Common Mode Chokes



Size _ 21
Impedance Range _ 30Ω to 900Ω
Inductance Range _ 1.25μH to 11.5μH
Test Frequency _ 100MHz
Tolerance _ ±20%

RDC _ 0.2Ω to 0.6Ω
IDC _ 80mA to 450mA
Packaging _ Tape, Reel

SMD Power Inductors

SSL Series

UNSHIELDED



Size _ 04LP, 0400, 0402, 0802, 0804, 0810, 1306, 0614
Inductance Range _ 1.0μH to 1,000μH
Test Frequency _ 100KHz
Tolerance _ ±20%

DC Resistance _ 0.009Ω to 22.6Ω
Isat2 _ 0.08A to 20A
Irms3 _ 0.05A to 8.6A
Packaging _ Tape, Reel

SSL_HC Series

UNSHIELDED



Size _ 0503, 0804, 1306
Inductance Range _ 0.33μH to 100μH
Test Frequency _ 100KHz
Tolerance _ ±20%

DC Resistance _ 0.002Ω to 32Ω
Isat2 _ 0.87A to 30A
Irms3 _ 0.72A to 16A
Packaging _ Tape, Reel

SCD Series

UNSHIELDED



Size _ 0301, 03011, 03015, 03021, 0403, 0501, 0502, 0503, 0504, 0506, 0703, 0705, 0706, 1004, 1005, 105B, 1006, 1307
Inductance Range _ 1.0μH to 8,200μH
Test Frequency _ 1KHz to 7.96MHz
Tolerance _ ±20%, ±30%

DC Resistance _ 0.02Ω to 50Ω
Rated Current _ 0.03A to 3.8A
Packaging _ Tape, Reel

SCDS Series

SHIELDED



Size _ 2D09, 2D11, 2D14, 2D18, 3D11, 3D16, 3D28, 4D18, 4D28, 5D18, 5D28, 6D28, 6D38, 62, 64, 73, 74, 124, 125, 127, 104R, 105R
Inductance Range _ 0.6μH to 1,000μH
Test Frequency _ 1KHz to 7.96MHz
Tolerance _ ±20%, ±30%, +40%/-20%

DC Resistance _ 1.09mΩ to 9.440mΩ
Rated Current _ 0.13A to 13.8A
Packaging _ Tape, Reel

SDS Series

SHIELDED



Size _ 0402BL, 0402, 0804, 1306
Inductance Range _ 0.1μH to 10,000μH
Test Frequency _ 100KHz
Tolerance _ ±20%
SRF _ 0.4MHz to 200MHz

DC Resistance _ 0.021Ω to 74Ω
Current _ 0.01A to 5.6A
Packaging _ Tape, Reel

SDT Series

SHIELDED



Size _ 0402, 0804
Inductance Range _ 1.0μH to 1,000μH
Test Frequency _ 100KHz
Tolerance _ ±20%
SRF _ 2.3MHz to 157MHz

DC Resistance _ 0.025Ω to 8.1Ω
Rated Current _ 0.08A to 5A
Packaging _ Tape, Reel

SLF Series

SHIELDED



Size _ 0628, 0728, 0730, 0732, 0745, 1045, 1055, 1255, 1265, 1275
Inductance Range _ 1.2μH to 1,500μH
Test Frequency _ 1KHz
Tolerance _ ±20%, ±30%

DC Resistance _ 0.0069Ω to 4.78Ω
Rated Current _ 0.13A to 13A
Packaging _ Tape, Reel



SMD Power Inductors

SCDA Series



Size _ 2D12, 2D15, 2D18
 Inductance Range _ 1.2μH to 47μH
 Test Frequency _ 100KHz / 1.0V
 Tolerance _ ±20%, ±30%

DC Resistance _ 120mΩ to 1,700mΩ
 IDC _ 0.23A to 1.3A
 Packaging _ Tape, Reel

STD Series

UNSHIELDED



Size _ 1109
 Inductance Range _ 10μH to 1,200μH
 Test Frequency _ 1KHz
 Tolerance _ ±20%

DC Resistance _ 0.06Ω to 3.5Ω
 Rated Current _ 0.35A to 3.5A
 Packaging _ Tape, Reel

SLH Series



Size _ 6.86 x 6.47 x 3.0, 6.86 x 6.47 x 5.0,
 11.5 x 10.3 x 4.0, 13.2 x 12.9 x 3.5
 Inductance Range _ 0.1μH to 10μH
 Test Frequency _ 100KHz / 1.0V
 Tolerance _ ±15%, ±20%, ±30%

DC Resistance _ 0.88mΩ to 102mΩ
 Rated Current _ 3A to 55A
 Packaging _ Reel

SFI Series



Size _ 100605, 100707
 Inductance Range _ 0.2μH to 0.51μH
 Test Frequency _ 100KHz / 1.0V
 Tolerance _ ±10%, ±15%, ±20%

DC Resistance _ 0.29mΩ to 0.47mΩ
 Packaging _ Reel

DIP Power Inductors

PMC Series



Size _ 11.5 x 11.5 x 8.6, 11.5 x 11.5 x 10.0,
 11.5 x 11.5 x 15.0, 14.0 x 14.0 x 8.5,
 14.0 x 14.0 x 10.0
 Inductance Range _ 0.25μH to 4.7μH
 Test Frequency _ 100MHz
 Tolerance _ ±20%

DC Resistance _ 0.56mΩ to 5.1mΩ
 Rated Current _ 15A to 40A
 Packaging _ Bulk

PMD Series



Size _ 8.5 x 8.3 x 9.7, 10 x 8.2 x 10.5,
 12.5 x 8.5 x 10, 13 x 12.5 x 10
 Inductance Range _ 0.2μH to 1.0μH
 Test Frequency _ 100KHz / 1.0V
 Tolerance _ ±15%, ±20%, ±30%

DC Resistance _ 1mΩ to 10mΩ
 Rated Current _ 10A to 50A
 Packaging _ Bulk

PMF Series



Size _ 8.2 x 8.2 x 6.0, 11.0 x 11.0 x 10,
 11.5 x 11.5 x 8.0, 10.5 x 10.5 x 10,
 11.5 x 11.5 x 10.5, 11.7 x 9.7 x 8.5,
 11.7 x 11.7 x 8.5, 14 x 13 x 11.5
 Inductance Range _ 0.25μH to 220μH
 Test Frequency _ 100KHz / 1.0V
 Tolerance _ ±15%, ±20%, ±30%

DC Resistance _ 0.65mΩ to 305mΩ
 Rated Current _ 10A to 50A
 Packaging _ Bulk

NSF Series



Size _ 8.2 x 8.2 x 7.0, 8.2 x 8.6 x 9.2,
 8.6 x 8.6 x 8.8, 10.5 x 10.5 x 10,
 11.5 x 11.5 x 10, 11.7 x 11.7 x 9.5,
 12.5 x 12.5 x 10, 12.8 x 11 x 10
 Inductance Range _ 0.25μH to 220μH
 Test Frequency _ 100KHz / 1.0V
 Tolerance _ ±15%, ±20%, ±30%

DC Resistance _ 0.5mΩ to 350mΩ
 Rated Current _ 10A to 50A
 Packaging _ Bulk



DIP Power Inductors

MC Series

Size _ 8 x 8 x 8, 8 x 8 x 9.5, 9 x 9 x 9.5,
10 x 9 x 9.8, 11.6 x 11.6 x 9.8,
11.7 x 11.7 x 8.5, 12 x 12 x 7.6,
12 x 12 x 9

Inductance Range _ 0.2 μ H to 4.7 μ H
Test Frequency _ 100KHz / 1.0V
Tolerance _ \pm 15%, \pm 20%, \pm 30%

DC Resistance _ 1m Ω to 10m Ω
Rated Current _ 10A to 50A
Packaging _ Bulk

SLM Series

Size _ 7.7 x 9.5, 8.5 x 8.3, 11.2 x 12.2
Inductance Range _ 1.0 μ H to 4,700 μ H
Tolerance _ \pm 10%, \pm 15%, \pm 20%

DC Resistance _ 0.006 Ω to 7.6 Ω
Packaging _ Bulk

SL Series

CHOKE COILS



Size _ 0406, 0608, 1016
Inductance Range _ 1.0 μ H to 47,000 μ H
Test Frequency _ 1KHz to 7.96MHz
Tolerance _ \pm 10%

DC Resistance _ 0.018 Ω to 190 Ω
IDC _ 15mA to 10A
Packaging _ Tape, Bulk

MB Series

CHOKE COILS



Size _ 5018, 5026, 5052, 6018, 6052
Inductance Range _ 1 μ H to 10 μ H
Test Frequency _ 1KHz to 300KHz
Tolerance _ \pm 15%

DC Current _ 2A to 20A

BC Series

CHOKE COILS



Size _ 1005, 1104, 1305, 1306, 1506, 1806,
2006, 2310, 2711, 3311
Inductance Range _ 30 μ H to 140 μ H
Test Frequency _ 100KHz
Tolerance _ \pm 15%

RDC _ 30m Ω to 71 Ω
Turns _ 24 to 40
Packaging _ Tape, Bulk



YAGEO
A Global Company
www.yageo.com

Global Headquarters

Yageo Corporation
3F 233-1, Baoqiao Rd.
Xindian, Taipei 231
Taiwan
Tel. +886 2 2917 7555 Fax. +886 2 2910 9056

Asia

Beijing, China
Suit 1216, No.8, Jianguomennei Ave.
Dong Cheng District
Beijing COFCO Plaza Tower B
Beijing 100005
P.R.C.
Tel. +86 10 851 20810 Fax. +86 10 851 20200

Dongguan, China
7-1, Gaoli 1st Rd.
Gaoli Industrial Zone
Tangxia, Dongguan
Guangdong Province 523726
P.R.C.
Tel. +86 769 8772 0275 Fax. +86 769 8791 0053

Hong Kong, China
Unit 7, 1F South Seas Ctr.
75 Mody Rd.
Tsimshatsui East
Kowloon
Hong Kong
Tel. +852 2342 6833 Fax. +852 2342 6588

Suzhou, China
10, Zhu Yuan Rd.
Suzhou New District
Suzhou, Jiangsu Province 215011
P.R.C.
Tel. +86 512 6825 5568 Fax. +86 512 6825 5386

Saitama, Japan
16th Namiki Building 3F, 4-116-1
Miya-cho Omiya-ku,
Saitama 330-0802
Japan
Tel. +81 48 795 8953 Fax. +81 48 795 8954

Kyunggi-Do, Korea
Room 1211, Hyundai Office Bldg.
9-4, Sunae-dong, Bundang-Ku
Seongnam-city 463-825
Kyunggi-Do
Korea
Tel. +82 31 712 4797 Fax. +82 31 712 5866

Kuala Lumpur, Malaysia
19, Jalan Puteri 5/8
Bandar Puteri Puchong
47100 Selangor
Malaysia
Tel. +60 3 8060 8864 Fax. +60 3 8068 2700

Singapore
No.514 Chai Chee Lane
#04-14 Bedok Industrial Estate
Singapore 469029
Tel. +65 6244 7800 Fax. +65 6244 4943

**North America****San Jose, U.S.A.**

2665 North 1st St., Suite 212
 San Jose, CA 95134
 U.S.A.
 Tel. +1 408 240 6200 Fax. +1 408 240 6201

Europe**Roermond, Benelux**

Bredeweg 10
 Roermond 6042 GG
 The Netherlands
 Tel. +31 475 385 428 Fax. +31 475 385 589

Brno, Czech Republic

Masna 16
 Brno 60200
 Czech Republic
 Tel. +420 7 2317 5035 Fax. +420 5 4325 4936

Paris, France

41 Boulevard des Bouvets
 Nanterre Cedex 92741
 France
 Tel. +33 1 5551 8404 Fax. +33 1 5551 8407

Hamburg, Germany

Ramskamp 70
 Elmshorn 25337
 Hamburg
 Germany
 Tel. +49 4121 870 189 Fax. +49 4121 870 271

Budapest, Hungary

Vasarter u. 2
 Szombathely 9700
 Hungary
 Tel. +36 13 097 280 Fax. +36 13 097 281

Milan, Italy

Viale Brianza, 20
 20092 Cinisello Balsamo (MI)
 Italy
 Tel. +39 02 6129 1017 Fax. +39 02 6601 7490

Moscow, Russian Federation

24 Kosinskaya St.
 111538 Moscow
 Russian Federation
 Tel. +7 916 625 92 38 Fax. +7 495 374 81 87

Barcelona, Spain

C/ Craywinckel, 8, 4-2
 Barcelona 08022
 Spain
 Tel. +34 93 212 3929 Fax. +39 02 6601 7490

Croydon, UK

Suite 95
 Airport House
 Purley Way, Croydon
 Surrey CR0 0XZ
 United Kingdom
 Tel. +44 208 781 1844 Fax. +44 208 781 1845

For more detailed and always up-to-date contact details of sales offices, distributors and representatives, please go to our web site at
www.yageo.com

© YAGEO Corporation

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.

No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.

Printed in Taiwan

Document order number : YL 100 00119

Date of release : April 2010

Innovative Service Around the Globe **YAGEO**