



> Description



The ACR series is a range of medium power inverters that provide a 230Vac true sinewave output with very low distortion. Designed for connection directly to the train auxiliary supply, the inverters incorporate surge and transient filtering ensuring compliance with both the traditional and latest rail specifications and norms for protection and EMC. The rugged construction and various mounting options ensure compliance with vibration and shock requirements.

Special features include:

- True sinewave output
- 250W continuous output power (400W peak)
- Very low distortion
- Protected to IP65

> Input Specifications

The following input voltages versions are available as standard:

110V	(66.0 - 137.5V)	dc	(Suffix A)
72V	(43.2 - 90.0V)	dc	(Suffix D)
52V	(31.2 - 65.0V)	dc	(Suffix C)
36V	(21.0 - 50.4V)	dc	(Suffix F)
24V	(16.8 - 33.6V)	dc	(Suffix B)

**Other ranges are available to order**

Parameter	Detail
Input Ripple	To EN50155
Input Protection	Reverse polarity protection. Surges and transients EN50155
Inrush Current	Limited to typically 5 x nominal current (after 0.1ms)
Efficiency	75% to 85% dependant on voltage combinations
Hold up time	10ms to EN50155 Class S2— except 24Vdc input.

> Output Specifications

Parameter	Detail									
Maximum Output Power	250W continuous 400W peak (for 15 seconds)									
Output Voltage	230Vac									
Setting Tolerance	±0.6% at 50% load, 15°C to 25°C									
Output frequency	50Hz									
Frequency Tolerance	±2%									
Waveform	True Sinewave									
Harmonic Distortion	<1.5%									
Output Current	1.1A continuous, 1.7 for 15 seconds									
Line & Load Regulation	±5.0% combined									
Temperature Coefficient	<0.02% / °C									
Output Ripple	Typically 5% Pk-Pk of Output Voltage									
Short circuit protection	Latch operates instantaneously if output power exceeds 15A (typically). LED indication provided. Reset by power-down, power-up.									
Delayed current limit	Latch operates if output power exceeds approximately 275W for longer than 16 to 20 seconds. LED indication provided. Reset by power-down, power-up.									
Thermal Protection	Output shuts off when safe internal temperature is exceeded. Auto recovery.									
Isolation	<table border="0"> <tr> <td>Input to Output</td> <td>1.0kV ac</td> <td>(tested at 1.5kV dc)</td> </tr> <tr> <td>Input to Case</td> <td>1.0kV ac</td> <td>(tested at 1.5kV dc)</td> </tr> <tr> <td>Output to Case</td> <td>1.0kV ac</td> <td>(tested at 1.5kV dc)</td> </tr> </table>	Input to Output	1.0kV ac	(tested at 1.5kV dc)	Input to Case	1.0kV ac	(tested at 1.5kV dc)	Output to Case	1.0kV ac	(tested at 1.5kV dc)
Input to Output	1.0kV ac	(tested at 1.5kV dc)								
Input to Case	1.0kV ac	(tested at 1.5kV dc)								
Output to Case	1.0kV ac	(tested at 1.5kV dc)								
Indicators	<table border="0"> <tr> <td>Input OK</td> <td>Green LED</td> </tr> <tr> <td>Output OK</td> <td>Green LED</td> </tr> <tr> <td>Lock out</td> <td>Red LED</td> </tr> <tr> <td>Over-current latch</td> <td>Red LED</td> </tr> </table>	Input OK	Green LED	Output OK	Green LED	Lock out	Red LED	Over-current latch	Red LED	
Input OK	Green LED									
Output OK	Green LED									
Lock out	Red LED									
Over-current latch	Red LED									





> Environmental Details

Parameter	Detail
Operating Temperature	-25°C to +55°C (no derating)
Storage Temperature	-40°C to +85°C
Cooling	By convection
Relative Humidity	99% max.
Shock & Vibration	EN 50155 (EN 61373), RIA 20
Environmental Protection	IP65

> Applicable Norms

Parameter	Detail
EMC	RIA 12, 18; EN50155 (2007), EN50121-3-2 (2006)
Other	RIA 13, 18, 20 EN50155 (2007), LUL G6621

> Mechanical Characteristics

Parameter	Detail
Construction	Fully enclosed in sealed die-cut aluminium case
Dimensions	Length = 280mm Width = 180mm Height = 100mm (Dimensions exclude base plate and connector)
Weight	<6.5kg (5kg excluding mounting plate)
Connections	Input and output via circular bayonet connector (shell size 18-11), earth via M5 stud
Fixings	Base plate allows surface mounting via six $\varnothing$ 9.5mm fixing holes. Other base plates available upon request.

