


18000 series

Snap-action momentary pushbutton switches

Distinctive features and specifications



- Panel and PC mount models
- Snap-in panel mounting version
- Tactile feedback

ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :
 - gold plated brass contacts : 100mA - 30VDC
 - gold plated silver contacts : 1A 125VAC, 1A 30VDC
 - Initial contact resistance : 50 mΩ max.
 - Insulation resistance : 1.000 MΩ min.
 - Dielectric strength : 1.000 Vrms 50 Hz min.
 - Electrical life : 60.000 cycles at full load
- Models for high currents : see 18635A and 18645A at the end of the series.

MATERIALS


- Case : PBT
- Actuator : polyamide, glass filled
- Bushing : brass, nickel plated
- Housing : stainless steel
- Bracket : tin plated steel
- Contacts
 - AD : silver, gold plated
 - CD : brass, gold plated
- Terminal seal : epoxy

GENERAL SPECIFICATIONS


- Total travel : 0,5 mm (.019)
- Torque : 1,25 Nm (.922 Ft.lb) max. applied to nut
- Operating temperature : -30°C to +65°C
- Soldering : 300°C, 3 sec. max.

18000 series

Snap-action momentary pushbutton switches



Overview




ABOUT THIS SERIES

On the following pages, you will find successively :
 - model structure of switches
 - options in the same order as in above chart

Dimensions : first dimensions are in mm while inches are shown as bracketted numbers.




NOTICE : please note that not all combinations of above numbers are available.
 Refer to the following pages for further information.



18000 series

Snap-action momentary pushbutton switches

Overview



Sealing boots are available to protect the switches against dust and water. They are presented in section H.



Mounting accessories : standard hardware supplied with all models with Ø 6,35 (1/4) threaded bushing :
 2 hex nuts 8 mm (.314) across flats, 1 locking ring and 1 lockwasher.
 Standard and special hardware available are presented in section I.





Packaging unit : 25 pieces for W, WW double pole and 18800 models
 50 pieces for other models.


18000 series

Snap-action momentary pushbutton switches


Threaded bushing $\varnothing 6,35$ (1/4) : 18500 - 18700 - 18200



- Solder lug or straight PC terminals
- Epoxy sealed terminals standard



MODEL STRUCTURE




Shown with standard plunger (-13)

Solder lug terminals : 18500




Single pole
18535

Double pole
18545



→ Keyway




Flatted bushing - solder lug terminals : 18700




Single pole
18735

Double pole
18745



→ Flat




Straight PC terminals : 18200




Single pole
18235

Double pole
18245



→ Keyway





18000 series

Snap-action momentary pushbutton switches

Threaded bushing $\varnothing 6,35$ (1/4) : 18900 - Snap-in mounting : 18800

Flatted bushing - straight PC terminals : 18900

→ Flat



Single pole
18935

Double pole
18945




ON



MOM

ON

MOM



Snap-in mounting - solder lug terminals : 18800

Shown with cap U910 + U1200



Single pole
18835

Double pole
18845




ON



MOM

ON


MOM




Available with straight PC terminals : see X662 under "Special options".

PANEL CUT-OUT

18500 - 18200




18700 - 18900




PANEL CUT-OUT

18800



With bezel **U1200**





With bezel **U1210 for LED**

B


18000 series

Snap-action momentary pushbutton switches


Plain bushing : 18200Y - 18200W - 18200WW



- Straight PC or right angle terminals
- Epoxy sealed terminals standard




MODEL STRUCTURE





Shown with standard plunger (-3)

Straight PC terminals - bracket mounting - single pole 18230Y




18235Y




Straight PC terminals - bracket mounting - double pole 18240Y



18245Y





Right angle terminals - horizontal : 18200W



Single pole
18235W

Double pole
18245W






18000 series

Snap-action momentary pushbutton switches

Right angle terminals - vertical : 18200WW



Single pole
18235WW

Double pole
18245WW



1-3

ON




1-2

MOM


ON

MOM




B

CONTACT MATERIALS




AD Silver, gold plated
CD Brass, gold plated


PLUNGERS



Dash compulsory before plunger code.




Ø 4 (.157) - standard with threaded bushing




Ø 3,1 (.122)



If plunger not specified, we supply former default option -13.




Ø 4 (.157) - standard with plain bushing




Ø 3,1 (.122)

18000 series

Snap-action momentary pushbutton switches



SPECIAL OPTIONS



X624 Straight PC terminals - bracket mounting - **with shorter bushing and plunger**

Single pole


18235Y -2X624



ON



MOM



Double pole


18245Y -2X624



ON



MOM



X662 Snap-in mounting - straight PC terminals

Single pole


18835 X662



ON



MOM




Double pole

18845 X662

ON

MOM






18000 series

Snap-action momentary pushbutton switches

SPECIAL OPTIONS (continued)




X371 Plain bushing \varnothing 6,25 mm (.246) (instead of standard threaded bushing).


X372 Shorter threaded bushing \varnothing 6,35 (1/4). Height 7 mm (.274).

X386 Threaded bushing \varnothing 6,35 mm (1/4) to replace plain bushing on models W - WW and Y.


X438 Plain bushing \varnothing 6,25 mm (.246). Height 7,2 mm (.283) - without shoulder.




X372



X438




X371




X386

B


CAPS




Caps for \varnothing 4 (.157) plungers (-13, -3)




U900




U1140




U1720



U480




U630



U2430

Square




U2020

Square


Cap colours			
Replace last "0" by number			
1	blue	5	yellow
1/4	dark blue	6	red
2	black	7	ivory
3	green	7/1	white
4	grey	9	orange

18000 series



Snap-action momentary pushbutton switches








CAPS (continued)





Caps for Ø 3,1 (.122) plungers (-5, -6)



Cap colours	
Replace "0" by number	
1	blue
1/4	dark blue
2	black
3	green
4	grey
5	yellow
6	red
7	ivory
7/1	white
9	orange



Caps for 18800 and 18800X662 models






18000 series

Snap-action momentary pushbutton switches


DRESS NUTS

For models with threaded bushing (18500 - 18700 - 18200 - 18900)


Chrome plated - Order separately.



For caps U1140 and U2510




For cap U480 and U2900





For caps U630 and U3400

BEZELS




For snap-in models (18800 - 18800X662)



For LED Ø 5 - not supplied


Bezel colours	
Replace last "0" by number	
1	blue
1/4	dark blue
2	black
3	green
4	grey
5	yellow
6	red
7	ivory
7/1	white
9	orange

For bracket mounting models (18200Y & 18200YX624)




STANDARD PANEL MOUNTING

Panel thickness with bezel : 1 mm (.039) to 2,5 mm (.098)



18800 + U910 + U1200



18800 + U910 + U1210

18000 series

Snap-action momentary pushbutton switches

For high currents

Tactile feedback

B

ELECTRICAL SPECIFICATIONS

- Max. current/voltage rating with resistive load :
3A 250VAC - 6A 125VAC - 7A 30VDC
- Initial contact resistance : 20 m Ω max. at 0,1A 3VDC
- Insulation resistance : 200.000 M Ω min. between terminals and frame
- Dielectric strength : 1.500 Vrms 50 Hz min.
- Electrical life : 60.000 cycles at full load

GENERAL SPECIFICATIONS


- Travel : 0,90 mm (.035) approx.
- Operating temperature :
-30°C to +85°C

MATERIALS

- Case : diallyphthalate (DAP)
- Actuator : glass filled polyester
- Bushing : brass, nickel plated
- Housing : stainless steel
- Contacts : silver
- Terminal seal : epoxy


18000 series

Snap-action momentary pushbutton switches



- Threaded bushing $\varnothing 6,35$ (1/4)
- Solder lug terminals
- Epoxy sealed terminals


MODEL
STRUCTURE




Single pole




18635A




→ Keyway




Double pole



18645A



→ Keyway




CAPS



Round	
U2400	$\varnothing 5$ (.196)
U2510	$\varnothing 8$ (.314)
U2130	$\varnothing 9,4$ (.370)
U2900	$\varnothing 10$ (.393)
U3400	$\varnothing 15$ (.590)

Square	
U910	Height 4 (.157)
U2340	Height 6 (.236)



For cap dimensions, see "Caps for $\varnothing 3,1$ (.122) plungers" on the preceding pages.