



CUT-OUT



MATERIAL:

Cover: Nylon66, UL rated: 94V-2 min

Base: Nylon66, UL rated: 94V-2 min

Terminal: Brass, silver or tin plated

Rating: 6A 125V AC (UL CUL)

3A 250V AC (UL CUL VDE CE CQC)

Function: ON-OFF-ON

Contact Resistance: 50mΩ Max

Insulation Resistance: 100MΩ Min

Dielectric Strength: 2000VAC 1Am of 1 minute

Electrical life: 10,000 cycles

Mechanical life : 50,000 cycles

Operating Temperature: -20°C~85°C

Safety Approval: cULus, VDE, CQC, CE, RoHS

	X	Y
0.75~1.25	13.6±0.1	8.7±0.1
1.25~2.00	13.7±0.1	8.7±0.1
2.00~3.00	13.8±0.1	8.7±0.1

A	W	R	B	■
灰色	白色	红色	黑色	柄颜色
A	W	R	B	●
灰色	白色	红色	黑色	基座颜色

德崧 DASUNG 东莞市德崧电子有限公司
DASUNG (DONGGUAN) ELECTRONICS CO.,LTD

			公差 TOLERANCES		X±0.3 XX±0.15		角度 ANGLE ±1°		单位 DIMENSION UNIT mm.	
版本 VERSION	A1	比例尺 SCALE	1:1	日期 DATE	2016.8.11	品名 TITLE	MR5-130-C3N-●■	图号 DRAWING NO	MR5-130-C3N-●■_0	
核准 APPROVED BY	<i>[Signature]</i>	核对 CHECKED BY	<i>[Signature]</i>	绘图 DRAWN BY	吴润成					
版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	2016.8.11	ECN NO.						