



- NOTE:
- 1.HOUSE MATERIAL: PBT+30%G.F 94L V-0 COLOR: BLACK.
 - 2.TERMINAL MATERIAL: COPPER ALLOY, THICKNESS = 0.30 ± 0.02 .
FINISH: GOLD PLATE ON CONTACT AREA, TIN PLATE ON SOLDER TAIL, NICKEL ON ALL SURFACE
 - 3.GROUND SPRING PIN: COPPER ALLOY, THICKNESS = 0.25 ± 0.02 .
FINISH: TIN OR GOLD PLATE ON ALL SURFACE, NICKEL ON ALL SURFACE.
 - 4.GROUND PIN: COPPER ALLOY, THICKNESS = 0.25 ± 0.02 mm.
FINISH: TIN OR GOLD PLATE ON ALL SURFACE, NICKEL ON ALL SURFACE
 - 5.OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$.
 - 6.CURRENT RATING: 1 Amp MAX.
 - 7.HSF Concraft level 1
 - 8.●: MANUFACTURER INSPECTION.
 - 9.◆: Q.C INSPECTION.

095BA33M□AA

Plate type:
P:Terminal plate gold flash;switch gold flash

				GENERAL TOLERANCE		DRAW:	PART NO:
				X. ± 0.30	X.° $\pm 2.00^{\circ}$	CHECKED:	095BA33M□AA
				.X ± 0.20	.X° $\pm 1.00^{\circ}$		TITLE:
B	E100189A	Jed	06/24/2010	.XX ± 0.10	.XX° $\pm 0.50^{\circ}$	APPROVE:	SMART CARD CLOSE TYPE
A	E090272A	Tony	09/07/2009	.XXX ± 0.05	.XXX° $\pm 0.10^{\circ}$		DRAWING NO:
REV.	ECO NO.	DRAW.	DATE	UNITS: mm	DATE: 09/07/2009	095BA33M□AA	
MATERIAL:		FINISH:	SCALE: 0.7/1	SHEET: 1/1	REV. B		