



RECOMENDED PCB LAYOUT
TOLERANCE:±0.05(TOP VIEW)
PCB THICKNESS:1.60mm±0.05

NOTE:

- 1.HOUSE MATERIAL: PBT+30%G.F 94L V-0 COLOR: BLACK.
- 2.TERMINAL MATERIAL: COPPER ALLOY, THICKNESS = 0.30±0.02.
FINISH: GOLD PLATE ON CONTACT AREA, TIN PLATE ON SOLDER TAIL,
NICKEL ON ALL SURFACE
- 3.GROUND SPRING PIN: COPPER ALLOY, THICKNESS = 0.25 ± 0.02.
FINISH: TIN OR GOLD PLATE ON ALL SURFACE, NICKEL ON ALL SURFACE.
- 4.GROUND PIN:COPPER ALLOY, THICKNESS = 0.25 ± 0.02mm.
FINISH: TIN OR GOLD PLATE ON ALL SURFACE,NICKEL ON ALL SURFACE
- 5.OPERATING TEMPERATURE: - 40 °C ~ +80 °C .
- 6.CURRENT RATING: 1 Amp MAX.
- 7.HSF Concraft level 1
- 8.● : MANUFACTURER INSPECTION.
- 9.◆ : Q.C INSPECTION.

095BA33P□AA

Plate type:
P:Terminal plate gold flash;switch gold flash

E	E100131A	JED	05/11/2010	GENERAL TOLERANCE		DRAW:	PART NO:
D	E090124A	JED	04/30/2009	X. ±0.30	X.° ±2.00°	JED	095BA33P□AA
C	E080350A	JED	11/28/2008	.X ±0.20	.X° ±1.00°	CHECKED:	TITLE:
B	E080224A	JED	08/20/2008	.XX ±0.10	.XX° ±0.50°	APPROVE:	SMART CARD CLOSE TYPE
REV.	ECO NO.	DRAW.	DATE	.XXX ±0.05	.XXX° ±0.10°		DRAWING NO:
MATERIAL:	FINISH:	SCALE:	SHEET:	UNITS:	DATE:		095BA33P□AA
		0.8/1	1/1	mm	06/25/2008		
				REV. A			