



- NOTE:
- 1.BASE MATERIAL: PBT+30%G.F 94L V-0 COLOR: BLACK.
 - 2.TERMINAL MATERIAL: COPPER ALLOY, THICKNESS = 0.30 ± 0.02 .
FINISH: GOLD PLATE ON CONTACT AREA, TIN PLATE ON SOLDER TAIL,
NICKEL ON ALL SURFACE
 - 3.GROUND SPRING PIN: COPPER ALLOY, THICKNESS = 0.25 ± 0.02 .
FINISH: SEE LEFT NOTE
 - 4.GROUND PIN: COPPER ALLOY, THICKNESS = 0.25 ± 0.02 mm.
FINISH: SEE LEFT NOTE
 - 5.OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$.
 - 6.CURRENT RATING: 1 Amp MAX.
 - 7.HSF Concraft level 1
 - 8.●: MANUFACTURER INSPECTION.
 - 9.◆: Q.C INSPECTION.

095BA64T□AA

Gold plate type:
C:Terminal plate 15u"gold;switch Gold flash
P:Terminal plate gold flash;switch Gold flash

				GENERAL TOLERANCE		DRAW:	PART NO:
				X. ± 0.30	X.° $\pm 2.00^{\circ}$		095BA64T□AA
				.X ± 0.20	.X° $\pm 1.00^{\circ}$	CHECKED:	TITLE:
B	E100221A	JED	08/13/2009	.XX ± 0.10	.XX° $\pm 0.50^{\circ}$		SMART CARD CLOSE TYPE
				.XXX ± 0.05		APPROVE:	DRAWING NO:
A	E090244A	JED	08/13/2009	UNITS: mm	DATE: 08/13/2009		095BA64T□AA
REV.	ECO NO.	DRAW.	DATE				
MATERIAL:	FINISH:	SCALE: 1/1	SHEET: 1/1				