



PANEL CUT-OUT		
Z	X	Y
0.70~1.25	20.2	20
1.25~2.00	20.5	20
2.00~3.00	20.8	20

NOTES:

1. Rating:
CCC 6(3)A 250V AC T105/55
ETL 6GPA 250V AC
6GPA 125V AC T105/55
TUV 6(3)A 250V AC T105/55
CB 6(3)A 250V AC T105/55
2. Circuit Diagram: 3P ON-OFF WITH LAMP
3. Terminal Strength: $\geq 80N$
4. Electrical life: ≥ 10000 cycles
5. Withstand Voltage: $\geq 1500VAC$ 1min
Terminals to Button: $3000VAC$ 1min
Leakage Current: $1mA$
6. Current resistance: $\leq 50m\Omega$ (initial)
7. Insulation resistance: $\geq 100M\Omega$
8. Body Material: NYLON 66 94V-0-2

普通公差:
COMMON TOLERANCE:

施霸(中国)电器制品有限公司
SIBER (CHINA) ELECTRIC MFG. CO., LTD

UP TO 5 ± 0.20

单位 mm

投影

比例

Free

ABOVE 5 TO 30 ± 0.30

核 对

核 对

比 例

KCD3-5

ANGULAR ABOVE 30 ± 0.50

日期

核 准

图 号

KCD3-5-001N

REVISION DESCRIPTION

日期

核 准

图 号

KCD3-5-001N

DATE

REVISION DESCRIPTION

DATE

REVISION DESCRIPTION