



PD548BA

N-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
30V	4.6m Ω @ $V_{GS} = 10V$	85A



TO-252

ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ }^\circ\text{C}$ Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS	SYMBOL	LIMITS	UNITS
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ²	I_D	$T_C = 25\text{ }^\circ\text{C}$	85
		$T_C = 100\text{ }^\circ\text{C}$	54
Pulsed Drain Current ¹	I_{DM}	170	A
Avalanche Current	I_{AS}	38	
Avalanche Energy	E_{AS}	72	mJ
Power Dissipation	P_D	$T_C = 25\text{ }^\circ\text{C}$	59
		$T_C = 100\text{ }^\circ\text{C}$	23
Junction & Storage Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Case	$R_{\theta JC}$		2.1	$^\circ\text{C} / \text{W}$
Junction-to-Ambient	$R_{\theta JA}$		62.5	

¹Pulse width limited by maximum junction temperature.

²Calculated continuous current based on maximum allowable junction temperature, Package limitation current is 40A.

PD548BA N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMIT			UNITS
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0V, I _D = 250μA	30			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	1.5	1.75	2.35	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0V, V _{GS} = ±20V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 24V, V _{GS} = 0V			1	μA
		V _{DS} = 20V, V _{GS} = 0V, T _J = 125 °C			10	
Drain-Source On-State Resistance ¹	R _{DS(ON)}	V _{GS} = 4.5V, I _D = 15A		4.5	7.2	mΩ
		V _{GS} = 10V, I _D = 20A		3.8	4.6	
Forward Transconductance ¹	g _{fs}	V _{DS} = 5V, I _D = 20A		70		S
DYNAMIC						
Input Capacitance	C _{iss}	V _{GS} = 0V, V _{DS} = 15V, f = 1MHz		2320		pF
Output Capacitance	C _{oss}			346		
Reverse Transfer Capacitance	C _{rss}			285		
Gate Resistance	R _g	V _{GS} = 0V, V _{DS} = 0V, f = 1MHz		0.9		Ω
Total Gate Charge ²	Q _g	V _{DS} = 15V, V _{GS} = 10V, I _D = 20A		54		nC
Gate-Source Charge ²	Q _{gs}			7.5		
Gate-Drain Charge ²	Q _{gd}			17.3		
Turn-On Delay Time ²	t _{d(on)}	V _{DS} = 15V, I _D ≅ 20A, V _{GS} = 10V, R _{GEN} = 6Ω		24		nS
Rise Time ²	t _r			16		
Turn-Off Delay Time ²	t _{d(off)}			63		
Fall Time ²	t _f			24		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (T_J = 25 °C)						
Continuous Current ³	I _S				85	A
Forward Voltage ¹	V _{SD}	I _F = 20A, V _{GS} = 0V			1.3	V
Reverse Recovery Time	t _{rr}	I _F = 20A, di _F /dt = 100A / μS		23		nS
Reverse Recovery Charge	Q _{rr}				10	

¹Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.


²Independent of operating temperature.

³Calculated continuous current based on maximum allowable junction temperature, Package limitation current is 40A.


PD548BA

N-Channel Enhancement Mode MOSFET


Output Characteristics




Transfer Characteristics




On-Resistance VS Temperature




Capacitance Characteristic



Gate charge Characteristics




Source-Drain Diode Forward Voltage




PD548BA

N-Channel Enhancement Mode MOSFET


Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve



PD548BA
N-Channel Enhancement Mode MOSFET

Package Dimension

TO-252 (DPAK) MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A	8.9	10	10.41	J	4.8		5.64
B	2.1	2.2	2.5	K	0.15		1.49
C	0.4	0.5	0.61	L	0.4	0.76	0.91
D	0.82	1.2	1.5	M	4.2	4.58	5
E	0.35	0.5	0.65	S	4.57	5.1	5.52
F	0		0.2	T	3.81	4.75	5.24
G	5.3	6.1	6.3	U	1.4		1.78
H	0.5		1.7	V	0.55	1.25	1.7
I	6.3	6.5	6.8				

