

Teledyne 氧传感器

10 种型号，常用型号现货供应

种类	背景气体	对应仪器型号	传感器类型
Trace	Less than 100 ppm CO ₂ in the background gas	311, 316, 317, 318, 3160	B-2C
		3000T series	L-2C
	More than 100 ppm up to 100% CO ₂ in the background gas	All trace oxygen instrument	A-2C
<p>Note: To use the A-2C or B-2C sensor in a 3000T series instrument, adapter part number B66378 is required.</p>			
<p>Note: The L-2C sensor cannot be used in our older analog models (300 series).</p>			
Percent	Less than 100 ppm CO ₂ in the background gas	311P, 320A / P / BRC, 326, 327, 328	B-1, B-3 standard; C-3 for high concentration of O ₂

	More than 1000 ppm up to 100% CO ₂ in the background gas		A-5
--	---	--	-----

C06689-A2C, A-2C, 测量酸性气体或高浓度 CO₂ 中的氧浓度%含量

C06689-A5, A-5, 测量常规混合气体或高浓度 CO₂ 中的氧浓度%含量

C06689-B1, B-1, 测量常规混合气体中的氧浓度%含量; 如: 烟气

C06689-B2C, B-2C, 测量 H₂、He、乙烯等气体中无 CO₂ 的低浓度氧 ppm 含量

C06689-B2CXL, B-2CXL, 测量 H₂、He、乙烯等气体中无 CO₂ 的超低浓度氧 ppm 含量

C06689-B3, B-3, 可用于测量烟气中的氧浓度%含量; 寿命优于 B-1

C06689-L2C, L-2C, 测量常规气体中的低浓度氧 ppm 含量

C06689-L2CL, L-2CL, 测量以 CO₂ 和 H₂ 混合背景的惰性气体中的氧浓度 ppm 含量

C06689-E2, E-2, 测量空气分离-氮液化工艺中, 氮中氧低浓氧含量; 长寿命型

B71875, INSTA TRACE, 测量酸性气体或碳烃类气体中超低浓度氧 ppm 含量

B73106, INSTA TRACE CO₂. 测量酸性气体中 CO₂ 为背景气体的超低浓度氧 ppm 含量