

• ETAB Series 1.6*1.2 Seam Sealing Crystal



FEATURES



- Very compact and thin (1.6*1.2*0.37mm max.)
- Frequency range of 24 to 54M with Fund
- Ideal for Wearable device and Short-range Wireless module
- Lead-free. Meets the requirements for re-flow profiling using lead-free solder

Electrical Specifications


Item	Type	ETAB		
		24 to 29.999MHz	30 to 39.999MHz	40 to 54.000MHz
Frequency Range	F0	24 to 29.999MHz	30 to 39.999MHz	40 to 54.000MHz
Mode of Vibration		Fundamental		
Load Capacitance	CL	8 to 16pF		
Frequency Tolerance	$\Delta F/F_0$	$\pm 10\text{ppm}, \pm 30\text{ppm}, \pm 50\text{ppm}(\text{At } 25^\circ\text{C})$		
Equivalent Series Resistance	ESR	100 Ω max.	80 Ω max.	60 Ω max.
Temperature Stability	TC	$\pm 10\text{ppm}, \pm 15\text{ppm}, \pm 30\text{ppm}(\text{Refer to } 25^\circ\text{C})$		
Operating Temperature Range	T _{OPR}	-20~+70°C, -30~+85°C Option		
Storage Temperature Range	T _{STG}	-55~+125°C		
Shunt Capacitance	C0	3pF max.		
Insulator Resistance	IR	500M Ω min. (At 100V _{DC})		
Drive Level	DL	50 μ W (100 μ W max.)		
Aging	Fa	$\pm 2\text{ppm}$ max. (At 25°C, First year)		
Packing Unit		3000pcs/reel		

**Please contact us for inquiries regarding other Specifications


Mechanical Dimensions(mm)



Top View



Recommended Solder Pattern



TAIWAN:

HOSONIC ELECTRONIC CO., LTD.
23-1 LANE 84. CHUN YING ST. SHULIN CHEN.
TAIPEI 23804. TAIWAN
WEB SITE: <http://www.hosonic.com>

☎: 886-2-86875200
☎: 886-2-26816456
✉: hosonic.sales@hosonic.com

CHINA:

HANGZHOU HOSONIC ELECTRONIC CO., LTD.
NO.242 LIANGBO ROAD. LIANGZHU TOWN.
YUHANG DISTRICT, HANGZHOU, ZHEJIANG, CHINA
WEB SITE: <http://www.hosonic.com>

☎: 86-571-88778189
☎: 86-571-88778857
✉: hosonic.sales@hosonic.com

Specifications are subject to change without notice