

# Clock Oscillators Surface Mount Type

## KC7050P-P2/ KC7050P-P3 Series



LV-PECL/ 3.3V or 2.5V/ 7.0x5.0mm



RoHS Compliant

### Features

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage  $V_{CC} = 3.3V$
- $\pm 25 \times 10^{-6}$  available

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	$\pm 50$	0 to +70	Standard specifications
S	$\pm 30$		
U	$\pm 25$		
F	$\pm 100$	-40 to +85	With only certain frequencies
G	$\pm 50$		
6	$\pm 50$	-40 to +105	

### How to Order

KC7050P 125.000 P 3 0 J 00  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3 : 3.3V or 2 : 2.5V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)  
J : Low Phase Noise
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

### Specifications

Item	Symbol	Specifications		Units	Conditions
		KC7050P-P2	KC7050P-P3		
Output Frequency Range <sup>Note1</sup>	$f_o$	25 to 175		MHz	
Frequency Tolerance	$f_{tol}$	$\pm 50/ -40$ to $+105^\circ C$		ppm	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration
		$\pm 100/ -40$ to $+85^\circ C$			
		$\pm 50/ -40$ to $+85^\circ C$			
		$\pm 50/ 0$ to $+70^\circ C$			
		$\pm 30/ 0$ to $+70^\circ C$			
Storage Temperature Range	$T_{stg}$	-55 to +125		°C	
		0 to +70		°C	Standard Specifications
Operating Temperature Range	$T_{use}$	-40 to +105		°C	Extend (Option)
Max. Supply Voltage	—	-0.5 to +5.0		V	
Supply Voltage	$V_{CC}$	+2.375 to +2.625	+2.97 to +3.63	V	
Current Consumption	$I_{CC}$	90 max.		mA	
Stand-by Current	$I_{std}$	30 max.		$\mu A$	
Symmetry	SYM	50 $\pm$ 5		%	50ohm @crossing point
Rise/ Fall Time (20% $V_{CC}$ to 80% $V_{CC}$ Maximum Loaded)	tr/ tf	0.6 max.		ns	50ohm
Low Level Output Voltage <sup>Note2</sup>	$V_{OL}$	$V_{CC} - 1.810$ to $V_{CC} - 1.405$	$V_{CC} - 1.810$ to $V_{CC} - 1.620$	V	
		$V_{CC} - 1.830$ to $V_{CC} - 1.305$	$V_{CC} - 1.830$ to $V_{CC} - 1.555$		
High Level Output Voltage <sup>Note2</sup>	$V_{OH}$	$V_{CC} - 1.025$ to $V_{CC} - 0.740$	$V_{CC} - 1.025$ to $V_{CC} - 0.880$	V	
		$V_{CC} - 1.085$ to $V_{CC} - 0.880$	$V_{CC} - 1.085$ to $V_{CC} - 0.900$		
Output Load	RL	50		ohm	
Input Voltage Range	$V_{IN}$	0 to $V_{CC}$			
Low Level Input Voltage	$V_{IL}$	30% $V_{CC}$ max.		V	
High Level Input Voltage	$V_{IH}$	70% $V_{CC}$ min.		V	
Disable Time	$t_{dis}$	150 max.		ns	
Enable Time	$t_{ena}$	10 max.		ms	
Start-up Time	$t_{str}$	10 max.		ms	@Minimum operating voltage to be 0 sec.
Deterministic Jitter	DJ	2 max.		ps	
1 Sigma Jitter	J $\sigma$	4 max.		ps	Measured with Wavecrest SIA-3000
Peak to Peak Jitter	J $PK-PK$	30 max.		ps	


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic

### Dimensions

(Unit: mm)



### Recommended Land Pattern

(Unit: mm)

