

Document No.	853-0633
ECN No.	99800
Date of Issue	June 14, 1990
Status	Product Specification
ECL Products	

100180

High Speed 8-Bit Adder

FEATURES

- Typical propagation delay: 2.35ns
- Typical supply current ($-I_{EE}$): 205mA

DESCRIPTION

The 100180 is a high-speed adder that can add two six-bit operands (A_n , B_n) and an Active-Low carry input (\overline{C}_{IN}).


The sum is presented on the function outputs (F_n). When used in conjunction with the 100179, the carry generate and propagate outputs (\overline{G} and \overline{P}) allow more than one 100180 to add operands larger than 6-bits.

All unused inputs can be left open due to integrated pull-down resistors.

PIN DESCRIPTION

PINS	DESCRIPTION
$A_0 - A_5$	Operand A Inputs
$B_0 - B_5$	Operand B Inputs
\overline{C}_{IN}	Carry Input (Active-Low)
\overline{G}	Carry Generate Output (Active-Low)
\overline{P}	Carry Propagate Output (Active-Low)
$F_0 - F_5$	Function Outputs


IEC/IEEE SYMBOL



ORDERING INFORMATION

DESCRIPTION	ORDER CODE
24-Pin Ceramic DIP (400 mils wide)	100180F
24-Pin Ceramic Flat Pack	100180Y
28-Pin PLCC	100180A


PIN CONFIGURATIONS



Adder

100180

LOGIC DIAGRAM



Adder**100180****ABSOLUTE MAXIMUM RATINGS** $V_{CC1} = V_{CC2} = \text{ground}$, $T_A = 0^{\circ}\text{C}$ to $+85^{\circ}\text{C}$ unless otherwise specified.

SYMBOL	PARAMETER	LIMITS	UNIT
V_{EE}	Supply voltage range	-7.0 to +0.5	V
V_{IN}	Input voltage (V_{IN} should never be more negative than V_{EE})	V_{EE} to +0.5	V
I_O	Output source current (continuous)	-55	mA
T_S	Storage temperature range	-65 to +150	$^{\circ}\text{C}$
T_J	Maximum junction temperature	+150	$^{\circ}\text{C}$

NOTE:

Operation beyond the limits set forth in this table may impair the useful life of the device.

DC OPERATING CONDITIONS

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			MIN.	NOM.	MAX.	
V_{CC1}, V_{CC2}	Circuit ground		0	0	0	V
V_{EE}	Supply voltage		-4.8	-4.5	-4.2	V
V_{EE}	Supply voltage when operating with the 10K or the 10KH ECL family		-5.7			V
V_{IH}	High level input voltage	$V_{EE} = -4.2\text{V}$	-1150		-880	mV
		$V_{EE} = -4.5\text{V}$	-1165			
		$V_{EE} = -4.8\text{V}$	-1165			
V_{IL}	Low level input voltage	$V_{EE} = -4.2\text{V}$	-1810		-1475	mV
		$V_{EE} = -4.5\text{V}$			-1475	mV
		$V_{EE} = -4.8\text{V}$			-1490	mV
T_A	Operating ambient temperature range		0	+25	+85	$^{\circ}\text{C}$

NOTE:When operating at other than the specified V_{EE} voltages (-4.2V, -4.5V, -4.8V), the DC and AC electrical characteristics will vary slightly from their specified values.

Adder

100180

DC ELECTRICAL CHARACTERISTICS $V_{CC1} = V_{CC2} = \text{ground}$, $V_{EE} = -4.8\text{V}$ to -4.2V , $T_A = 0^\circ\text{C}$ to $+85^\circ\text{C}$ unless otherwise specified^{1,3,4}

SYMBOL	PARAMETER	TEST CONDITIONS ²			LIMITS			UNIT
					MIN.	TYP.	MAX.	
V _{OH}	High level output voltage	Outputs loaded with 50Ω to -2.0V ±0.010V	Inputs at V _{IHMAX} or V _{ILMIN} .	V _{EE} = -4.2V	-1020		-870	mV
				V _{EE} = -4.5V	-1025	-955	-880	mV
				V _{EE} = -4.8V	-1035		-880	mV
V _{OHT}	High level output threshold voltage		Apply V _{IHMIN} or V _{ILMAX} to one input at a time, other inputs at V _{IHMAX} or V _{ILMIN} .	V _{EE} = -4.2V	-1030			mV
				V _{EE} = -4.5V	-1035			mV
				V _{EE} = -4.8V	-1045			mV
V _{OLT}	Low level output threshold voltage		Apply V _{IHMIN} or V _{ILMAX} to one input at a time, other inputs at V _{IHMAX} or V _{ILMIN} .	V _{EE} = -4.2V			-1595	mV
				V _{EE} = -4.5V			-1610	mV
				V _{EE} = -4.8V			-1610	mV
V _{OL}	Low level output voltage		Inputs at V _{IHMAX} or V _{ILMIN} .	V _{EE} = -4.2V	-1810		-1605	mV
				V _{EE} = -4.5V	-1810	-1705	-1620	mV
				V _{EE} = -4.8V	-1830		-1620	mV
I _{IH}	High level input current	One input under test at V _{IHMAX} . Other inputs at V _{ILMIN} .					220	μA
I _{IL}	Low level input current	One input under test at V _{ILMIN} . Other inputs at V _{IHMAX} .			0.5			μA
-I _{EE}	V _{EE} supply current	All inputs at V _{IHMAX} .			135	205	290	mA

NOTES:

- The specified limits represent the worst case values for the parameter. Since these worst case values normally occur at the supply voltage and temperature extremes, additional noise immunity can be achieved by decreasing the allowable operating condition ranges.
- Conditions for testing shown in the tables are not necessarily worst case. For worst case testing guidelines, refer to DC Testing, Chapter 1, Section 3.
- The specified limits shown in the DC electrical characteristics table can be met only after thermal equilibrium has been established. Thermal equilibrium is established by applying power for at least 2 minutes, while maintaining transverse airflow of 2.5 meters/sec (500 linear feet/min) over the device, mounted either in a test socket or on a printed circuit board. Test voltage values are given in the DC operating conditions table.
- The device can function down to $V_{EE} = -5.7\text{V}$, allowing operation with either the 10K or the 10KH family. Correction factors can be used to calculate new DC limits for the extended V_{EE} range. For more information, see Chapters 5 and 10, Section 4.

AC ELECTRICAL CHARACTERISTICSCeramic DIP $V_{CC1} = V_{CC2} = \text{ground}$, $V_{EE} = -4.8\text{V}$ to -4.2V

SYMBOL	PARAMETER	TEST CONDITION	LIMITS						UNIT
			T _A = 0°C		T _A = +25°C		T _A = +85°C		
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to F _n	Waveform 1	1.10 1.10	4.70 4.70	1.10 1.10	4.60 4.60	1.10 1.10	4.70 4.70	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to P		1.00 1.00	3.00 3.00	1.00 1.00	3.00 3.00	1.00 1.00	3.30 3.30	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to G		1.10 1.10	3.90 3.90	1.20 1.20	3.80 3.80	1.20 1.20	3.90 3.90	ns ns
t _{PLH} t _{PHL}	Propagation delay C _{IN} to F _n		0.90 0.90	4.00 4.00	0.90 0.90	3.90 3.90	0.90 0.90	4.00 4.00	ns ns
t _{TLH} t _{THL}	Transition time F _n , P, G		0.45 0.45	2.30 2.30	0.45 0.45	2.20 2.20	0.45 0.45	2.30 2.30	ns ns

NOTE:

For AC test setup information, see AC Testing, Chapter 2, Section 3.

Adder**100180****AC ELECTRICAL CHARACTERISTICS****Ceramic DIP** $V_{CC1} = V_{CC2} = \text{ground}$, $V_{EE} = -5.2V \pm 5\%$

SYMBOL	PARAMETER	TEST CONDITION	LIMITS						UNIT
			T _A = 0°C		T _A = +25°C		T _A = +85°C		
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to F _n	Waveform 1	1.10 1.10	4.70 4.70	1.10 1.10	4.60 4.60	1.10 1.10	4.70 4.70	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to P̄		1.00 1.00	3.00 3.00	1.00 1.00	3.00 3.00	1.00 1.00	3.30 3.30	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to Ḡ		1.10 1.10	3.90 3.90	1.20 1.20	3.80 3.80	1.20 1.20	3.90 3.90	ns ns
t _{PLH} t _{PHL}	Propagation delay C _{IN} to F _n		0.90 0.90	4.00 4.00	0.90 0.90	3.90 3.90	0.90 0.90	4.00 4.00	ns ns
t _{TLH} t _{THL}	Transition time F _n , P̄, Ḡ		0.45 0.45	2.30 2.30	0.45 0.45	2.20 2.20	0.45 0.45	2.30 2.30	ns ns

NOTE:

For AC test setup information, see AC Testing, Chapter 2, Section 3.

AC ELECTRICAL CHARACTERISTICS**Flat Pack and PLCC** $V_{CC1} = V_{CC2} = \text{ground}$, $V_{EE} = -4.8V$ to $-4.2V$

SYMBOL	PARAMETER	TEST CONDITION	LIMITS						UNIT
			T _A = 0°C		T _A = +25°C		T _A = +85°C		
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to F _n	Waveform 1	1.10 1.10	4.50 4.50	1.10 1.10	4.40 4.40	1.10 1.10	4.50 4.50	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to P̄		1.00 1.00	2.80 2.80	1.00 1.00	2.80 2.80	1.00 1.00	3.10 3.10	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to Ḡ		1.10 1.10	3.70 3.70	1.20 1.20	3.60 3.60	1.20 1.20	3.70 3.70	ns ns
t _{PLH} t _{PHL}	Propagation delay C _{IN} to F _n		0.90 0.90	3.80 3.80	0.90 0.90	3.70 3.70	0.90 0.90	3.80 3.80	ns ns
t _{TLH} t _{THL}	Transition time F _n , P̄, Ḡ		0.45 0.45	2.30 2.30	0.45 0.45	2.20 2.20	0.45 0.45	2.30 2.30	ns ns

NOTE:


For AC test setup information, see AC Testing, Chapter 2, Section 3.

AC ELECTRICAL CHARACTERISTICS**Flat Pack and PLCC** $V_{CC1} = V_{CC2} = \text{ground}$, $V_{EE} = -5.2V \pm 5\%$

SYMBOL	PARAMETER	TEST CONDITION	LIMITS						UNIT
			T _A = 0°C		T _A = +25°C		T _A = +85°C		
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to F _n	Waveform 1	1.10 1.10	4.50 4.50	1.10 1.10	4.40 4.40	1.10 1.10	4.50 4.50	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to P̄		1.00 1.00	2.80 2.80	1.00 1.00	2.80 2.80	1.00 1.00	3.10 3.10	ns ns
t _{PLH} t _{PHL}	Propagation delay A _n , B _n to Ḡ		1.10 1.10	3.70 3.70	1.20 1.20	3.60 3.60	1.20 1.20	3.70 3.70	ns ns
t _{PLH} t _{PHL}	Propagation delay C _{IN} to F _n		0.90 0.90	3.80 3.80	0.90 0.90	3.70 3.70	0.90 0.90	3.80 3.80	ns ns
t _{TLH} t _{THL}	Transition time F _n , P̄, Ḡ		0.45 0.45	2.30 2.30	0.45 0.45	2.20 2.20	0.45 0.45	2.30 2.30	ns ns

NOTE:

For AC test setup information, see AC Testing, Chapter 2, Section 3.

Adder**100180****AC WAVEFORMS****NOTE:**

All power and signal voltages shifted up 2.0V for AC bench test purposes.