	13	12	11	10	9	8	7	6	5	4	3	2	1	
	MATERIAL NUMBER	ENGINEERIN PART NUMBER 1A3006-34		ING NUT ERIAL Rass	COUPLING FINISH nickel pla <sup>-</sup>									J
	1300170012	1A3006-348		SS STEEL	PASSIVATE									
I														I
н														
G						.4 REF.								G
		LE RANGE				1	6							
F	.2048/						(7) -/		(5) -/		(3)-/ (4)-	/ ~7/	8-16 UN	F
E					1									E
D			2		-2	1 2 3								D
			MALE	FACE VIEV	<u>/</u>	<u>wiring</u>	CHART			VOLTAGE RAT AMPERAGE RAT PROTECTION	ING	600VAC/VI 13 AMPS IP67		
С										OPERATING TEMPERATUR SA CERTIFICAT	E	-20°C TO 8 Certified,		С
	ITEM CO	MPONENT	MATERIA		H							LR6837		
В	1 2 PIN 3	INSERT I CONTACTS O-RING	NYLON COPPER ALLOY NITRILE	BLACH GOLD PLATE BLACH	D	81 8/25/09		UNLESS SPE	CIFIED) INCH ±	LDEGE 2009/08/2	 5 <sup>TITLE</sup> MINI C	HANGE ATT		B
	4 C 🗆	JPLING NUT LDED BODY	SEE CHAR		ART	RELEASE NA2010-000		3 PLACES ±.005   2 PLACES ±.013   1 PLACE ±.025	±.010 BWO ±.020 APPRO	ODMAN 2009/08/2	5 .20"	3-POLE MALE <u>48" CABLE F</u> LEX INCORP(	RANGE	_
A	6	GROMMET ORD GRIP BODY	NITRILE	BLACH	<		CH'KD: BWOODMAN APPR: JFMURPHY 200 0=0	ANGULAR ± DRAFT WH APPLICAE MUST REM	±1/2° JFML IERE BLE MAIN SIZE	SEE CHART THIS DRAWING CO	DOCUMENT NO. SD- ONTAINS INFORMATI	<b>130017-007</b>	SHEET NO. <b>1 OF 1</b> TARY TO MOLEX	A
	13	12	11	10	9	8 A	22	6 WITHIN DIMEN	5 SIONS	INCORPORATED AN	ND SHOULD NOT BE	USED WITHOUT WRIT	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	-