

This document was generated on 05/07/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>14-44-5303</u>

Status: Active

Overview: C-Grid® Products

Description: 2.54mm Pitch SL™ Insulation Displacement Connector Assembly, Male, Single Row,

Version D, Back Ribs, for Wire Size 22 AWG, 0.38µm Gold (Au), 3 Circuits

Documents:

<u>3D Model</u> <u>Product Specification PS-70400 (PDF)</u>
<u>Drawing (PDF)</u> <u>RoHS Certificate of Compliance (PDF)</u>

General

Product Family Ribbon Cable / Wire Trap Connectors

Series <u>70475</u>

Comments Terminals Preloaded

Component Type Housing Glow-Wire Compliant No

Overview <u>C-Grid® Products</u>

Product Name SL™

Physical

Circuits (Loaded) 3
Color - Resin Black
Durability (mating cycles max) 50
Entry Angle Vertical
Lock to Mating Part None

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin Polyester Alloy

Number of Rows **PCB** Retention None Packaging Type Tube Pitch - Mating Interface 2.54mm Plating min - Mating 0.381um Plating min - Termination 1.905µm Polarized to Mating Part No Stackable Yes Surface Mount Compatible (SMC) N/A

Temperature Range - Operating -40°C to +105°C Termination Interface: Style IDT or Pierce Wire Insulation Diameter 1.35mm max.

Wire Size AWG

Wire/Cable Type Discrete Wire, Ribbon Cable

Electrical


Current - Maximum per Contact 3A Voltage - Maximum 250V

Material Info

Old Part Number 70475-2347

Reference - Drawing Numbers

Product Specification PS-70400



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status

Not Reviewed

(P)

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

70475Series

Mates With

70004 Interim Clip (Single Row), 70013 Interim Clip (Dual Row)

Use With

7307 Tinned 28AWG, 7767 Topcoat 28AWG, 24241 Tinned 26AWG, 8996 Topcoat 26AWG, 24226 Tinned 24AWG, 8997 Topcoat 24AWG, 24369 High Flex 26AWG, 24389 High Flex 24AWG

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

Description Product #

Ribbon Cable Tool 0622016600 Kit, Press Not Included

This document was generated on 05/07/2012

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION