



14J7

14J7  
TO  
14R7

## TRIODE-HEPTODE CONVERTER

Heater, for Unipotential Cathode:

Voltage. . . . . 12.6<sup>□</sup> . . . . . ac or dc volts

Current. . . . . 0.15<sup>□□</sup> . . . . . amp

*The 14J7 is the same as the 7J7 except for heater rating.*

□ Nominal voltage = 14.0 volts.

□□ Nominal current = 0.16 ampere.

14N7

## MEDIUM-MU TWIN TRIODE

Heater, for Unipotential Cathodes:

Voltage. . . . . 12.6<sup>□</sup> . . . . . ac or dc volts

Current. . . . . 0.3<sup>□□</sup> . . . . . amp

*The 14N7 is the same as the 7N7 except for heater rating.*

□ Nominal voltage = 14.0 volts.

□□ Nominal current = 0.32 ampere.

14Q7

## PENTAGRID CONVERTER

Heater, for Unipotential Cathode:

Voltage. . . . . 12.6<sup>□</sup> . . . . . ac or dc volts

Current. . . . . 0.15<sup>□□</sup> . . . . . amp

*The 14Q7 is the same as the 7Q7 except for heater rating.*

□ Nominal voltage = 14.0 volts.

□□ Nominal current = 0.16 ampere.

14R7

## TWIN DIODE—REMOTE-CUTOFF PENTODE

Heater, for Unipotential Cathode:

Voltage. . . . . 12.6<sup>□</sup> . . . . . ac or dc volts

Current. . . . . 0.15<sup>□□</sup> . . . . . amp

*The 14R7 is the same as the 7R7 except for heater rating.*

□ Nominal voltage = 14.0 volts.

□□ Nominal current = 0.16 ampere.