



158SML6R3M

SURFACE MOUNT

Parts are RoHS compliant

Date code when parts became RoHS: 26

APPLICATIONS: General purpose, filtering, bypass, filtering

ELECTRICAL SPECIFICATIONS

Capacitance: 1500 uF

Dissipation Factor: 0.28 Max at 120 Hz and 20°C

Temperature Range: -40°C to +85°C

ESR: 0.3095 Ohms Max at 20°C and 120 Hz

Impedance: N/A

Tolerance: -20 %, +20 %

WVDC: 6.3 Volts DC

SVDC: 7.9 Volts DC

Ripple Current: 750 mA at 120 Hz and 85°C

Impedance Ratios: -25°C/20°C 5 and -40°C/20°C - 10

Leakage Current: .01CV or 3uA, whichever is greater

94.5 uA after 2 Minutes

Load Life: 2000 hours at 85°C with 100 % of rated voltage and with 0 % of rated ripple current

Capacitance Change: ≤20% of initial measured value

Dissipation Factor: ≤200% of maximum specified value

Leakage Current: ≤100% of maximum specified value

Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.7	1	1.17	1.36	1.5	1.5

Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1.35	1.35	1.35	1.35	1	1	0	0

PHYSICAL DIMENSIONS

Diameter (D): 10 mm + 0.5 mm


Length (L): 10.5 mm + 0.5 mm

Lead Spacing (S): 4.5 mm +/- 0.2 mm

Lead Wire Diameter (d): 0.95 mm +/- 0.15 mm

Lead Length: mm +/- 0.2 mm

Lead Finish: Matte Tin



3757 W. Touhy Ave. Lincolnwood, IL 60712 (847) 675-1760 FAX (847) 673-2850

Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.ilcap.com.hk

© Copyright 2017 Illinois Capacitor. A division of Cornell Dubilier, All Rights Reserved