



# Series 680 Program Header and Cover

## FEATURES


- Complete versatility for programming within the unit itself, thus eliminating the need for DIP switches in many situations.
- Available pre-programmed from Aries, or do-it-yourself using Aries Hand Tool P/N T-680. Consult Data Sheet 22002 for Programming Tool information.
- Available with plain (solid) or "top-slot" press-on covers. Plain covers protect programs while "top-slot" covers allow programming of opposing pins through square openings on top.

## GENERAL SPECIFICATIONS

- STANDARD BODY AND COVER: black UL 94V-0 Glass filled 4/6 Nylon
- PINS: Brass 260 3/4-hard, ASTM B-36
- PIN PLATING: "-T" 50-150 $\mu$  [1.27 $\mu$ ] min. matte Sn per ASTM B545-97(2004) e1 over 50 $\mu$  [1.27 $\mu$ ] min. Ni per SAE AMS-QQ-N-290B; "-TL" 50-150 $\mu$  [1.27 - 3.81 $\mu$ ] min. 60/40 Sn/Pb per SAE AMS-P-81728 over 50 $\mu$  [1.27 $\mu$ ] min. Ni per SAE AMS-QQ-N-290B
- CURRENT RATING: 1 amp
- OPERATING TEMPERATURE: 221°F [105°C]

## MOUNTING CONSIDERATIONS

- SUGGESTED PCB HOLE SIZE: 0.032  $\pm$  0.002 [0.81  $\pm$  0.05] dia.




**CUSTOMIZATION:** In addition to the standard products shown on this page, Aries specializes in custom design and production. Special materials, platings, sizes, and configurations can be furnished, depending on the quantity. **NOTE:** Aries reserves the right to change product general specifications without notice.

## ORDERING INFORMATION

**XX-680-19X XX X**

No. of Pins — 4 thru 24  
 Series —  
 Interconnection Styles — see below  
 Optional Top Slot = "C" preassembled to header Style 191 only  
 Plating —  
 T = Sn  
 TL = Sn/Pb

ALL DIMENSIONS: INCHES [MILLIMETERS]  
 ALL TOLERANCES:  $\pm$ 0.005 [0.13] UNLESS OTHERWISE SPECIFIED  
 "A" # PINS PER ROW  $\times$  0.100 [2.54] +0.050 [1.27]  
 "B" (# PINS PER ROW -1)  $\times$  0.100 [2.54]  
 CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS



## COVER ORDERING INFORMATION

**XX-68X-10**

No. of Pins — 4 thru 24  
 Cover Series — 655 = Plain, 658 = Top Slot  
 Cover No. —

	<b>STYLE 190</b> All pins interconnected, both adjacent and opposing
	<b>STYLE 191</b> Opposing pins interconnected only.



Bristol, PA 19007-6810 USA  
 TEL (215) 781-9956 • FAX (215) 781-9845  
 WWW.ARIESELEC.COM • INFO@ARIESELEC.COM

