

±6 V/+12 V, 5 Ω, LOW r_{ON} SINGLE SPDT ANALOG SWITCH




Check for Samples: [TS12A12511](#)

FEATURES

- ±2.7 V to ±6 V Dual Supply
- 2.7 V to 12 V Single Supply
- 5-Ω (typ) ON-State Resistance
- 1.6-Ω (typ) ON-State Resistance Flatness
- 3.3-V, 5-V Compatible Digital Control Inputs
- Rail-to-Rail Analog Signal Handling
- Fast t_{ON} , t_{OFF} Times
- Tiny 8-Lead SOT-23, 8-Lead MSOP, and QFN-8 Packages
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II
- ESD Performance Tested per JESD 22
 - 2000-V Human-Body Model (A114-B, Class II)
 - 1000-V Charged-Device Model (C101)

APPLICATIONS

- Automatic Test Equipment
- Power Routing
- Communication Systems
- Data Acquisition Systems
- Sample-and-Hold Systems
- Relay Replacement
- Battery-Powered Systems



N.C. – Not internally connected
NC – Normally closed
NO – Normally open

The Exposed Thermal Pad must be electrically connected to V_- or left floating.

DESCRIPTION/ORDERING INFORMATION

The TS12A12511 is a single-pole double-throw (SPDT) analog switch capable of passing signals with swings of 0 to 12 V or –6 V to 6 V. This switch conducts equally well in both directions when it is on. It also offers a low ON-state resistance of 5 Ω (typical), which is matched to within 1 Ω between channels. The max current consumption is <1 μA and –3 dB bandwidth is >93 MHz. The TS12A12511 exhibits break-before-make switching action, preventing momentary shorting when switching channels. This device is available packaged in an 8-lead MSOP, 8-lead SOT-23, and a 8-pin QFN.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

Table 1. ORDERING INFORMATION

T_A	PACKAGE ^{(1) (2)}		ORDERABLE PART NUMBER	TOP-SIDE MARKING
–40°C to 85°C	MSOP – DGK	Tape and reel	TS12A12511DGKR	2US
	QFN – DRJ	Tape and reel	TS12A12511DRJR	ZVE
	SOT – DCN	Tape and reel	TS12A12511DCNR	NFH

- (1) Package drawings, thermal data, and symbolization are available at www.ti.com/packaging.
(2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at www.ti.com.

TRUTH TABLE

IN	NC TO COM, COM TO NC	NO TO COM, COM TO NO
L	On	Off
H	Off	On

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

$T_A = 25^\circ\text{C}$ (unless otherwise noted).

		MIN	MAX	UNIT	
V_+ to V_-			13	V	
V_+ to GND		–0.3	13	V	
V_- to GND		–6.5	0.3	V	
$V_{I/O}$	Analog inputs	$V_- - 0.5$	$V_+ + 0.5$	V	
I_{IN}	Digital inputs		±30	mA	
$I_{I/O}$	Peak current	NC, NO, or COM		±100	mA
	Continuous current	NC, NO, or COM		±50	mA
T_{stg}	Storage temperature range	–65	150	°C	
T_A	Operating temperature range	–40	85	°C	

- (1) Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

THERMAL IMPEDANCE RATINGS

			UNIT
θ_{JA}	Package thermal impedance	DCN package	220
		DGK package	173
		DRJ package	103

ELECTRICAL CHARACTERISTICS

±5-V Dual Supply

 $V_+ = 5\text{ V} \pm 10\%$, $V_- = -5\text{ V} \pm 10\%$, $T_A = -40^\circ\text{C}$ to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	$T_A = 25^\circ\text{C}$			$T_A = -40^\circ\text{C}$ to 85°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Analog Switch									
Analog signal range						V_-	V_+		V
ON-state resistance	r_{ON}	$V_{NC} = -4.5\text{ V}$ to $+4.5\text{ V}$ or $V_{NO} = -4.5\text{ V}$ to $+4.5\text{ V}$, $I_{COM} = -10\text{ mA}$; see Figure 12		5			5	8	Ω
ON-state resistance match between channels	Δr_{ON}	$V_{NC} = -4.5\text{ V}$ to $+4.5\text{ V}$ or $V_{NO} = -4.5\text{ V}$ to $+4.5\text{ V}$, $I_{COM} = -10\text{ mA}$		1	1.2			1.6	Ω
ON-state resistance flatness	$r_{ON(Flat)}$	$V_{NC} = -3.3\text{ V}$ to $+3.3\text{ V}$ or $V_{NO} = -3.3\text{ V}$ to $+3.3\text{ V}$, $I_{COM} = -10\text{ mA}$		1.6	2.2			2.2	Ω
Leakage Currents									
OFF leakage current	$I_{NC(OFF)}$, $I_{NO(OFF)}$	$V_{NC} = -4.5\text{ V}$ to $+4.5\text{ V}$ or $V_{NO} = -4.5\text{ V}$ to $+4.5\text{ V}$ $V_{COM} = -4.5\text{ V}$ to $+4.5\text{ V}$; see Figure 13		± 0.5	± 1			± 50	nA
ON leakage current	$I_{NC(ON)}$, $I_{NO(ON)}$	$V_{NC} = -4.5\text{ V}$ to $+4.5\text{ V}$ or $V_{NO} = -4.5\text{ V}$ to $+4.5\text{ V}$ $V_{COM} = \text{open}$; see Figure 14		± 0.5	± 1			± 50	nA
Digital Inputs									
High-level input voltage	V_{INH}					2.4	V_+		V
Low-level input voltage	V_{INL}					0	0.8		V
Input current	I_{INL} , I_{INH}	$V_{IN} = V_{INL}$ or V_{INH}		0.005				± 1	μA
Control input capacitance	C_{IN}			2.5					pF
Dynamic⁽¹⁾									
Turn-ON time	t_{ON}	$R_L = 300\ \Omega$, $C_L = 35\text{ pF}$, $V_{COM} = 3.3\text{ V}$; see Figure 16		80	95			115	ns
Turn-OFF time	t_{OFF}	$R_L = 300\ \Omega$, $C_L = 35\text{ pF}$, $V_{COM} = 3.3\text{ V}$		41	50			56	ns
Break-before-make time delay	t_{BBM}	$R_L = 300\ \Omega$, $C_L = 35\text{ pF}$, $V_{NC} = V_{NO} = 3.3\text{ V}$; see Figure 17		36			18		ns
Charge injection	Q_C	$V_{NC} = V_{NO} = 0\text{ V}$, $R_{GEN} = 0\ \Omega$, $C_L = 1\text{ nF}$; see Figure 18		26					pC
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, $C_L = 5\text{ pF}$, $f = 1\text{ MHz}$; see Figure 19		-70					dB
Channel-to-channel crosstalk	X_{TALK}	$R_L = 50\ \Omega$, $C_L = 5\text{ pF}$, $f = 1\text{ MHz}$, see Figure 20		-70					dB
Bandwidth -3 dB	BW	$R_L = 50\ \Omega$, $C_L = 5\text{ pF}$; see Figure 21		93					MHz
Total harmonic distortion	THD	$R_L = 600\ \Omega$, $C_L = 15\text{ pF}$, $V_{NO} = 1V_{RMS}$, $f = 20\text{ kHz}$; see Figure 22		0.004					%
NC, NO OFF capacitance	$C_{NC(OFF)}$, $C_{NO(OFF)}$	$f = 1\text{ MHz}$; see Figure 15		14					pF
COM, NC, NO ON capacitance	$C_{COM(ON)}$, $C_{NC(ON)}$, $C_{NO(ON)}$	$f = 1\text{ MHz}$; see Figure 15		60					pF
Supply									
Positive supply current	I_+			0.03				1	μA

(1) Ensured by design, not subject to production test.

ELECTRICAL CHARACTERISTICS

12-V Single Supply

 $V_+ = 12\text{ V} \pm 10\%$, $V_- = 0\text{ V}$, $\text{GND} = 0\text{ V}$, $T_A = -40^\circ\text{C}$ to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	$T_A = 25^\circ\text{C}$			$T_A = -40^\circ\text{C}$ to 85°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Analog Switch									
Analog signal range						0		V_+	V
ON-state resistance	r_{on}	$V_{\text{NC}} = 0\text{ V}$ to 10.8 V or $V_{\text{NO}} = 0\text{ V}$ to 10.8 V , $I_{\text{COM}} = -10\text{ mA}$, see Figure 12		5			5	8	Ω
ON-state resistance match between channels	Δr_{on}	$V_{\text{NC}} = 0\text{ V}$ to 10.8 V or $V_{\text{NO}} = 0\text{ V}$ to 10.8 V , $I_{\text{COM}} = -10\text{ mA}$		1.6	2.4			2.6	Ω
ON-state resistance flatness	$r_{\text{on(flat)}}$	$V_{\text{NC}} = 3.3\text{ V}$ to 7 V or $V_{\text{NO}} = 3.3\text{ V}$ to 7 V , $I_{\text{COM}} = -10\text{ mA}$		1.7			1.8	3.2	Ω
Leakage Currents									
OFF leakage current	$I_{\text{NC(OFF)}}$, $I_{\text{NO(OFF)}}$	$V_{\text{NC}} = 0\text{ V}$ to 10.8 V or $V_{\text{NO}} = 0\text{ V}$ to 10.8 V , $V_{\text{COM}} = 0\text{ V}$ to 10.8 V ; see Figure 13		± 0.5	± 10			± 50	nA
ON leakage current	$I_{\text{NC(ON)}}$, $I_{\text{NO(ON)}}$	$V_{\text{NC}} = 0\text{ V}$ to 10.8 V or $V_{\text{NO}} = 0\text{ V}$ to 10.8 V , $V_{\text{COM}} = \text{open}$; see Figure 14		± 0.5	± 10			± 50	nA
Digital Inputs									
High-level input voltage	V_{INH}					5		V_+	V
Low-level input voltage	V_{INL}					0		0.8	V
Input current	I_{INL} , I_{INH}	$V_{\text{IN}} = V_{\text{INL}}$ or V_{INH}		± 0.005				± 0.1	μA
Digital input capacitance	C_{IN}			2.7					pF

ELECTRICAL CHARACTERISTICS
12-V Single Supply (continued)
 $V_+ = 12\text{ V} \pm 10\%$, $V_- = 0\text{ V}$, $\text{GND} = 0\text{ V}$, $T_A = -40^\circ\text{C}$ to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	$T_A = 25^\circ\text{C}$			$T_A = -40^\circ\text{C}$ to 85°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Dynamic⁽¹⁾									
Turn-ON time	t_{ON}	$R_L = 300\ \Omega$, $C_L = 35\ \text{pF}$, $V_{\text{COM}} = 3.3\ \text{V}$; see Figure 16		56	85			110	ns
Turn-OFF time	t_{OFF}	$R_L = 300\ \Omega$, $C_L = 35\ \text{pF}$, $V_{\text{COM}} = 3.3\ \text{V}$; see Figure 16		25	30			31	ns
Break-before-make time delay	t_{BBM}	$R_L = 300\ \Omega$, $C_L = 35\ \text{pF}$, $V_{\text{NC}} = V_{\text{NO}} = 3.3\ \text{V}$; see Figure 17		30		19			ns
Charge injection	Q_C	$R_{\text{GEN}} = V_{\text{NC}} = V_{\text{NO}} = 0\ \text{V}$, $R_{\text{GEN}} = 0\ \Omega$, $C_L = 1\ \text{nF}$; see Figure 18		491					pC
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, $C_L = 5\ \text{pF}$, $f = 1\ \text{MHz}$, see Figure 19		-70					dB
Channel-to-channel crosstalk	X_{TALK}	$R_L = 50\ \Omega$, $C_L = 5\ \text{pF}$, $f = 1\ \text{MHz}$, see Figure 20		-70					dB
Bandwidth -3 dB	BW	$R_L = 50\ \Omega$, $C_L = 5\ \text{pF}$, see Figure 21		122					MHz
Total harmonic distortion	THD	$R_L = 600\ \Omega$, $C_L = 15\ \text{pF}$, $V_{\text{NO}} = 1\ \text{V}_{\text{RMS}}$, $f = 20\ \text{kHz}$; see Figure 22		0.04					%
NC, NO OFF capacitance	$C_{\text{NC(OFF)}}$, $C_{\text{NO(OFF)}}$	$f = 1\ \text{MHz}$, see Figure 15		14					pF
COM, NC, NO ON capacitance	$C_{\text{COM(ON)}}$, $C_{\text{NC(ON)}}$, $C_{\text{NO(ON)}}$	$f = 1\ \text{MHz}$, see Figure 15		55					pF
Supply									
Positive supply current	I_+			0.07				1	μA

(1) Ensured by design, not subject to production test.

ELECTRICAL CHARACTERISTICS

5-V Single Supply

$V_+ = 5\text{ V} \pm 10\%$, $V_- = 0\text{ V}$, $\text{GND} = 0\text{ V}$, $T_A = -40^\circ\text{C}$ to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	$T_A = 25^\circ\text{C}$			$T_A = -40^\circ\text{C}$ to 85°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Analog Switch									
Analog signal range						0	V_+		V
ON-state resistance	r_{on}	$V_{\text{NC}} = 0\text{ V}$ to 4.5 V or $V_{\text{NO}} = 0\text{ V}$ to 4.5 V ; $I_{\text{COM}} = -10\text{ mA}$; see Figure 12		8	10			12.5	Ω
ON-state resistance match between channels	Δr_{on}	$V_{\text{NC}} = 0\text{ V}$ to 4.5 V or $V_{\text{NO}} = 0\text{ V}$ to 4.5 V ; $I_{\text{COM}} = -10\text{ mA}$		1	1.1			1.5	Ω
ON-state resistance flatness	$r_{\text{on(Flat)}}$	$V_{\text{NC}} = 0\text{ V}$ to 4.5 V or $V_{\text{NO}} = 0\text{ V}$ to 4.5 V ; $I_{\text{COM}} = -10\text{ mA}$		1.3			1.3	2	Ω
Leakage Currents									
OFF leakage current	$I_{\text{NC(OFF)}}$, $I_{\text{NO(OFF)}}$	$V_{\text{NC}} = 0\text{ V}$ to 4.5 V or $V_{\text{NO}} = 0\text{ V}$ to 4.5 V ; $V_{\text{COM}} = 0\text{ V}$ to 4.5 V ; see Figure 13		± 0.5	± 1			± 50	nA
ON leakage current	$I_{\text{NC(ON)}}$, $I_{\text{NO(ON)}}$	$V_{\text{NC}} = 0\text{ V}$ to 4.5 V or $V_{\text{NO}} = 0\text{ V}$ to 4.5 V ; $V_{\text{COM}} = \text{open}$; see Figure 14		± 0.5	± 1			± 50	nA
Digital Inputs									
High-level input voltage	V_{INH}					2.4	V_+		V
Low-level input voltage	V_{INL}					0	0.8		V
Input current	I_{INL} , I_{INH}	$V_{\text{IN}} = V_{\text{INL}}$ or V_{INH}		0.01				± 0.1	μA
Digital input capacitance	C_{IN}			2.8					pF

ELECTRICAL CHARACTERISTICS
5-V Single Supply (continued)
 $V_+ = 5\text{ V} \pm 10\%$, $V_- = 0\text{ V}$, $\text{GND} = 0\text{ V}$, $T_A = -40^\circ\text{C}$ to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	$T_A = 25^\circ\text{C}$			$T_A = -40^\circ\text{C}$ to 85°C			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
Dynamic⁽¹⁾									
Turn-ON time	t_{ON}	$R_L = 300\ \Omega$, $C_L = 35\ \text{pF}$, $V_{\text{COM}} = 3.3\ \text{V}$; see Figure 16		119	145			178	ns
Turn-OFF time	t_{OFF}	$R_L = 300\ \Omega$, $C_L = 35\ \text{pF}$, $V_{\text{COM}} = 3.3\ \text{V}$; see Figure 16		38	47			95.2	ns
Break-before-make time delay	t_{BBM}	$R_L = 300\ \Omega$, $C_L = 35\ \text{pF}$, $V_{\text{NC}} = V_{\text{NO}} = 3.3\ \text{V}$; see Figure 17		79		44			ns
Charge injection	Q_C	$V_{\text{GEN}} = V_{\text{NC}} = V_{\text{NO}} = 0\ \text{V}$, $R_{\text{GEN}} = 0\ \Omega$, $C_L = 1\ \text{nF}$; see Figure 18		65					pC
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, $C_L = 5\ \text{pF}$, $f = 1\ \text{MHz}$, see Figure 19		-70					dB
Channel-to-channel crosstalk	X_{TALK}	$R_L = 50\ \Omega$, $C_L = 5\ \text{pF}$, $f = 1\ \text{MHz}$, see Figure 20		-70					dB
Bandwidth -3 dB	BW	$R_L = 50\ \Omega$, see Figure 21		152					MHz
Total harmonic distortion	THD	$R_L = 600\ \Omega$, $C_L = 15\ \text{pF}$, $V_{\text{NO}} = 1\ \text{V}_{\text{RMS}}$, $f = 20\ \text{kHz}$; see Figure 22		0.04					%
NC, NO OFF capacitance	$C_{\text{NC(OFF)}}$, $C_{\text{NO(OFF)}}$	$f = 1\ \text{MHz}$, see Figure 15		15					pF
COM, NC, NO ON capacitance	$C_{\text{COM(ON)}}$, $C_{\text{NC(ON)}}$, $I_{\text{NO(ON)}}$	$f = 1\ \text{MHz}$, see Figure 15		55					pF
Power Requirements									
V_+ supply current	I_+	$V_{\text{IN}} = 0\ \text{V}$ or V_+		0.02				1	μA

(1) Ensured by design, not subject to production test.

PIN CONFIGURATIONS AND FUNCTION DESCRIPTIONS
Pin Function Descriptions

TERMINAL		DESCRIPTION
NAME	NO.	
1	COM	Common terminal. Can be an input or output.
2	NC	Normally closed. Can be an input or output.
3	GND	Ground (0 V) reference
4	V_+	Most positive power supply
5	N.C.	No connect. Not internally connected.
6	IN	Logic control input
7	V_-	Most negative power supply. This pin is only used in dual-supply applications and should be tied to ground in single-supply applications.
8	NO	Normally open. Can be an input or output.

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. r_{ON} vs V_{IO}




Figure 2. Leakage Current vs I/O voltage (Switch ON)




Figure 3. Leakage Current vs I/O Voltage (Switch OFF)




Figure 4. Positive Supply Current vs Temperature




Figure 5. Negative Supply Current vs Temperature




Figure 6. Control Input (IN) Threshold Voltage

TYPICAL PERFORMANCE CHARACTERISTICS (continued)




Figure 7. Bandwidth Dual Supply (±5V)




Figure 8. Off Isolation vs Frequency Dual Supply (±5v)




Figure 9. Crosstalk vs Frequency Dual Supply (±5V)




Figure 10. THD+N (%) vs Frequency

TYPICAL PERFORMANCE CHARACTERISTICS (continued)




Figure 11. Charge Injection vs Bias Voltage

TEST CIRCUITS




Figure 12. ON-State Resistance




Figure 13. OFF-State Leakage Current ($I_{COM(OFF)}$, $I_{NC(OFF)}$)




Figure 14. ON-State Leakage Current ($I_{COM(ON)}$, $I_{NC(ON)}$)






Figure 15. Capacitance ($C_{COM(OFF)}$, $C_{COM(ON)}$, $C_{NC(OFF)}$, $C_{NC(ON)}$)




(1) All input pulses are supplied by generators having the following characteristics: PRR \approx 10 MHz, $Z_O = 50 \Omega$, $t_r < 5 \text{ ns}$, $t_f < 5 \text{ ns}$.
 (2) C_L includes probe and jig capacitance.

Figure 16. Turn-ON (t_{ON}) and Turn-OFF Time (t_{OFF})



- (1) All input pulses are supplied by generators having the following characteristics: PRR ≈ 10 MHz, Z_O = 50 Ω, t_r < 5 ns, t_f < 5 ns.
- (2) C_L includes probe and jig capacitance.

Figure 17. Break-Before-Make Time Delay (t_{BBM})



- (1) C_L includes probe and jig capacitance.
- (2) All input pulses are supplied by generators having the following characteristics: PRR ≈ 10 MHz, Z_O = 50 Ω, t_r < 5 ns, t_f < 5 ns.

Figure 18. Charge Injection (Q_C)




Figure 19. OFF Isolation (O_{ISO})




Figure 20. Channel-to-Channel Crosstalk (X_{TALK})





Figure 21. Bandwidth (BW)





(1) C_L includes probe and jig capacitance.

Figure 22. Total Harmonic Distortion

REVISION HISTORY

Changes from Revision A (May 2010) to Revision B	Page
• Deleted preview status from DGK and DCN packages.	1

TAPE AND REEL INFORMATION
REEL DIMENSIONS

TAPE DIMENSIONS


A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

TAPE AND REEL INFORMATION

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TS12A12511DCNR	SOT-23	DCN	8	3000	180.0	8.4	3.23	3.17	1.37	4.0	8.0	Q3
TS12A12511DGKR	MSOP	DGK	8	2500	330.0	12.4	5.3	3.4	1.4	8.0	12.0	Q1
TS12A12511DRJR	SON	DRJ	8	1000	180.0	12.4	4.25	4.25	1.15	8.0	12.0	Q2


TAPE AND REEL BOX DIMENSIONS


*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TS12A12511DCNR	SOT-23	DCN	8	3000	202.0	201.0	28.0
TS12A12511DGKR	MSOP	DGK	8	2500	358.0	335.0	35.0
TS12A12511DRJR	SON	DRJ	8	1000	210.0	185.0	35.0

DCN (R-PDSO-G8)


PLASTIC SMALL-OUTLINE PACKAGE (DIE DOWN)



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Package outline exclusive of metal burr & dambar protrusion/intrusion.
 - D. Package outline inclusive of solder plating.
 - E. A visual index feature must be located within the Pin 1 index area.
 - F. Falls within JEDEC MO-178 Variation BA.
 - G. Body dimensions do not include flash or protrusion. Mold flash and protrusion shall not exceed 0.25 per side.

DCN (R-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE (DIE DOWN)




4211034/B 01/12

- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525.
 - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

DRJ (S-PWSON-N8)

PLASTIC SMALL OUTLINE NO-LEAD



4205439/C 12/10

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
 - B. This drawing is subject to change without notice.
 - C. SON (Small Outline No-Lead) package configuration.
 - The package thermal pad must be soldered to the board for thermal and mechanical performance. See the Product Data Sheet for details regarding the exposed thermal pad dimensions.
 - E. Package complies to JEDEC MO-229 variation WGGB.

THERMAL PAD MECHANICAL DATA

DRJ (S-PWSON-N8)


PLASTIC SMALL OUTLINE NO-LEAD

THERMAL INFORMATION

This package incorporates an exposed thermal pad that is designed to be attached directly to an external heatsink. The thermal pad must be soldered directly to the printed circuit board (PCB). After soldering, the PCB can be used as a heatsink. In addition, through the use of thermal vias, the thermal pad can be attached directly to the appropriate copper plane shown in the electrical schematic for the device, or alternatively, can be attached to a special heatsink structure designed into the PCB. This design optimizes the heat transfer from the integrated circuit (IC).

For information on the Quad Flatpack No-Lead (QFN) package and its advantages, refer to Application Report, QFN/SON PCB Attachment, Texas Instruments Literature No. SLUA271. This document is available at www.ti.com.

The exposed thermal pad dimensions for this package are shown in the following illustration.



Bottom View


Exposed Thermal Pad Dimensions

4206882/F 01/11

NOTE: All linear dimensions are in millimeters

DRJ (S-PWSON-N8)

SMALL PACKAGE OUTLINE NO-LEAD



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. This package is designed to be soldered to a thermal pad on the board. Refer to Application Note, Quad Flat-Pack Packages, Texas Instruments Literature No. SLUA271, and also the Product Data Sheets for specific thermal information, via requirements, and recommended board layout. These documents are available at www.ti.com <<http://www.ti.com>>.
 - E. Laser cutting apertures with electropolish and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC 7525 for stencil design considerations.
 - F. Customers should contact their board fabrication site for solder mask tolerances and vias tenting recommendations for vias placed in the thermal pad.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Mobile Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community Home Page

e2e.ti.com

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2012, Texas Instruments Incorporated