





NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. CONTACTS: COPPER ALLOY
PLATING: GOLD over NICKEL
4. THREADED INSERTS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
5. COLLARS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
7. CONNECTOR IS PART MARKED: 163A11419X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH										tolerance			 dim. in mm	scale: 2:1 (5:1)						
														material: see notes						
										DO NOT ALTER CAD DRAWING BY HAND						date	name	title: D-SUB MALE 9pos. SOLDER PIN STRAIGHT with threaded insert		
										a	Original					drawn	29.03.12	Henneboel		
rev.	description	date	name			appd.	30.03.12	Fischer												
						norm														
						d-old			dwg no: DIN-A3 16K1A3049 sh: 1											
									part no: 163A11419X											

CONEC