


ST SERIES

Standard

- Surface-mounted device.
- Non-polar capacitor.
- Lead free reflow soldering is available.

RoHS
compliance




◆SPECIFICATIONS

Items	Characteristics	
Category Temperature Range	-55~+125°C	
Rated Voltage Range	16~63Vdc	100Vdc
Capacitance Range	0.047~22μF (473~226)	0.001~0.1μF (102~104)
Capacitance Tolerance	±10% (K), ±20% (M)	
Dissipation Factor (tanδ)	1.5% or less(1kHz±20%, 5Vrms or less)	
Voltage Proof	Nothing abnormal shall be found, when applying 150% of the rated voltage for 1 minute or 175% of the rated voltage for 1 second to 5 seconds.	
Insulation Resistance	C≤0.1μF:3000MΩ or more (After 1 minute application of rated voltage) C>0.1μF:300MΩ·μF or more (After 1 minute application of rated voltage)	1000MΩ or more (After 1 minute application of rated voltage)

◆PART NUMBER

Rated Voltage	Series	Capacitance	Capacitance Tolerance	Option	TP code	Chip Size
Code		Code	Code			Code
16	ST	102	K			3216
25		473	M			3225
35		684				4532
50		335				5750
63		106				
100		226				
Rated Voltage		Capacitance	Tolerance			Chip Size
16Vdc		0.001μF	±10%			3.2×1.6mm
25Vdc		0.047μF	±20%			3.2×2.5mm
35Vdc		0.68μF				4.5×3.2mm
50Vdc		3.3μF				5.7×5.0mm
63Vdc		10μF				
100Vdc		22μF				

◆PERMISSIBLE CURRENT FOR FREQUENCY



◆STANDARD SIZE

□:Capacitance Tolerance

Rated Voltage (Vdc)	Capacitance (μF)	Size			Part No.
		L (mm)	W (mm)	H (mm)	
16	1.0	3.2	1.6	1.4	16ST105□A23216
	1.5	3.2	1.6	1.4	16ST155□A23216
	2.2	3.2	2.5	1.8	16ST225□B23225
	3.3	3.2	2.5	2.0	16ST335□B33225
	4.7	4.5	3.2	1.4	16ST475□C14532
	6.8	4.5	3.2	1.8	16ST685□C24532
	10	4.5	3.2	2.6	16ST106□C44532
	15	5.7	5.0	1.8	16ST156□D15750
	22	5.7	5.0	2.6	16ST226□D35750
25	0.68	3.2	1.6	1.4	25ST684□A23216
	1.0	3.2	1.6	1.4	25ST105□A23216
	1.5	3.2	2.5	2.0	25ST155□B33225
	2.2	3.2	2.5	1.8	25ST225□B23225
	3.3	4.5	3.2	1.4	25ST335□C14532
	4.7	4.5	3.2	1.8	25ST475□C24532
	6.8	4.5	3.2	2.6	25ST685□C44532
	10	5.7	5.0	1.8	25ST106□D15750
	15	5.7	5.0	2.6	25ST156□D35750
35	0.47	3.2	1.6	1.0	35ST474□A13216
	0.68	3.2	1.6	1.4	35ST684□A23216
	1.0	3.2	2.5	1.4	35ST105□B13225
	1.5	3.2	2.5	2.0	35ST155□B33225
	2.2	4.5	3.2	1.4	35ST225□C14532
	3.3	4.5	3.2	1.8	35ST335□C24532
	4.7	4.5	3.2	2.6	35ST475□C44532
	6.8	5.7	5.0	1.8	35ST685□D15750
	10	5.7	5.0	2.6	35ST106□D35750
50	0.10	3.2	1.6	1.0	50ST104□A13216
	0.15	3.2	1.6	1.0	50ST154□A13216
	0.22	3.2	1.6	1.0	50ST224□A13216
	0.33	3.2	1.6	1.4	50ST334□A23216
	0.47	3.2	2.5	1.4	50ST474□B13225
	0.68	3.2	2.5	1.8	50ST684□B23225
	1.0	4.5	3.2	1.4	50ST105□C14532
	1.5	4.5	3.2	1.8	50ST155□C24532
	2.2	4.5	3.2	2.6	50ST225□C44532
	3.3	5.7	5.0	1.8	50ST335□D15750
	4.7	5.7	5.0	2.6	50ST475□D35750

Rated Voltage (Vdc)	Capacitance (μF)	Size			Part No.
		L (mm)	W (mm)	H (mm)	
63	0.047	3.2	1.6	1.0	63ST473□A13216
	0.068	3.2	1.6	1.0	63ST683□A13216
	0.10	3.2	1.6	1.0	63ST104□A13216
	0.15	3.2	1.6	1.0	63ST154□A13216
	0.22	3.2	1.6	1.4	63ST224□A23216
	0.33	3.2	2.5	1.4	63ST334□B13225
	0.47	3.2	2.5	1.8	63ST474□B23225
	0.68	4.5	3.2	1.4	63ST684□C14532
	1.0	4.5	3.2	1.8	63ST105□C24532
	1.5	4.5	3.2	2.6	63ST155□C44532
	2.2	5.7	5.0	1.8	63ST225□D15750
	3.3	5.7	5.0	2.6	63ST335□D35750
100	0.0010	3.2	1.6	1.0	100ST102□A13216
	0.0015	3.2	1.6	1.0	100ST152□A13216
	0.0022	3.2	1.6	1.0	100ST222□A13216
	0.0033	3.2	1.6	1.0	100ST332□A13216
	0.0047	3.2	1.6	1.0	100ST472□A13216
	0.0068	3.2	1.6	1.0	100ST682□A13216
	0.010	3.2	1.6	1.0	100ST103□A13216
	0.015	3.2	1.6	1.0	100ST153□A13216
	0.022	3.2	1.6	1.0	100ST223□A13216
	0.033	3.2	1.6	1.0	100ST333□A13216
	0.047	3.2	1.6	1.4	100ST473□A23216
	0.068	3.2	2.5	1.4	100ST683□B13225
	0.10	3.2	2.5	1.8	100ST104□B23225

Size Code Conversion

mm	inch
3216	1206
3225	1210
4532	1812
5750	2220

◆DIMENSIONS

(mm)

