

DCP01 系列 1W、1000V_{RMS} 隔离式非稳压直流/直流转换器模块

1 特性

- 1kV 隔离(工作):1 秒测试
- 在隔离层中施加连续电压:60VDC/42.5VAC
- UL1950 认证组件
- EN55022 B 类 EMC 性能
- 7 引脚 PDIP 和 7 引脚 SOP 封装
- 输入电压:5V、15V或24V
- 输出电压: ±5V、±6.5V、±12V 或 ±15V
- 器件间同步
- 过热保护
- 短路保护
- 高效率

2 应用

- 信号路径隔离
- 消除接地环路
- 数据采集
- 工业控制和仪表
- 测试设备

3 说明

DCP01B 系列是 1W 隔离式非稳压直流/直流转换器模块。DCP01B 系列器件具有片上器件保护,只需要很少的外部元件即可提供额外的功能,例如输出禁用和开关频率同步。

DCP01B 系列器件集这些特性和较小的尺寸于一体, 非常适合用于各种应用,并且对需要信号路径隔离的应 用来说,它是一个易于使用的解决方案。

警告:此产品具有运行隔离功能,仅可用于信号隔离。不可作为需 要增强型隔离的安全隔离电路的一部分使用。请参阅*特性说明* 中的 定义。

器件信息						
器件型号	封装 ⁽¹⁾	封装尺寸(标称值)				
	PDIP (7)	10 18mm x 10 60mm				
DCFUTXXXD	SOP (7)	19.101111 ~ 10.001111				

(1) 要了解所有可用封装,请参见数据表末尾的可订购产品附录。





Table of Contents

1	特性1	
2	应用1	
3	说明1	
4	Revision History	2
5	Pin Configuration and Functions4	÷
	Pin Functions4	÷
6	Specifications5	,
	6.1 Absolute Maximum Ratings5	,
	6.2 ESD Ratings5	,
	6.3 Recommended Operating Conditions5	,
	6.4 Thermal Information5	,
	6.5 Electrical Characteristics6	
	6.6 Switching Characteristics6	
	6.7 Typical Characteristics7	
7	Detailed Description12	2
	7.1 Overview12	2
	7.2 Functional Block Diagrams12	2
	7.3 Feature Description13	

7.4 Device Functional Modes	16
8 Application and Implementation	18
8.1 Application Information	. 18
8.2 Typical Application	. 18
9 Power Supply Recommendations	.23
10 Layout	24
10.1 Layout Guidelines	24
10.2 Layout Example	24
11 Device and Documentation Support	26
11.1 Device Support	26
11.2 Documentation Support	. 26
11.3 Receiving Notification of Documentation Updates	26
11.4 Support Resources	. 26
11.5 Trademarks	26
11.6 Glossary	26
11.7 Electrostatic Discharge Caution	26
12 Mechanical, Packaging, and Orderable	
Information	26

4 Revision History

注:以前版本的页码可能与当前版本的页码不同

Cł	nanges from Revision H (May 2019) to Revision I (April 2020)	Page
•	更新了整个文档的表、图和交叉参考的编号格式。	1
•	添加了链接至	1
Cł	nanges from Revision G (February 2017) to Revision H (May 2019)	Page
•	Added # 7.3.6	14
•	Added #7.3.7	14
•	Added	15
Cł	nanges from Revision F (October 2015) to Revision G (February 2017)	Page
•	Adjusted Operating temperature specification to "ambient temperature range, T _A " in # 6.3	5
Cł	nanges from Revision E (December 2000) to Revision F (Octobert 2015)	Page
•	添加了 图 3-1	1
•	Renamed pin " 0V " to " COM " (output side common pin) in <i>[†]</i> Pin Functions	4
•	Renamed pin "V _S " to "+V _S " (input voltage pin) in <i># Pin Functions</i>	4
•	Renamed pin " 0V " to " - V _S " (input side common pin) in <i>[#] Pin Functions</i>	4
•	Added # 6.3	5
•	Added # 6.4	5
•	Added information to the ISOLATION section of $\#$ 6.5	6
•	Added # 7.3.1 to # 7.3	

2 Submit Document Feedback



Device Comparison Table

at $T_A = 25^{\circ}C$, +V _S = nominal, $C_{IN} = 2.2 \ \mu\text{F}$, $C_{OUT} = 0.1 \ \mu\text{F}$, (unless otherwise noted)
--	----------------------------

DEVICE NUMBER	INPUT VOLTAGE V _S (V)		OUTPUT VOLTAGE V _{NOM} AT V _S (TYP) (V) 75% LOAD		DEVICE LOAD I OUTPUT REGULATION C CURRENT 10% TO 100% LOAD (1)		NO LOAD CURRENT I _Q (mA) 0% LOAD	EFFICIENCY (%) 100% LOAD	BARRIER CAPACITANCE C _{ISO} (pF) V _{ISO} = 750Vrms						
	MIN	TYP	MAX	MIN	TYP	MAX	MAX	TYP	MAX	TYP	TYP	TYP			
DCP010505BP DCP010505BP-U				4.75	5	5.25	200	19	31	20	80	3.6			
DCP010505DBP DCP010505DBP-U				±4.25	±5	±5.75	200 ⁽²⁾	18	32	22	81	3.8			
DCP010507DBP DCP010507DBP-U							±5.75	±6.5	±7.25	153 ⁽²⁾	21	35	38	81	3.0
DCP010512BP DCP010512BP-U	4.5	5	5.5	11.4	12	12.6	83	21	38	29	85	5.1			
DCP010512DBP DCP010512DBP-U				±11.4	±12	±12.6	83 ⁽²⁾	19	37	40	82	4.0			
DCP010515BP DCP010515BP-U				14.25	15	15.75	66	26	42	34	82	3.8			
DCP010515DBP DCP010515DBP-U				±14.25	±15	±15.75	66 ⁽²⁾	19	41	42	85	4.7			
DCP011512DBP DCP011512DBP-U	13.5	15	16.5	±11.4	±12	±12.6	83	11	39	19	78	2.5			
DCP011515DBP DCP011515DBP-U	13.5	15	10	.5 15	3.0 15	10.5	±14.25	±15	±15.75	66 ⁽²⁾	12	39	20	80	2.5
DCP012405BP DCP012405BP-U	21.6	24	26.4	4.75	5	5.25	200	13	23	14	77	2.5			
DCP012415DBP DCP012415DBP-U	21.0	27	20.4	±14.25	±15	±15.75	66 ⁽²⁾	10	35	17	76	3.8			

(1) Load regulation = (V_{OUT} at 10% load - V_{OUT} at 100%)/V_{OUT} at 75% load

(2) $I_{OUT1} + I_{OUT2}$

(3) P_{OUT(max)} = 1 W

 $Copyright @ 2021 \ Texas \ Instruments \ Incorporated \\$



5 Pin Configuration and Functions



图 5-1. 7-Pin PDIP and SOP (Single Output) NVA and DUA Package (Top View)





Pin Functions

	PIN NUMBER				
PIN NAME	SINGLE- OUTPUT	DUAL- OUTPUT	I/O ⁽¹⁾	DESCRIPTION	
СОМ	—	5	0	Output side common	
NC	7	—	—	No connection	
SYNCIN	14	14	I	Synchronization. Synchronize multiple devices by connecting the SYNC pins of each. Pulling this pin low disables the internal oscillator.	
SYNCOUT	8	8	0	Synchronization output. Unrectified transformer output	
+V _{OUT}	6	6	0	Positive output voltage	
+V _S	1	1	I	Input voltage	
- V _{OUT}	5	7	0	Negative output voltage	
- V _S	2	2	I	Input side common	

(1) I = Input, O = Output

4 Submit Document Feedback

6 Specifications

6.1 Absolute Maximum Ratings

over operating free-air temperature range (unless otherwise noted) (1)

		MIN	MAX	UNIT
Input voltage	5-V input devices		7	
	15-V input devices	18		V
	24-V input devices		29	
Lead temperature (solde	ring, 10 s)		270	°C
Storage temperature, T _{stg}			125	°C

(1) Stresses beyond those listed under Absolute Maximum Ratings may cause permanent damage to the device. These are stress ratings only, which do not imply functional operation of the device at these or any other conditions beyond those indicated under Recommended Operating Conditions. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

6.2 ESD Ratings

			VALUE	UNIT
V _(ESD)	Electrostatic discharge	Human-body model (HBM), per ANSI/ESDA/JEDEC JS-001 ⁽¹⁾	±1000	V
	Electrostatic discharge	Charged-device model (CDM), per JEDEC specification JESD22-C101 ⁽²⁾	±250	V

(1) JEDEC document JEP155 states that 500-V HBM allows safe manufacturing with a standard ESD control process.

(2) JEDEC document JEP157 states that 250-V CDM allows safe manufacturing with a standard ESD control process.

6.3 Recommended Operating Conditions

over operating free-air temperature range (unless otherwise noted)

		MIN	NOM	MAX	UNIT
Input voltage	5-V input devices	4.5	5	5.5	
	15-V input devices	13.5	15	16.5	V
	24-V input devices	21.6	24	26.4	
Operating ambient temperature range, T _A		- 40		100	°C

6.4 Thermal Information

		DCP01B	DCP01B	UNIT
	THERMAL METRIC ⁽¹⁾	NVA (PDIP)	DUA (SOP)	
		7 PINS	7 PINS	
R _{0 JA}	Junction-to-ambient thermal resistance	61	61	°C/W
R ₀ JC(top)	Junction-to-case (top) thermal resistance	26	26	°C/W
R _{0 JB}	Junction-to-board thermal resistance	24	24	°C/W
ΨJT	Junction-to-top characterization parameter	7	7	°C/W
ψ _{JB}	Junction-to-board characterization parameter	24	24	°C/W
R ₀ JC(bot)	Junction-to-case (bottom) thermal resistance	N/A	N/A	°C/W

(1) For more information about traditional and new thermal metrics, see the *Semiconductor and IC Package Thermal Metrics* application report, SPRA953.

Copyright © 2021 Texas Instruments Incorporated



6.5 Electrical Characteristics

	PARAMETER	TEST CO	NDITIONS	MIN	TYP	MAX	UNIT
OUTPUT							
P _{OUT}	Output power	I _{LOAD} = 100% (full	load)			1	W
V _{RIPPLE}	Output voltage ripple	C _{OUT} = 1 μ F, I _{LOA}	_{.D} = 50%		20		mV _{PP}
		$-40^{\circ}C \leqslant T_A \leqslant 2$	5°C		0.046		%/°C
	voltage vs. Temperature	$25^{\circ}C \leqslant T_A \leqslant 100$	°C		0.016		%/°C
INPUT			I				
Vs	Input voltage range			- 10%		10%	
ISOLATIO	N						
			Voltage	1			kVrms
		1-second flash test	dV/dt			500	V/s
V _{ISO} Isolation	la alatian		Leakage current			30	μA
	Isolation	Continuous	DC			60	VDC
		working voltage across isolation barrier	AC			42.5	VAC
LINE REC	GULATION	·					
	Output valtage	$I_{OUT} \ge 10\%$ load constant, V _S (min) to V _S (type)	current and		1%	15%	
V _{OUT}	Output voitage	I _{OUT} ≥ 10% load o constant, V _S (typ) to V _S (ma	current and x)		1%	15%	
RELIABI	LITY						
	Demonstrated	T _A = 55°C			55		FITS
THERMA	L SHUTDOWN						
T _{SD}	Die temperature at shutdown				150		°C
I _{SD}	Shutdown current				3		mA

6.6 Switching Characteristics

at $T_A = +25^{\circ}C$, $+V_S =$ nominal, $C_{IN} = 2.2 \ \mu$ F, $C_{OUT} = 0.1 \ \mu$ F, (unless otherwise noted)

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f _{OSC}	Oscillator frequency	$f_{SW} = f_{OSC}/2$		800		kHz
V _{IL}	Low-level input voltage, SYNC		0		0.4	V
I _{SYNC}	Input current, SYNC	V _{SYNC} = 2 V		75		μA
t _{DISABLE}	Disable time			2		μs
C _{SYNC}	Capacitance loading on SYNC pin $^{(1)}$	External			3	pF

(1) The application report External Synchronization of the DCP01/02 Series of DC/DC Converters (SBAA035) describes this configuration.



6.7 Typical Characteristics

At $T_A = 25^{\circ}C$, V_{+VS} = nominal, (unless otherwise noted)



Submit Document Feedback 7

DCP010505B, DCP010512B, DCP010515B, DCP012405B, DCP010505DB, DCP010507DB DCP010512DB, DCP010515DB, DCP011512DB, DCP011515DB, DCP012415DB ZHCSJP7I - DECEMBER 2000 - REVISED SEPTEMBER 2020





8 Submit Document Feedback

Copyright © 2021 Texas Instruments Incorporated



DCP010505B, DCP010512B, DCP010515B, DCP012405B, DCP010505DB, DCP010507DB DCP010512DB, DCP010515DB, DCP011512DB, DCP011515DB, DCP012415DB

ZHCSJP7I - DECEMBER 2000 - REVISED SEPTEMBER 2020



Copyright © 2021 Texas Instruments Incorporated

Submit Document Feedback 9

DCP010505B, DCP010512B, DCP010515B, DCP012405B, DCP010505DB, DCP010507DB DCP010512DB, DCP010515DB, DCP011512DB, DCP011515DB, DCP012415DB ZHCSJP7I - DECEMBER 2000 - REVISED SEPTEMBER 2020





10 Submit Document Feedback

Copyright © 2021 Texas Instruments Incorporated





Copyright © 2021 Texas Instruments Incorporated

Submit Document Feedback 11



7 Detailed Description

7.1 Overview

The DCP01B offers up to 1 W of isolated, unregulated output power from a 5-V, 15-V, or 24-V input source with a typical efficiency of up to 85%. This efficiency is achieved through highly integrated packaging technology and the implementation of a custom power stage and control device. The DCP01B devices are specified for operational isolation only. The circuit design uses an advanced BiCMOS and DMOS process.

7.2 Functional Block Diagrams







图 7-2. Dual Output Device



7.3 Feature Description

7.3.1 Isolation

Underwriters Laboratories, UL[™] defines several classes of isolation that are used in modern power supplies.

Safety extra low voltage (SELV) is defined by UL (UL1950 E199929) as a secondary circuit which is so designated and protected that under normal and single fault conditions the voltage between any two accessible parts, or between an accessible part and the equipment earthing terminal for operational isolation does not exceed steady state 42.5 V peak or 60 V_{DC} for more than one second.

7.3.1.1 Operation or Functional Isolation

Operational or functional isolation is defined by the use of a high-potential (hipot) test only. Typically, this isolation is defined as the use of insulated wire in the construction of the transformer as the primary isolation barrier. The hipot one-second duration test (dielectric voltage, withstand test) is a production test used to verify that the isolation barrier is functioning. Products with operational isolation must never be used as an element in a safety-isolation system.

7.3.1.2 Basic or Enhanced Isolation

Basic or enhanced isolation is defined by specified creepage and clearance limits between the primary and secondary circuits of the power supply. Basic isolation is the use of an isolation barrier in addition to the insulated wire in the construction of the transformer. Input and output circuits must also be physically separated by specified distances.

7.3.1.3 Continuous Voltage

For a device that has no specific safety agency approvals (operational isolation), the continuous voltage that can be applied across the part in normal operation is less than 42.5 V_{RMS} , or 60 V_{DC} . Ensure that both input and output voltages maintain normal SELV limits. The isolation test voltage represents a measure of immunity to transient voltages.

WARNING

Do not use the device as an element of a safety isolation system that exceeds the SELV limit.

If the device is expected to function correctly with more than 42.5 V_{RMS} or 60 V_{DC} applied continuously across the isolation barrier, then the circuitry on both sides of the barrier must be regarded as operating at an unsafe voltage, and further isolation or insulation systems must form a barrier between these circuits and any user-accessible circuitry according to safety standard requirements.

7.3.1.4 Isolation Voltage

The terms *Hipot test, flash-tested, withstand voltage, proof voltage, dielectric withstand voltage,* and *isolation test voltage* all describe a similar idea. They describe a test voltage applied for a specified time across a component designed to provide electrical isolation to verify the integrity of that isolation. TI' s DCP01B series of DC/DC converters are all 100% production tested at 1.0 kV_{AC} for one second.

7.3.1.5 Repeated High-Voltage Isolation Testing

Repeated high-voltage isolation testing of a barrier component can degrade the isolation capability, depending on materials, construction, and environment. The DCP01B series of DC/DC converters have toroidal, enameled, wire isolation transformers with no additional insulation between the primary and secondary windings. While a device can be expected to withstand several times the stated test voltage, the isolation capability depends on the wire insulation. Any material, including this enamel (typically polyurethane), is susceptible to eventual chemical degradation when subject to very-high applied voltages. Therefore, strictly limit the number of high-voltage tests and repeated high-voltage isolation testing. However, if it is absolutely required, reduce the voltage by 20% from specified test voltage with a duration limit of one second per test.

Copyright © 2021 Texas Instruments Incorporated



7.3.2 Power Stage

The DCP01B series of devices uses a push-pull, center-tapped topology. The DCP01B devices switch at 400 kHz (divide-by-2 from an 800-kHz oscillator).

7.3.3 Oscillator And Watchdog Circuit

The onboard, 800-kHz oscillator generates the switching frequency by a divide-by-2 circuit. The oscillator can be synchronized to other DCP01B series device circuits or an external source, and is used to minimize system noise.

A watchdog circuit checks the operation of the oscillator circuit. The oscillator can be disabled by pulling the $SYNC_{IN}$ pin low. When the $SYNC_{IN}$ pin goes low, the output pins transition into tri-state mode, which occurs within 2 μ s.

7.3.4 Thermal Shutdown

The DCP01B series of devices are protected by a thermal-shutdown circuit.

If the on-chip temperature rises above 150°C, the device shuts down. Normal operation resumes as soon as the temperature falls below 150°C. While the over temperature condition continues, operation randomly cycles on and off. This cycling continues until the temperature is reduced.

7.3.5 Synchronization

When more than one DC/DC converter is needed onboard, beat frequencies and other electrical interference can be generated. This interference occurs because of the small variations in switching frequencies between the DC/DC converters.

The DCP01B series of devices overcomes this interference by allowing devices to synchronize to one another. Synchronize up to eight devices by connecting the SYNC pins of each device, taking care to minimize the capacitance of tracking. Stray capacitance (greater than 3 pF) reduces the switching frequency, or can sometimes stop the oscillator circuit. The maximum recommended voltage applied to the SYNC pin is 3.0 V.

For an application that uses more than eight synchronized devices, use an external device to drive the SYNC pins. The application report *External Synchronization of the DCP01/02 Series of DC/DC Converters* describes this configuration.

Note

During the start-up period, all synchronized devices draw maximum current from the input simultaneously. If the input voltage falls below approximately 4 V, the devices may not start up. A 2.2- μ F capacitor should be connected close to each device input pin.

7.3.6 Light Load Operation (< 10%)

Operation below 10% load can cause the output voltage to increase up to double the typical output voltage. For applications that operate less than 10% of rated output current, it is recommended to add a minimum load to ensure the output voltage of the device is within the load regulation range. For example, connect a 250- Ω pre-load resistor to meet the 10% minimum load condition for the DCP010505BP.

7.3.7 Load Regulation (10% to 100%)

The load regulation of the DCP01B series of devices is specified at 10% to 100% load. Placing a minimum 10% load will ensure the output voltage is within the range specified in # 6.5. For more information regarding operation below 10% load, see # 7.3.6.

7.3.8 Construction

The basic construction of the DCP01B series of devices is the same as standard integrated circuits. The molded package contains no substrate. The DCP01B series of devices are constructed using an IC, rectifier diodes, and a wound magnetic toroid on a lead frame. Because the package contains no solder, the devices do not require



any special printed circuit board (PCB) assembly processing. This architecture results in an isolated DC/DC converter with inherently high reliability.

7.3.9 Thermal Management

Due to the high power density of these devices, it is advisable to provide ground planes on the input and output rails.

7.3.10 Power-Up Characteristics

The DCP01B series of devices do not include a soft-start feature. Therefore, a high in-rush current during power up is expected. Refer to the DCPA1 series of devices for a 1-W, isolated, unregulated DC/DC converter module with soft start included. 8 7-3 shows the typical start-up waveform for a DCP010505BP, operating from a 5-V input with no load on the output. 8 7-4 shows the start-up waveform for a DCP010505BP starting up into a 10% load. 8 7-5 shows the start-up waveform starting up into a full (100%) load.





7.4 Device Functional Modes

7.4.1 Disable and Enable (SYNC_{IN} Pin)

Each of the DCP01B series devices can be disabled or enabled by driving the SYNC_{IN} pin using an open-drain CMOS gate. If the SYNC_{IN} pin is pulled low, the DCP01B becomes disabled. The disable time depends upon the external loading. The internal disable function is implemented within 2 μ s. Removal of the pulldown causes the DCP01B to be enabled.

Capacitive loading on the SYNC_{IN} pin must be minimized (\leq 3 pF) to prevent a reduction in the oscillator frequency. The application report *External Synchronization of the DCP01/02 Series of DC/DC Converters* describes disable and enable control circuitry.

7.4.2 Decoupling

7.4.2.1 Ripple Reduction

The high switching frequency of 400 kHz allows simple filtering. To reduce ripple, it is recommended that a minimum of 1- μ F capacitor be used on the +V_{OUT} pin. For dual output devices, decouple both of the outputs to the COM pin. The required 2.2- μ F, low ESR ceramic input capacitor also helps reduce ripple and noise, (24-V input voltage versions require only 0.47 μ F of input capacitance). See application report *DC-to-DC Converter Noise Reduction*.

7.4.2.2 Connecting the DCP01B in Series

Multiple DCP01B isolated 1-W DC/DC converters can be connected in series to provide non-standard voltage rails. This configuration is possible by using the floating outputs provided by the galvanic isolation of the DCP01.

Connect the +V_{OUT} from one DCP01B to the $-V_{OUT}$ of another (see $\[B]$ 7-6). If the SYNC_{IN} pins are tied together, the self-synchronization feature of the DCP01B prevents beat frequencies on the voltage rails. The synchronization feature of the DCP01B allows easy series connection without external filtering, thus minimizing cost.



图 7-6. Multiple DCP01B Devices Connected in Series

The outputs of a dual-output DCP01B can also be connected in series to provide two times the magnitude of $+V_{OUT}$, as shown in \mathbb{Z} 7-7. For example, connect a dual-output, 15-V, DCP012415DB device to provide a 30-V rail.







7.4.2.3 Connecting the DCP01B in Parallel

If the output power from one DCP01B is not sufficient, it is possible to parallel the outputs of multiple DCP01Bs, as shown in 8 7-8 (applies to single output devices only). The synchronization feature allows easy synchronization to prevent power-rail beat frequencies at no additional filtering cost.



图 7-8. Multiple DCP01B Devices Connected in Parallel



8 Application and Implementation

Note

Information in the following applications sections is not part of the TI component specification, and TI does not warrant its accuracy or completeness. TI's customers are responsible for determining suitability of components for their purposes. Customers should validate and test their design implementation to confirm system functionality.

8.1 Application Information

8.2 Typical Application



图 8-1. Typical DCP010505 Application

8.2.1 Design Requirements

For this design example, use the parameters listed in $\frac{1}{8}$ 8-1 and follow the design procedures shown in the $\frac{1}{8}$ 8.2.2.

	PARAMETER	VALUE	UNIT
V _(+VS)	Input voltage	5	V
V _(+VOUT)	Output voltage	5	V
I _{OUT}	Output current rating	200	mA
f _{SW}	Operating frequency	400	kHz

表 8-1. Design Example Parameters

8.2.2 Detailed Design Procedure

8.2.2.1 Input Capacitor

For all 5-V and 15-V input voltage designs, select a 2.2- μ F low-ESR ceramic input capacitor to ensure a good startup performance. 24-V input applications require only 0.47- μ F of input capacitance.

8.2.2.2 Output Capacitor

For any DCP01B design, select a 1.0- µ F low-ESR ceramic output capacitor to reduce output ripple.

8.2.2.3 SYNC_{IN} Pin

In a stand-alone application, leave the $SYNC_{IN}$ pin floating.

18 Submit Document Feedback

8.2.3 DCP010505 Application Curves



8.2.4 PCB Design

The copper losses (resistance and inductance) can be minimized by the use of mutual ground and power planes (tracks) where possible. If that is not possible, use wide tracks to reduce the losses. If several devices are being powered from a common power source, a star-connected system for the track must be deployed. Do not connect the devices in series, because that type of connection cascades the resistive losses. The position of the decoupling capacitors is important. They must be as close to the devices as possible in order to reduce losses. See # 10 for more details.

8.2.5 Decoupling Ceramic Capacitors

All capacitors have losses because of internal equivalent series resistance (ESR), and to a lesser degree, equivalent series inductance (ESL). Values for ESL are not always easy to obtain. However, some manufacturers provide graphs of frequency versus capacitor impedance. These graphs typically show the capacitor impedance falling as frequency is increased (as shown in \mathbb{R} 8-4). In \mathbb{R} 8-4, X_C is the reactance due to the capacitance, X _L is the reactance due to the ESL, and f₀ is the resonant frequency. As the frequency increases, the impedance stops decreasing and begins to rise. The point of minimum impedance indicates the resonant frequency of the capacitor. This frequency is where the components of capacitance and inductance reactance are of equal magnitude. Beyond this point, the capacitor is not effective as a capacitor.





Copyright © 2021 Texas Instruments Incorporated



However, there is a 180° phase difference resulting in cancellation of the imaginary component. The resulting effect is that the impedance at the resonant point is the real part of the complex impedance, namely, the value of the ESR. The output capacitor's resonant frequency must be higher than the default switching frequency (800 kHz) of the device to properly decouple noise at and below the switching frequency.



The effect of the ESR is to cause a voltage drop within the capacitor. The value of this voltage drop is simply the product of the ESR and the transient load current, as shown in \overline{j} 程式 1.

$$V_{IN} = V_{PK} - (ESR \times I_{TR})$$

(1)

where

- V_{IN} is the voltage at the device input
- V_{PK} is the maximum value of the voltage on the capacitor during charge
- I_{TR} is the transient load current

The other factor that affects the performance is the value of the capacitance. However, for the input and the full wave outputs (single-output voltage devices), ESR is the dominant factor.

8.2.6 Input Capacitor and the Effects of ESR

If the input decoupling capacitor is not ceramic (and has an ESR greater than 20 m Ω), then at the instant the power transistors switch on, the voltage at the input pins falls momentarily. If the voltage falls below approximately 4 V, the device detects an undervoltage condition and switches the internal drive circuits to a momentary off state. This detection is carried out as a precaution against a genuine low input voltage condition that could slow down or even stop the internal circuits from operating correctly. A slow-down or stoppage results in the drive transistors being turned on too long, causing saturation of the transformer and destruction of the device.

Following detection of a low input voltage condition, the device switches off the internal drive circuits until the input voltage returns to a safe value, at which time the device tries to restart. If the input capacitor is still unable to maintain the input voltage, shutdown recurs. This process repeats until the input capacitor charges sufficiently to start the device correctly.

Normal start-up should occur in approximately 1 ms after power is applied to the device. If a considerably longer start-up duration time is encountered, it is likely that either (or both) the input supply or the capacitors are not performing adequately.

For 5-V to 15-V input devices, a 2.2- μ F, low-ESR ceramic capacitor ensures good startup performance. For 24-V input voltage devices, 0.47- μ F ceramic capacitors are recommended. Tantalum capacitors are not recommended, since most do not have low-ESR values and will degrade performance. If tantalum capacitors must be used, close attention must be paid to both the ESR and voltage as derated by the vendor.

Note

During the start-up period, these devices may draw maximum current from the input supply. If the input voltage falls below approximately 4 V, the devices may not start up. Connect a 2.2- μ F ceramic capacitor close to the input pins.

8.2.7 Ripple and Noise

A good quality, low-ESR ceramic capacitor placed as close as practical across the input reduces reflected ripple and ensures a smooth start-up.

A good quality, low-ESR ceramic capacitor placed as close as practical across the rectifier output terminal and output ground gives the best ripple and noise performance. See application report *DC-to-DC Converter Noise Reduction* for more information on noise rejection.

8.2.7.1 Output Ripple Calculation Example

The following example shows that increasing the capacitance has a much smaller effect on the output ripple voltage than does reducing the value of the ESR for the filter capacitor.

To calculate the output ripple for a DCP010505 device:

• V_{OUT} = 5 V

Copyright © 2021 Texas Instruments Incorporated



- I_{OUT} = 0.2 A
- At full output power, the load resistor is 25 Ω
- Ceramic output capacitor of 1 $\,\mu$ F, ESR of 0.1 Ω
- Capacitor discharge time 1% of 800 kHz (ripple frequency)

t_{DIS} = 0.0125 μs

$$\tau = \mathbf{C} \times \mathbf{R}_{\mathsf{LOAD}}$$

 $\tau = 1 \times 10^{-6} \times 12.5 = 12.5 \ \mu s$

 $V_{\text{DIS}} = V_{O}(1 - \text{EXP}(-t_{\text{DIS}} / \tau))$

 $V_{DIS} = 5 \text{ mV}$

By contrast, the voltage dropped because of ESR:

 $V_{ESR} = I_{LOAD} \times ESR$

 $V_{ESR} = 20 \text{ mV}$

Ripple voltage = 25 mV

8.2.8 Dual DCP01B Output Voltage

The voltage output for dual DCP01B devices is half wave rectified; therefore, the discharge time is 1.25 μ s. Repeating the above calculations using the 100% load resistance of 50 Ω (0.1 A per output), the results are:

τ = 25 μs

 $t_{DIS} = 1.25 \ \mu \, s$

V_{DIS} = 244 mV

 V_{ESR} = 10 mV

Ripple Voltage = 133 mV

This time, it is the capacitor discharging that contributes to the largest component of ripple. Changing the output filter to 10 μ F, and repeating the calculations, the result is:

Ripple voltage = 25 mV

This value is composed of almost equal components.

The previous calculations are offered as a guideline only. Capacitor parameters usually have large tolerances and can be susceptible to environmental conditions.

8.2.9 Optimizing Performance

Optimum performance can only be achieved if the device is correctly supported. The very nature of a switching converter requires power to be instantly available when it switches on. If the converter has DMOS switching transistors, the fast edges will create a high current demand on the input supply. This transient load placed on the input is supplied by the external input decoupling capacitor, thus maintaining the input voltage. Therefore, the input supply does not see this transient (this is an analogy to high-speed digital circuits). The positioning of the capacitor is critical and must be placed as close as possible to the input pins and connected via a low-impedance path.

The optimum performance primarily depends on two factors:

- Connection of the input and output circuits for minimal loss.
- The ability of the decoupling capacitors to maintain the input and output voltages at a constant level.



9 Power Supply Recommendations

The DCP01B is a switching power supply, and as such can place high peak current demands on the input supply. To avoid the supply falling momentarily during the fast switching pulses, ground and power planes must be used to connect the power to the input of DCP01 device. If this connection is not possible, then the supplies must be connected in a star formation with the traces made as wide as possible.

Copyright © 2021 Texas Instruments Incorporated



10 Layout

10.1 Layout Guidelines

Due to the high power density of these devices, provide ground planes on the input and output rails.

图 10-1 and 图 10-2 show the schematic for the two DIP through-hole packages, and two SOP surface-mount packages for the DCP family of products which include DCP01B, DCP02, DCV01, DCR01, and DCR02. 🛽 10-3 and 8 10-4 illustrate a printed circuit board (PCB) layout for the schematics.

Including input power and ground planes provides a low-impedance path for the input power. For the output, the COM signal connects via a ground plane, while the connections for the positive and negative voltage outputs conduct via wide traces in order to minimize losses.

The output should be taken from the device using ground and power planes, thereby ensuring minimum losses.

The location of the decoupling capacitors in close proximity to their respective pins ensures low losses due to the effects of stray inductance, thus improving the ripple performance. This location is of particular importance to the input decoupling capacitor, because this capacitor supplies the transient current associated with the fast switching waveforms of the power drive circuits.

Allow the unused SYNC pin, to remain configured as a floating pad. It is advisable to place a guard ring (connected to input ground) or annulus connected around this pin to avoid any noise pick up. When connecting a SYNC pin to one or more SYNC design the linking trace to be short and narrow to avoid stray capacitance. Ensure that no other trace is in close proximity to this trace SYNC trace to decrease the stray capacitance on this pin. The stray capacitance affects the performance of the oscillator.

CON1 CON3 SYNC +V_S SYNC 28 OO JP1 VS1 O -0 0 JP1 VS3 O 14 1 +Vs C1 C11 NC 27 NC 26 0V1 C 2 0V3 O 2 $-V_S$ -Vs DCP02xxxxP 3 -Vs +V_{OUT} +V1 C 6 +V3 C 13 +Vout C3 C2-1 C2 C12 C13 <r> $>_{R5}$ DCP02xxxxU COM 5 12 COM C4 COM1 C5 C4-1 COM3 C14 C15 R₂ \leq R6 – V1 C -Vout – V3 C 14 -Vout CON2 CON4 SYNC 14 SYNC 28 OQ 1b5 VS2 C +Vs ဝင်္ဝ ၂၉2 VS4 1 +Vs C6 C16 NC 27 NC 26 0V2 C 2 -Vs 0V4 C 2 -Vs 3 DCP02xxxxP -Vs +V2 C 6 +V_{OUT} +V4 C 13 +Vout C8 C7-1 C7 C17 _C18 ≤r3 ≤r7 DCP02xxxxU COM 5 12 COM COM2 C9 C10 C9-1 COM4 C19 C20 R4 R8 - V2 C 7 -Vout – V4 C -V_{OUT} 14 图 10-2. PCB Schematic, U Package

10.2 Layout Example



Copyright © 2021 Texas Instruments Incorporated





图 10-3. PCB Layout Example, Component-Side View



图 10-4. PCB Layout Example, Non-Component-Side View

Copyright © 2021 Texas Instruments Incorporated



11 Device and Documentation Support

11.1 Device Support

11.1.1 Device Nomenclature

	DCP01	05	05	(D)	в	(P)
Basic model number: 1-W product Voltage input:	J					
5, 15, or 24 Voltage output:						
5, 7, 12 or 15 Output type:						
Series					J	
Package code: P = 7-pin PDIP (NVA package)						
P - U = i - pin SOP (DUA package)						

图 11-1. Supplemental Ordering Information

11.2 Documentation Support

11.2.1 Related Documentation

- DC-to-DC Converter Noise Reduction
- External Synchronization of the DCP01/02 Series of DC/DC Converters
- Optimizing Performance of the DCP01/02 Series of DC/DC Converters

11.3 Receiving Notification of Documentation Updates

To receive notification of documentation updates, navigate to the device product folder on ti.com. Click on *Subscribe to updates* to register and receive a weekly digest of any product information that has changed. For change details, review the revision history included in any revised document.

11.4 Support Resources

TI E2E^m support forums are an engineer's go-to source for fast, verified answers and design help — straight from the experts. Search existing answers or ask your own question to get the quick design help you need.

Linked content is provided "AS IS" by the respective contributors. They do not constitute TI specifications and do not necessarily reflect TI's views; see TI's Terms of Use.

11.5 Trademarks

Underwriters Laboratories, UL[™] is a trademark of UL LLC. TI E2E[™] is a trademark of Texas Instruments. 所有商标均为其各自所有者的财产。

11.6 Glossary

TI Glossary This glossary lists and explains terms, acronyms, and definitions.

11.7 Electrostatic Discharge Caution



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

12 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

26 Submit Document Feedback

Copyright © 2021 Texas Instruments Incorporated



PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
DCP010505BP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010505BP	Samples
DCP010505BP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505BP-U	Samples
DCP010505BP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505BP-U	Samples
DCP010505BP-U/7E4	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505BP-U	Samples
DCP010505BP-UE4	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505BP-U	Samples
DCP010505DBP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010505DBP	Samples
DCP010505DBP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505DBP-U	Samples
DCP010505DBP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505DBP-U	Samples
DCP010505DBP-U/7E4	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010505DBP-U	Samples
DCP010507DBP-U/7E4	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010507DBP-U	Samples
DCP010507DBP-UE4	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010507DBP-U	Samples
DCP010507DBPE4	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010507DBP	Samples
DCP010512BP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010512BP	Samples
DCP010512BP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010512BP-U	Samples
DCP010512BP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010512BP-U	Samples
DCP010512DBP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010512DBP	Samples



www.ti.com

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
DCP010512DBP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010512DBP-U	Samples
DCP010512DBP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010512DBP-U	Samples
DCP010512DBPE4	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010512DBP	Samples
DCP010515BP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010515BP	Samples
DCP010515BP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010515BP-U	Samples
DCP010515BP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010515BP-U	Samples
DCP010515DBP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP010515DBP	Samples
DCP010515DBP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010515DBP-U	Samples
DCP010515DBP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP010515DBP-U	Samples
DCP011512DBP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP011512DBP	Samples
DCP011512DBP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP011512DBP-U	Samples
DCP011515DBP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP011515DBP	Samples
DCP011515DBP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP011515DBP-U	Samples
DCP011515DBP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP011515DBP-U	Samples
DCP012405BP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP012405BP	Samples
DCP012405BP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP012405BP-U	Samples
DCP012415DBP	ACTIVE	PDIP	NVA	7	25	RoHS & Non-Green	NIPDAU	N / A for Pkg Type	-40 to 100	DCP012415DBP	Samples



Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
DCP012415DBP-U	ACTIVE	SOP	DUA	7	25	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP012415DBP-U	Samples
DCP012415DBP-U/700	ACTIVE	SOP	DUA	7	700	RoHS & Non-Green	NIPDAU	Level-3-260C-168 HR	-40 to 100	DCP012415DBP-U	Samples

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ RoHS: TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

Green: TI defines "Green" to mean the content of Chlorine (CI) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

⁽³⁾ MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

⁽⁴⁾ There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

MECHANICAL DATA



- G. Pointed or rounded lead tips are preferred to ease insertion.
- L. Falls within JEDEC MS-001-AA.



MECHANICAL DATA



- to be 0.005 (0,13) minimum.
- TEXAS INSTRUMENTS

www.ti.com

重要声明和免责声明

TI 提供技术和可靠性数据(包括数据表)、设计资源(包括参考设计)、应用或其他设计建议、网络工具、安全信息和其他资源,不保证没 有瑕疵且不做出任何明示或暗示的担保,包括但不限于对适销性、某特定用途方面的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任:(1) 针对您的应用选择合适的 TI 产品,(2) 设计、验证并测试您的应用,(3) 确保您的应用满足相应标准以及任何其他安全、安保或其他要求。这些资源如有变更,恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的应用。严禁对这些资源进行其他复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。您应全额赔偿因在这些资源的使用中对 TI 及其代表造成的任何索赔、损害、成本、损失和债务,TI 对此概不负责。

TI 提供的产品受 TI 的销售条款 (https:www.ti.com.cn/zh-cn/legal/termsofsale.html) 或 ti.com.cn 上其他适用条款/TI 产品随附的其他适用条款 的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。

> 邮寄地址:上海市浦东新区世纪大道 1568 号中建大厦 32 楼,邮政编码:200122 Copyright © 2021 德州仪器半导体技术(上海)有限公司