



# AiP74LVC245

## Octal Bus Transceiver; 3-state

### Product Specification

**Specification Revision History:**

Version	Date	Description
2017-10-A1	2017-10	New
2021-12-A2	2021-12	Modify Ordering Information
2022-02-A3	2022-02	Modify ambient temperature to -40°C~+105°C and add electrical characteristics of -40°C~+105°C
2022-10-A4	2022-10	Modify Reel packing specifications



## General Description

The AiP74LVC245 is a 8-bit transceivers featuring non-inverting 3-state bus compatible outputs in both send and receive directions. The device features an output enable( $\overline{OE}$ ) input for easy cascading and a send/receive (DIR) input for direction control.  $\overline{OE}$  controls the outputs so that the buses are effectively isolated.

Inputs can be driven from either 3.3V or 5V devices. When disabled, up to 5.5V can be applied to the outputs. These features allow the use of these devices in mixed 3.3V and 5V applications.

### Features:

- 5V tolerant inputs/outputs for interfacing with 5V logic
- Wide supply voltage range from 1.2V to 3.6V
- CMOS low power consumption
- Direct interface with TTL levels
- Inputs accept voltages up to 5.5V
- High-impedance when  $V_{CC}=0V$
- Packaging information: SOP20/TSSOP20/DHVQFN20

**Ordering Information:****Tube packing specifications:**

Part number	Packaging form	Marking code	Tube quantity	Boxed tube quantity	Boxed quantity	Notes
AiP74LVC245SA20.TB	SOP20	74LVC245	35 PCS/tube	80 tube/box	2800 PCS/box	Dimensions of plastic enclosure: 12.8mm×7.5mm Pin spacing: 1.27mm
AiP74LVC245TA20.TB	TSSOP20	74LVC245	70 PCS/tube	200 tube/box	14000 PCS/box	Dimensions of plastic enclosure: 6.5mm×4.4mm Pin spacing: 0.65mm

**Reel packing specifications:**

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP74LVC245SA20.TR	SOP20	74LVC245	2000 PCS/reel	2000 PCS/box	Dimensions of plastic enclosure: 12.8mm×7.5mm Pin spacing:1.27mm
AiP74LVC245TA20.TR	TSSOP20	74LVC245	4000 PCS/reel	8000 PCS/box	Dimensions of plastic enclosure: 6.5mm×4.4mm Pin spacing:0.65mm
AiP74LVC245QE20.TR	DHVQFN20	74LVC245	3000 PCS/reel	3000 PCS/box	Dimensions of plastic enclosure: 4.5mm×2.5mm Pin spacing:0.5mm

Note: If the physical information is inconsistent with the ordering information, please refer to the actual product.



## 2、Block Diagram And Pin Description

### 2.1、Block Diagram




Figure 1. Logic diagram





Figure 2. IEC logic symbol



## 2.2、Pin Configurations



Note:(1) This is not a supply pin. The substrate is attached to this pad using conductive die attach material. There is no electrical or mechanical requirement to solder this pad. However, if it is soldered, the solder land should remain floating or be connected to GND.

## 2.3、Pin Description

Pin No.	Pin Name	Description
1	DIR	direction control
2	A0	data input/output
3	A1	data input/output
4	A2	data input/output
5	A3	data input/output
6	A4	data input/output
7	A5	data input/output
8	A6	data input/output
9	A7	data input/output
10	GND	ground (0 V)
11	B7	data input/output
12	B6	data input/output
13	B5	data input/output
14	B4	data input/output
15	B3	data input/output
16	B2	data input/output
17	B1	data input/output
18	B0	data input/output
19	$\overline{OE}$	output enable input (active LOW)
20	V <sub>CC</sub>	supply voltage



## 2.4、Function Table

Input		Inputs/outputs	
OE	DIR	An	Bn
L	L	An=Bn	inputs
L	H	inputs	Bn=An
H	X	Z	Z

Note: H=HIGH voltage level; L=LOW voltage level; X=don't care; Z=high-impedance OFF-state.

## 3、Electrical Parameter

### 3.1、Absolute Maximum Ratings

(Voltages are referenced to GND(ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Max.	Unit
supply voltage	$V_{CC}$	-	-0.5	6.5	V
input clamping current	$I_{IK}$	$V_I < 0V$	-50	-	mA
input voltage	$V_I$	-	-0.5	6.5	V
output clamping current	$I_{OK}$	$V_O > V_{CC}$ or $V_O < 0V$	-	$\pm 50$	mA
output voltage	$V_O$	output HIGH or LOW	-0.5	$V_{CC}+0.5$	V
		output 3-state	-0.5	6.5	V
output current	$I_O$	$V_O=0V$ to $V_{CC}$	-	$\pm 50$	mA
supply current	$I_{CC}$	-	-	100	mA
ground current	$I_{GND}$	-	-100	-	mA
storage temperature	$T_{stg}$	-	-65	150	°C
total power dissipation	$P_{tot}$	-	-	500	mW
Soldering Temperature	$T_L$	10s	250		°C

Note:

[1] The minimum input voltage ratings may be exceeded if the input current ratings are observed.

[2] The output voltage ratings may be exceeded if the output current ratings are observed.

[3] For SOP20 packages: above 70°C the value of  $P_{tot}$  derates linearly with 8mW/K.

For TSSOP20 packages: above 60°C the value of  $P_{tot}$  derates linearly with 5.5mW/K.

For DHVQFN20 packages: above 60°C the value of  $P_{tot}$  derates linearly with 4.5mW/K.



### 3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V <sub>CC</sub>	-	1.65	-	3.6	V
		functional	1.2	-	3.6	V
input voltage	V <sub>I</sub>	-	0	-	5.5	V
output voltage	V <sub>O</sub>	output HIGH or LOW	0	-	V <sub>CC</sub>	V
		output 3-state	0	-	5.5	V
ambient temperature	T <sub>amb</sub>	in free air	-40	-	+105	°C
input transition rise and fall rate	Δt/ΔV	V <sub>CC</sub> =1.2V to 2.7V	0	-	20	ns/V
		V <sub>CC</sub> =2.7V to 3.6V	0	-	10	ns/V

### 3.3、Electrical Characteristics

#### 3.3.1、DC Characteristics 1

(T<sub>amb</sub>=-40°C to +85°C, voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
HIGH-level input voltage	V <sub>IH</sub>	V <sub>CC</sub> =1.2V	1.08	-	-	V	
		V <sub>CC</sub> =1.65V to 1.95V	0.65×V <sub>CC</sub>	-	-	V	
		V <sub>CC</sub> =2.3V to 2.7V	1.7	-	-	V	
		V <sub>CC</sub> =2.7V to 3.6V	2.0	-	-	V	
LOW-level input voltage	V <sub>IL</sub>	V <sub>CC</sub> =1.2V	-	-	0.12	V	
		V <sub>CC</sub> =1.65V to 1.95V	-	-	0.35×V <sub>CC</sub>	V	
		V <sub>CC</sub> =2.3V to 2.7V	-	-	0.7	V	
		V <sub>CC</sub> =2.7V to 3.6V	-	-	0.8	V	
HIGH-level output voltage	V <sub>OH</sub>	V <sub>I</sub> =V <sub>IH</sub> or V <sub>IL</sub>	I <sub>O</sub> =-100uA; V <sub>CC</sub> =1.65V to 3.6V	V <sub>CC</sub> -0.2	-	-	V
			I <sub>O</sub> =-4mA; V <sub>CC</sub> =1.65V	1.2	-	-	V
			I <sub>O</sub> =-8mA; V <sub>CC</sub> =2.3V	1.8	-	-	V
			I <sub>O</sub> =-12mA; V <sub>CC</sub> =2.7V	2.2	-	-	V
			I <sub>O</sub> =-18mA; V <sub>CC</sub> =3.0V	2.4	-	-	V
			I <sub>O</sub> =-24mA; V <sub>CC</sub> =3.0V	2.2	-	-	V
LOW-level output voltage	V <sub>OL</sub>	V <sub>I</sub> =V <sub>IH</sub> or V <sub>IL</sub>	I <sub>O</sub> =100uA; V <sub>CC</sub> =1.65V to 3.6V	-	-	0.2	V
			I <sub>O</sub> =4mA; V <sub>CC</sub> =1.65V	-	-	0.45	V
			I <sub>O</sub> =8mA; V <sub>CC</sub> =2.3V	-	-	0.6	V
			I <sub>O</sub> =12mA; V <sub>CC</sub> =2.7V	-	-	0.4	V
			I <sub>O</sub> =24mA; V <sub>CC</sub> =3.0V	-	-	0.55	V
input leakage current	I <sub>I</sub>	V <sub>CC</sub> =3.6V; V <sub>I</sub> =5.5V or GND	-	±0.1	±5	uA	
OFF-state output current	I <sub>OZ</sub>	V <sub>CC</sub> =3.6V; V <sub>I</sub> =V <sub>IH</sub> or V <sub>IL</sub> ; V <sub>O</sub> =5.5V or GND	-	±0.1	±5	uA	



power-off leakage current	$I_{OFF}$	$V_{CC}=0V; V_I$ or $V_O=5.5V$	-	$\pm 0.1$	$\pm 10$	$\mu A$
supply current	$I_{CC}$	$V_{CC}=3.6V; V_I=V_{CC}$ or GND; $I_O=0A$	-	0.1	10	$\mu A$
additional supply current	$\Delta I_{CC}$	per input pin; $V_{CC}=2.7V$ to $3.6V$ ; $V_I=V_{CC}-0.6V; I_O=0A$	-	5	500	$\mu A$
input capacitance	$C_I$	$V_{CC}=0V$ to $3.6V; V_I=GND$ to $V_{CC}$	-	4	-	pF
input/output capacitance	$C_{I/O}$	$V_{CC}=0V$ to $3.6V; V_I=GND$ to $V_{CC}$	-	10	-	pF

Note:

 [1] All typical values are measured at  $V_{CC}=3.3V$  (unless stated otherwise) and  $T_{amb}=25^{\circ}C$ .

### 3.3.2、DC Characteristics 2

 ( $T_{amb}=-40^{\circ}C$  to  $+105^{\circ}C$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
HIGH-level input voltage	$V_{IH}$	$V_{CC}=1.2V$	1.08	-	-	V	
		$V_{CC}=1.65V$ to $1.95V$	$0.65 \times V_{CC}$	-	-	V	
		$V_{CC}=2.3V$ to $2.7V$	1.7	-	-	V	
		$V_{CC}=2.7V$ to $3.6V$	2.0	-	-	V	
LOW-level input voltage	$V_{IL}$	$V_{CC}=1.2V$	-	-	0.12	V	
		$V_{CC}=1.65V$ to $1.95V$	-	-	$0.35 \times V_{CC}$	V	
		$V_{CC}=2.3V$ to $2.7V$	-	-	0.7	V	
		$V_{CC}=2.7V$ to $3.6V$	-	-	0.8	V	
HIGH-level output voltage	$V_{OH}$	$V_I=V_{IH}$ or $V_{IL}$	$I_O=-100\mu A$ ; $V_{CC}=1.65V$ to $3.6V$	$V_{CC}-0.3$	-	-	V
			$I_O=-4mA$ ; $V_{CC}=1.65V$	1.05	-	-	V
			$I_O=-8mA$ ; $V_{CC}=2.3V$	1.65	-	-	V
			$I_O=-12mA$ ; $V_{CC}=2.7V$	2.05	-	-	V
			$I_O=-18mA$ ; $V_{CC}=3.0V$	2.25	-	-	V
			$I_O=-24mA$ ; $V_{CC}=3.0V$	2.0	-	-	V
LOW-level output voltage	$V_{OL}$	$V_I=V_{IH}$ or $V_{IL}$	$I_O=100\mu A$ ; $V_{CC}=1.65V$ to $3.6V$	-	-	0.3	V
			$I_O=4mA$ ; $V_{CC}=1.65V$	-	-	0.65	V
			$I_O=8mA$ ; $V_{CC}=2.3V$	-	-	0.8	V
			$I_O=12mA$ ; $V_{CC}=2.7V$	-	-	0.6	V
			$I_O=24mA$ ; $V_{CC}=3.0V$	-	-	0.8	V
input leakage current	$I_I$	$V_{CC}=3.6V; V_I=5.5V$ or GND	-	-	$\pm 20$	$\mu A$	
OFF-state output current	$I_{OZ}$	$V_{CC}=3.6V; V_I=V_{IH}$ or $V_{IL}$ ; $V_O=5.5V$ or GND	-	-	$\pm 20$	$\mu A$	
power-off	$I_{OFF}$	$V_{CC}=0V; V_I$ or $V_O=5.5V$	-	-	$\pm 20$	$\mu A$	





leakage current						
supply current	$I_{CC}$	$V_{CC}=3.6V$ ; $V_I=V_{CC}$ or GND; $I_O=0A$	-	-	40	$\mu A$
additional supply current	$\Delta I_{CC}$	per input pin; $V_{CC}=2.7V$ to $3.6V$ ; $V_I=V_{CC}-0.6V$ ; $I_O=0A$	-	-	5000	$\mu A$

Note:

[1] All typical values are measured at  $V_{CC}=3.3V$  (unless stated otherwise) and  $T_{amb}=25^\circ C$ .

### 3.3.3、AC Characteristics 1

( $T_{amb}=-40^\circ C$  to  $+85^\circ C$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
nAn to nBn nBn to nAn propagation delay	$t_{pd}$	see Figure 4	$V_{CC}=1.2V$	-	17.0	-	ns
			$V_{CC}=1.65V$ to $1.95V$	1.5	6.5	14.6	ns
			$V_{CC}=2.3V$ to $2.7V$	1.0	3.4	7.6	ns
			$V_{CC}=2.7V$	1.5	3.4	7.3	ns
			$V_{CC}=3.0V$ to $3.6V$	1.5	2.9	6.3	ns
nOE to nAn/nBn enable time	$t_{en}$	see Figure 5	$V_{CC}=1.2V$	-	22.0	-	ns
			$V_{CC}=1.65V$ to $1.95V$	1.9	8.3	19.5	ns
			$V_{CC}=2.3V$ to $2.7V$	1.5	4.6	10.7	ns
			$V_{CC}=2.7V$	1.5	4.8	9.5	ns
			$V_{CC}=3.0V$ to $3.6V$	1.5	3.7	8.5	ns
nOE to nAn/nBn disable time	$t_{dis}$	see Figure 5	$V_{CC}=1.2V$	-	12.0	-	ns
			$V_{CC}=1.65V$ to $1.95V$	2.9	5.5	12.3	ns
			$V_{CC}=2.3V$ to $2.7V$	1.0	3.1	7.1	ns
			$V_{CC}=2.7V$	1.5	3.9	8.0	ns
			$V_{CC}=3.0V$ to $3.6V$	1.7	3.6	7.0	ns
output skew time	$t_{sk(o)}$	-	-	-	1.0	ns	
power dissipation capacitance	$C_{PD}$	per input; $V_I=GND$ to $V_{CC}$	$V_{CC}=1.65V$ to $1.95V$	-	7.7	-	pF
			$V_{CC}=2.3V$ to $2.7V$	-	11.3	-	
			$V_{CC}=3.0V$ to $3.6V$	-	14.4	-	

Note:

[1] Typical values are measured at  $T_{amb}=25^\circ C$  and  $V_{CC}=1.8V, 2.5V, 2.7V$ , and  $3.3V$  respectively.

[2]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ .

$t_{en}$  is the same as  $t_{PZH}$  and  $t_{PZL}$ .

$t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ .

[3] Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.

[4]  $C_{PD}$  is used to determine the dynamic power dissipation ( $P_D$  in  $\mu W$ ).

$$P_D=(C_{PD} \times V_{CC}^2 \times f_i \times N) + \sum(C_L \times V_{CC}^2 \times f_o) \text{ where:}$$

$f_i$ =input frequency in MHz.

$f_o$ =output frequency in MHz.

$C_L$ =output load capacitance in pF.

$V_{CC}$ =supply voltage in  $V_{olt}$ .

$N$ =number of inputs switching.

$\sum(C_L \times V_{CC}^2 \times f_o)$ =sum of the outputs.



### 3.3.4、 AC Characteristics 2

( $T_{amb}=-40^{\circ}\text{C}$  to  $+105^{\circ}\text{C}$ , voltages are referenced to GND (ground=0V), unless otherwise specified.)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
nAn to nBn nBn to nAn propagation delay	$t_{pd}$	see Figure 4	$V_{CC}=1.65\text{V to }1.95\text{V}$	1.5	-	16.9	ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.0	-	8.7	ns
			$V_{CC}=2.7\text{V}$	1.5	-	9.5	ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.5	-	8.0	ns
$\overline{\text{nOE}}$ to nAn/nBn enable time	$t_{en}$	see Figure 5	$V_{CC}=1.65\text{V to }1.95\text{V}$	1.9	-	22.5	ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.5	-	12.4	ns
			$V_{CC}=2.7\text{V}$	1.5	-	12.0	ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.5	-	11.0	ns
$\overline{\text{nOE}}$ to nAn/nBn disable time	$t_{dis}$	see Figure 5	$V_{CC}=1.65\text{V to }1.95\text{V}$	2.9	-	14.2	ns
			$V_{CC}=2.3\text{V to }2.7\text{V}$	1.0	-	8.2	ns
			$V_{CC}=2.7\text{V}$	1.5	-	10.0	ns
			$V_{CC}=3.0\text{V to }3.6\text{V}$	1.7	-	9.0	ns
output skew time	$t_{sk(o)}$	-	-	-	1.5	ns	

Note:

[1] Typical values are measured at  $T_{amb}=25^{\circ}\text{C}$  and  $V_{CC}=1.8\text{V}, 2.5\text{V}, 2.7\text{V}$ , and  $3.3\text{V}$  respectively.

[2]  $t_{pd}$  is the same as  $t_{PLH}$  and  $t_{PHL}$ .

$t_{en}$  is the same as  $t_{PZH}$  and  $t_{PZL}$ .

$t_{dis}$  is the same as  $t_{PLZ}$  and  $t_{PHZ}$ .

[3] Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.



#### 4、Testing Circuit

##### 4.1、AC Testing Circuit





Figure 3. Test circuit for measuring switching times

Definitions for test circuit:

$R_L$ =Load resistance.

$C_L$ =Load capacitance including jig and probe capacitance.

$R_T$ =Termination resistance should be equal to the output impedance  $Z_o$  of the pulse generator.

$V_{EXT}$ =External voltage for measuring switching times.



4.2、AC Testing Waveforms




Figure 4. The input (An,Bn) to output (Bn,An) propagation delays




Figure 5. 3-state enable and disable times

4.3、Measurement Points

Supply voltage $V_{CC}$	$V_M$	Input		
		$V_I$	$V_X$	$V_Y$
1.2V	$0.5 \times V_{CC}$	$V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
1.65V to 1.95V	$0.5 \times V_{CC}$	$V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
2.3V to 2.7V	$0.5 \times V_{CC}$	$V_{CC}$	$V_{OL} + 0.15V$	$V_{OH} - 0.15V$
2.7V	1.5V	2.7V	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$
3.0V to 3.6V	1.5V	2.7V	$V_{OL} + 0.3V$	$V_{OH} - 0.3V$


4.4、Test Data

Supply voltage $V_{CC}$	Input		Load		$V_{EXT}$		
	$V_I$	$t_r, t_f$	$C_L$	$R_L$	$t_{PLH}, t_{PHL}$	$t_{PLZ}, t_{PZL}$	$t_{PHZ}, t_{PZH}$
1.2V	$V_{CC}$	$\leq 2ns$	30pF	1k $\Omega$	open	$2 \times V_{CC}$	GND
1.65V to 1.95V	$V_{CC}$	$\leq 2ns$	30pF	1k $\Omega$	open	$2 \times V_{CC}$	GND
2.3V to 2.7V	$V_{CC}$	$\leq 2ns$	30pF	500 $\Omega$	open	$2 \times V_{CC}$	GND
2.7V	2.7V	$\leq 2.5ns$	50pF	500 $\Omega$	open	$2 \times V_{CC}$	GND
3.0V to 3.6V	2.7V	$\leq 2.5ns$	50pF	500 $\Omega$	open	$2 \times V_{CC}$	GND



## 5、Package Information


### 5.1、SOP20



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	2.350	2.650	0.093	0.104
A1	0.100	0.300	0.004	0.012
A2	2.100	2.500	0.083	0.098
b	0.330	0.510	0.013	0.020
c	0.204	0.330	0.008	0.013
D	12.520	13.000	0.493	0.512
E	7.400	7.600	0.291	0.299
E1	10.210	10.610	0.402	0.418
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°




## 5.2、TSSOP20



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
D	6.400	6.600	0.252	0.259
E	4.300	4.500	0.169	0.177
b	0.190	0.300	0.007	0.012
e	0.090	0.200	0.004	0.008
E1	6.250	6.550	0.246	0.258
A		1.200		0.047
A2	0.800	1.000	0.031	0.039
A1	0.050	0.150	0.002	0.006
e	0.65 (BSC)		0.026 (BSC)	
L	0.500	0.700	0.020	0.028
H	0.25(TYP)		0.01(TYP)	
$\theta$	1°	7°	1°	7°



## 5.3、DHVQFN20





## 6、 Statements And Notes

### 6.1、 The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

### 6.2、 Notes

Recommended carefully reading this information before the use of this product;

The information in this document are subject to change without notice;

This information is using to the reference only, the company is not responsible for any loss;

The company is not responsible for the any infringement of the third party patents or other rights of the responsibility.