

Features

- $V_{DS} (V) = 60V$
- $R_{DS(ON)} < 85m\Omega$ ($V_{GS} = 10V$)
- $R_{DS(ON)} < 99m\Omega$ ($V_{GS} = 4.5V$)


Application(s)

- Load/ System Switch


Benefits

- Multi-vendor compatibility
- Easier manufacturing
- Environmentally friendly
- Increased reliability

SOT - 23



1. GATE
2. SOURCE
3. DRAIN



Absolute Maximum Ratings

Symbol	Parameter	Max.	Units
V_{DS}	Drain-Source Voltage	60	V
$I_D @ T_A = 25^\circ C$	Continuous Drain Current, $V_{GS} @ 10V$	1.2	A
$I_D @ T_A = 70^\circ C$	Continuous Drain Current, $V_{GS} @ 10V$	0.93	
I_{DM}	Pulsed Drain Current	4.8	W
$P_D @ T_A = 25^\circ C$	Maximum Power Dissipation	1.25	
$P_D @ T_A = 70^\circ C$	Maximum Power Dissipation	0.80	
	Linear Derating Factor	0.01	$W/\text{ }^\circ C$
V_{GS}	Gate-to-Source Voltage	± 16	V
T_J, T_{STG}	Junction and Storage Temperature Range	-55 to + 150	$^\circ C$

Thermal Resistance

Symbol	Parameter	Typ.	Max.	Units
R_{QJA}	Junction-to-Ambient ③	100	100	$^\circ C/W$
R_{QJA}	Junction-to-Ambient ($t < 10s$) ④		99	


Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature.
- ② Pulse width $\leq 400\mu s$; duty cycle $\leq 2\%$.
- ③ Surface mounted on 1 in square Cu board.

Electric Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	60			V	$V_{GS} = 0V, I_D = 250\mu\text{A}$
$\Delta V_{(\text{BR})\text{DSS}}/\Delta T_J$	Breakdown Voltage Temp. Coefficient		0.06		V/ $^\circ\text{C}$	Reference to $25^\circ\text{C}, I_D = 5.0\text{mA}$
$R_{DS(\text{on})}$	Static Drain-to-Source On-Resistance		75	85	$\text{m}\Omega$	$V_{GS} = 10V, I_D = 1.2\text{A}$ ②
			83	99		$V_{GS} = 4.5V, I_D = 0.96\text{A}$ ②
$V_{GS(\text{th})}$	Gate Threshold Voltage	1.0		2.5	V	$V_{DS} = V_{GS}, I_D = 25\mu\text{A}$
I_{DSS}	Drain-to-Source Leakage Current			20	μA	$V_{DS} = 60V, V_{GS} = 0V$
				150		$V_{DS} = 60V, V_{GS} = 0V, T_J = 125^\circ\text{C}$
I_{GSS}	Gate-to-Source Forward Leakage			100	nA	$V_{GS} = 16V$
	Gate-to-Source Reverse Leakage			-100		$V_{GS} = -16V$
R_G	Internal Gate Resistance		7.5		Ω	
g_{fs}	Forward Transconductance	1.6			S	$V_{DS} = 25V, I_D = 1.2\text{A}$
Q_g	Total Gate Charge		0.67		nC	$I_D = 1.2\text{A}$
Q_{gs}	Gate-to-Source Charge		0.18			$V_{DS} = 30V$
Q_{gd}	Gate-to-Drain ("Miller") Charge		0.40			$V_{GS} = 4.5V$ ②
$t_{d(on)}$	Turn-On Delay Time		4.9		ns	$V_{DD} = 30V$ ②
t_r	Rise Time		3.8			$I_D = 1.2\text{A}$
$t_{d(off)}$	Turn-Off Delay Time		3.7			$R_G = 6.8\Omega$
t_f	Fall Time		2.8			$V_{GS} = 4.5V$
C_{iss}	Input Capacitance		64		pF	$V_{GS} = 0V$
C_{oss}	Output Capacitance		13			$V_{DS} = 25V$
C_{rss}	Reverse Transfer Capacitance		6.6			$f = 1.0\text{MHz}$

Source - Drain Ratings and Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Units	
I_s	Continuous Source Current (Body Diode)			1.2	A	MOSFET symbol showing the integral reverse p-n junction diode.
I_{SM}	Pulsed Source Current (Body Diode) ①			4.8		
V_{SD}	Diode Forward Voltage			1.2	V	$T_J = 25^\circ\text{C}, I_s = 1.2\text{A}, V_{GS} = 0V$ ②
t_{rr}	Reverse Recovery Time		14	21		$T_J = 25^\circ\text{C}, V_R = 30V, I_F = 1.3\text{A}$
Q_{rr}	Reverse Recovery Charge		8.3	12	nC	$dI/dt = 100\text{A}/\mu\text{s}$ ②

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics








Fig 4. Normalized On-Resistance vs. Temperature

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Fig 5.** Typical Capacitance vs.
Drain-to-Source Voltage**Fig 6.** Typical Gate Charge vs.
Gate-to-Source Voltage**Fig 7.** Typical Source-Drain Diode
Forward Voltage**Fig 8.** Maximum Safe Operating Area




Fig 9. Maximum Drain Current vs. Ambient Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Typical Effective Transient Thermal Impedance, Junction-to-Ambient




Fig 12. Typical On-Resistance vs. Gate Voltage




Fig 13. Typical On-Resistance vs. Drain Current




Fig 14a. Basic Gate Charge Waveform




Fig 14b. Gate Charge Test Circuit




Fig 15. Typical Threshold Voltage vs.
Junction Temperature






Fig 16. Typical Power vs. Time

SOT-23 PACKAGE OUTLINE DIMENSIONS

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

Marking**Ordering information**

Order code	Package	Baseqty	Deliverymode
IRLML2060TR	SOT-23	3000	Tape and reel