

isc Silicon NPN Power Transistors
MJ15024G
DESCRIPTION

- Complement to Type PNP MJ15025
- Excellent Safe Operating Area
- High DC current Gain
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Designed for high power audio, disk head positioners and other linear applications



ABSOLUTE MAXIMUM RATINGS(T_c=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V _{CBO}	Collector-Base Voltage	400	V
V _{CEO}	Collector-Emitter Voltage	250	V
V _{EBO}	Emitter-Base Voltage	5	V
I _C	Collector Current-Continuous	16	A
I _{CM} (1)	Collector Current-Peak	30	A
I _B	Base Current-Continuous	5	A
P _D	Total Power Dissipation @T _c =25°C	250	W
T _j	Junction Temperature	-65~200	°C
T _{stg}	Storage Temperature	-65~200	°C

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal Resistance, Junction to Case	0.70	°C/W

(1) Pulse Test: Pulse Width = 5 ms, Duty Cycle < 10%.



isc Silicon NPN Power Transistors**MJ15024G****ELECTRICAL CHARACTERISTICS**T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V _{CE0(SUS)} (1)	Collector-Emitter Sustaining Voltage	I _C = 100mA ; I _B = 0	250		V
V _{CE(sat)-1}	Collector-Emitter Saturation Voltage	I _C = 8A; I _B = 0.8A		1.4	V
V _{CE(sat)-2}	Collector-Emitter Saturation Voltage	I _C = 16A; I _B = 3.2A		4.0	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 8A ; V _{CE} = 4V		2.2	V
I _{CEO}	Collector Cutoff Current	V _{CE} = 200V; I _B = 0		0.5	mA
I _{CBO}	Collector Cutoff Current	V _{CB} = 250V; I _E = 0		0.25	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C =0		0.5	mA
h _{FE-1}	DC Current Gain	I _C = 8A ; V _{CE} = 4V	15	60	
h _{FE-2}	DC Current Gain	I _C = 16A ; V _{CE} = 4V	5		
C _{OB}	Output Capacitance	I _E = 0 ; V _{CB} = 10V; f _{test} = 1.0MHz	300		pF
f _T	Current-Gain—Bandwidth Product	I _C = 1A ; V _{CE} = 10V; f _{test} = 1.0MHz	4		MHz

(1) Pulse Test: Pulse Width = 300 μs, Duty Cycle < 2%.

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.