

isc Silicon NPN Power Transistors
2SC3298B
DESCRIPTION



- Good Linearity of h_{FE}
- High Collector-Emitter Breakdown Voltage-
 $V_{(BR)CEO} = 200V(\text{Min})$
- Complement to Type 2SA1306B
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

APPLICATIONS

- Power amplifier applications.
- Driver stage amplifier applications.

ABSOLUTE MAXIMUM RATINGS(Ta=25°C)

SYMBOL	PARAMETER		VALUE	UNIT
V_{CBO}	Collector-Base Voltage	2SC3298B	200	V
V_{CEO}	Collector-Emitter Voltage	2SC3298B	200	V
V_{EBO}	Emitter-Base Voltage		5	V
I_C	Collector Current-Continuous		1.5	A
I_B	Base Current-Continuous		0.15	A
P_C	Collector Power Dissipation @ $T_C=25^\circ\text{C}$		20	W
T_J	Junction Temperature		150	°C
T_{stg}	Storage Temperature Range		-55~150	°C



isc Silicon NPN Power Transistors

2SC3298B

ELECTRICAL CHARACTERISTICS

T_c=25°C unless otherwise specified

SYMBOL	PARAMETER		CONDITIONS	MIN	TYP.	MAX	UNIT
V _{(BR)CEO}	Collector-Emitter Breakdown Voltage	2SC3298B	I _C = 10mA; I _B = 0	200			V
V _{CE(sat)}	Collector-Emitter Saturation Voltage		I _C = 500mA; I _B = 50mA			1.5	V
V _{BE(on)}	Base-Emitter On Voltage		I _C = 500mA; V _{CE} = 5V			1.0	V
I _{CBO}	Collector Cutoff Current		V _{CB} = 160V; I _E = 0			1.0	μ A
I _{EBO}	Emitter Cutoff Current		V _{EB} = 5V; I _C =0			1.0	μ A
h _{FE}	DC Current Gain		I _C = 100mA ; V _{CE} = 5V	70		240	
f _T	Current-Gain—Bandwidth Product		I _C = 100mA ; V _{CE} = 10V		100		MHz
C _{OB}	Output Capacitance		I _E = 0 ; V _{CB} = 10V; f _{test} = 1.0MHz		25		pF

◆ h_{FE} Classifications

O	Y
70-140	120-240

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.