

**isc N-Channel MOSFET Transistor**
**FDP18N20F**
**FEATURES**

- Drain Current - $I_D = 9A @ T_C = 25^\circ C$
- Drain Source Voltage - $V_{DSS} = 200V(\text{Min})$
- Static Drain-Source On-Resistance  
- $R_{DS(\text{on})} = 0.14\Omega(\text{Max}) @ V_{GS} = 10V$

**DESCRIPTION**



- motor drive, DC-DC converter, power switch and solenoid drive.

**ABSOLUTE MAXIMUM RATINGS( $T_a = 25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{DSS}$	Drain-Source Voltage	200	V
$V_{GS}$	Gate-Source Voltage-Continuous	$\pm 30$	V
$I_D$	Drain Current-Continuous	18	A
$I_{DM}$	Drain Current-Single Pulse	72	A
$P_D$	Total Dissipation @ $T_C = 25^\circ C$	100	W
$T_J$	Max. Operating Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature	-55~150	$^\circ C$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.2	$^\circ C/W$



## isc N-Channel MOSFET Transistor

## FDP18N20F

ELECTRICAL CHARACTERISTICS (T<sub>c</sub>=25°C unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> = 0; I <sub>D</sub> = 0.25mA	200	--	V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> ; I <sub>D</sub> = 0.25mA	2.5	4.5	V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =200V; V <sub>GS</sub> = 0	--	10	uA
I <sub>GSS</sub>	Gate-Body Leakage Current	V <sub>GS</sub> = ±30V; V <sub>DS</sub> = 0	--	±100	nA
R <sub>DS(on)</sub>	Drain-Source On-Resistance	V <sub>GS</sub> = 10V; I <sub>D</sub> = 9A	--	0.14	Ω
V <sub>SD</sub>	Forward On-Voltage	I <sub>S</sub> = 18A; V <sub>GS</sub> = 0	--	1.5	V

## Product Disclaimer

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.