

**isc N-Channel MOSFET Transistor**
**SPW32N50C3**
**ISPW32N50C3**
**• FEATURES**

- Static drain-source on-resistance:  
 $R_{ds(on)} \leq 110m\Omega$
- Enhancement mode:
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**• DESCRIPTION**



- Improved Transconductance

**• ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ C$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{DSS}$	Drain-Source Voltage	500	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current-Continuous	32	A
$I_{DM}$	Drain Current-Single Pulsed	96	A
$P_D$	Total Dissipation @ $T_c=25^\circ C$	284	W
$T_j$	Max. Operating Junction Temperature	150	$^\circ C$
$T_{stg}$	Storage Temperature	-55~150	$^\circ C$

**• THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th(j-c)}$	Channel-to-case thermal resistance	0.44	$^\circ C/W$
$R_{th(j-a)}$	Channel-to-ambient thermal resistance	62	$^\circ C/W$



## isc N-Channel MOSFET Transistor

SPW32N50C3

ISPW32N50C3

## ELECTRICAL CHARACTERISTICS

 $T_c=25^\circ\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0V; I_D=0.25mA$	500			V
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}; I_D=1800\mu A$	2.1		3.9	V
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10V; I_D=20A$			110	$m\Omega$
$I_{GSS}$	Gate-Source Leakage Current	$V_{GS}=20V; V_{DS}=0V$			0.1	$\mu A$
$I_{DSS}$	Drain-Source Leakage Current	$V_{DS}=500V; V_{GS}=0V$			25	$\mu A$
$V_{SD}$	Diode forward voltage	$I_F=I_S; V_{GS}=0V$			1.2	V

**NOTICE:**

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.