

HSF






SPECIFICATIONS:

Current Rating: 0.75Amp
 Insulation Resistance: 1000M ohms min
 Contact Resistance: 20M ohms max
 Dielectric Withstanding: AC500V
 Operating Temperature: -65° C to +125° C
 Contact Material: Brass
 Insulator Material: PA6T, UL 94V-0 Black

Ordering Code:

PHBS02 - X - X - S - A-C-B - X - X - X
 ① ② ③ ④ ⑤ ⑥ ⑦ ⑧

- ① Series No:
- ② No. of Contacts: 01 To 50
- ③ Contact Plating:
 G0:Gold flash S0:Selective
 G1:3u" Gold S1:Selective 3u"
 G2:5u" Gold S2:Selective 5u"
 G3:10u" Gold S3:Selective 10u"
 G4:15u" Gold S4:Selective 15u"
 G5:30u" Gold S5:Selective 30u"
 SN: Tin
- ④ Connector Type:
 S:Single
- ⑤ Pin Length:
 A:0180=1.8mm
 C:0420=4.2mm
 B:0180=1.8mm
 Please mark the desired length in the A/C/B
- ⑥ Insulator Material:
 B:PA6T
 C:LCP
 E:PA9T
- ⑦ Packing:
 A:Tray
 B:Bag
 T:Tube
 U:Tube+CAP
 R:Tape&Reel
 W:Tape&Reel+CAP
- ⑧ Plastic High:
 H1:1.0mm
 H2:1.5mm



P. C. B LAYOUT

Standard IE P/N :

PHBS02-10-G0-S-0180-0420-0180-B-B-H1


A	C	B	Unless Otherwise specified tolerance	
1.8	4.2	1.8	X. ±0.35	X.XX: ±0.20
			X.X: ±0.25	X.XXX: ±0.15

Optional		SCALE: As Shown	UNIT: mm
DRAW	YG ZHONG	DATE	11/30/2015
CHECK	BobYang	DATE	11/30/2015

Antenk® ANTENK ELECTRONICS CO.,LTD
 Http://www.antenk.com
 E-mail:sales@antenk.com

TITLE: 1.00mm Pin Header Single Row
 Double Plastic Straight Type

DRAWING NO: PHBS02-XXS-0180-0420-0180-XXX
 PRODUCT NO: PHBS02-XXS-0180-0420-0180-XXX



REV	Increase packing method and material	2016/10/25
	DESCRIPTION	DATE