


DSIC Series



SWITCH OPERATION AND TAPING

- ① Use tweezers or ball point pen for operation
- ② Flux cleaning should be done without removing the Tape
- ③ If the Tape is removed, it adhered less than before when it is placed back on, possibly causing flux inflow.
- ④ Sealed switches withstand aqueous, detergent and isopropyl alcohol washing.

FEATURES

- ① All materials are UL94V0 grade, temperature resistant plastic.
- ② Twin contact design to ensure stable contact
- ③ Gold-plated contact to ensure low contact resistance Tin plated terminals to prevent contamination during soldering.

MATERIAL

Part Name	Material	Finished
Base	UL94V0(PPS)	Black
Cover	UL94V0(PPS)	Black
Actuator	UL94V0(PA46)	White
Movable	Copper Alloy	Gold/Tin
Terminal Contact	Brass	Gold/Tin
Terminal	Brass	Gold/Tin
Mylar	UL94VO	0.05mm

RATINGS

Contact Rating	Switching	25mA at 24VDC
	Non-Switching	100mA at 50VDC
Contact Resistance	Initial	50mΩ Max.
	After life	100mΩ Max.
	Insulation Resistance	100MΩ Min.60sec at 500VDC
	Dielectric Strength	500V DC for 60 seconds
	Switch Capacitance	5pF Max. at 1M Hz
	Operation Temperature	-40°C~+85°C
	Storage Temperature	-40°C~+85°C
Mechanical & Processing	Operation Force	1000gf Max.
	Mechanical Life	3000 cycles operations
	Resistance to Soldering	260±5°C for 3-5 seconds
	Electrical Life	2000 cycles 25mA 24VDC

DIMENSIONS (UNIT:MM)


Gold/Gold Platedg Type P/N	Dimensions mm(inch)		Quantity per Tube
	A	B	
DSIC01LH/S/JGET	—	2.54(0.1)	190
DSIC02LH/S/JGET	2.54(0.1)	5.08(0.2)	98
DSIC03LH/S/JGET	5.08(0.2)	7.62(0.3)	66
DSIC04LH/S/JGET	7.62(0.3)	10.16(0.4)	50
DSIC05LH/S/JGET	10.16(0.4)	12.70(0.5)	40
DSIC06LH/S/JGET	12.70(0.5)	15.24(0.6)	33
DSIC07LH/S/JGET	15.24(0.6)	17.78(0.7)	28
DSIC08LH/S/JGET	17.78(0.7)	20.32(0.8)	25
DSIC09LH/S/JGET	20.32(0.8)	22.86(0.9)	22
DSIC10LH/S/JGET	22.86(0.9)	25.40(1.0)	20
DSIC12LH/S/JGET	27.94(1.1)	30.48(1.2)	16

Piece/Tape&Reel:LS...800pcs;Ts...1000pcs

ORDER INFORMATION

DSIC	04	T	S	G	E	R
 IC Type	 Positions: 01=1 Position 02=2 Position 08=8 Position	 Terminal A=Auto insert H=Straight J=J lead S= SMD type	 Finish E=3u"Gold-plated F=10u"Gold-plated A=12u"Gold-plated B=20u"Gold-plated G=30u"Gold-plated	 Actuator: L=Extension S=Low profile W/O Tape T=Tape sealed	 Finish G=Full Gold S=Contat-Gold-plated Terminal-Tin Plated	 Packing R=Tepe&Reel T=Tube

DRAGRAM



ENVIRONMENTAL TEST

Cold Resistance Test	Switches under temperature at $-40^{\circ}\text{C} \pm 2^{\circ}\text{C}$ for 96 hours.
Dry Heat Resistance Test	Switches under temperature at $85^{\circ}\text{C} \pm 2^{\circ}\text{C}$ for 96 hours.
Humidity Test	Per MIL-STD-202F, Method 103B, Test Condition B:
	There shall be no evidence of corrosion and the insulation resistance shall be no less than 100 megaohms.
Vibration Test	Per MIL-STD-202F, Method 204D, Test Condition A:
	There shall be no opening of closed contacts or closing of open contacts in excess of 10 microseconds.
Shock Test	Per MIL-STD-202F, Method 213B, Test Condition A:
	There shall be no opening of closed contacts or closing of open contacts in excess of 10 microseconds.
Thermal Shock Test	Per MIL-STD-202F, Method 107G, Test Condition A:
	There shall be no evidence of physical damage or permanent change in electrical characteristics.
Salt-Spray Test	Per MIL-STD-202F, Method 101D, Test Condition B:
	There are under $35 \pm 2^{\circ}\text{C}$ in temperature and $5 \pm 1\%$ salt-water concentration for 48 ± 1 hour.