



### Key Features:

- VFD Mode for superior accuracy on VFD-controlled equipment
- Inrush mode to capture AC Current spikes during start-up
- Bluetooth® connectivity up to 10 m (32 ft)

### Main Applications:

- Advanced power analysis and variable frequency drive (VFD) filtering functions
- Accurately analyze voltage in complex machinery
- Harmonics, inrush, current, and phase rotation testing

[www.flir.com/CM85-2](http://www.flir.com/CM85-2)

## SPECIFICATIONS

Measurement Ranges and Accuracy	
Voltage DC	99.99 V, $\pm(0.7\% + 2 \text{ digits})$ 999.9 V, $\pm(0.7\% + 2 \text{ digits})$
Voltage AC	0.05 V to 99.99 V, $\pm(1.0\% + 5 \text{ digits})$ 999.9 V, 50 Hz to 500 Hz
VFD, ACV	0.05 V to 99.99 V, 50 Hz to 60 Hz $\pm(1\% + 5 \text{ digits})$ 999.9 V, 50 Hz to 60 Hz $\pm(1\% + 5 \text{ digits})$
Current DC	99.99 A, $\pm(2\% + 0.5 \text{ A})$ 999.9 A, $\pm(2\% + 5 \text{ digits})$
Current AC	0.10 A to 99.99 A, 50 Hz to 60 Hz $\pm(2\% + 5 \text{ digits})$ 999.9 A, >60 Hz to 400 Hz $\pm(2.5\% + 5 \text{ digits})$
VFD, ACA	0.10 A to 99.99 A, 50 Hz to 60 Hz $\pm(2\% + 5 \text{ digits})$ 999.9 A, 50 Hz to 60 Hz $\pm(2\% + 5 \text{ digits})$
Peak Hold ACV	140.0 V, $\pm(3.0\% + 15 \text{ digits})$ 1400 V, $\pm(3.0\% + 15 \text{ digits})$
Peak Hold ACA	140.0 A, $\pm(3.5\% + 15 \text{ digits})$ 1400 A, $\pm(3.5\% + 15 \text{ digits})$
Frequency	20.00 Hz to 99.99 Hz, $\pm(0.5\% + 3 \text{ digits})$ 20.0 Hz to 999.9 Hz, $\pm(0.5\% + 3 \text{ digits})$ 0.020 kHz to 9.999 kHz, $\pm(0.5\% + 3 \text{ digits})$
Total harmonic distortion ACA/ACV	99.9%, $\pm(3.0\% + 10 \text{ digits})$
Harmonic distortion H01–H12	99.9%, $\pm(5\% + 10 \text{ digits})$
Harmonic distortion H13–H25	99.9%, $\pm(10\% + 10 \text{ digits})$
Inrush current ACA	99.99 A, $\pm(3\% + 0.3 \text{ A})$ 999.9 A, $\pm(3\% + 5 \text{ digits})$
Watts DC	9.999 kW (10 V, 5 A min), $\pm(3\% + 0.05 \text{ kW})$ 99.99 kW (10 V, 5 A min), $\pm(3\% + 0.5 \text{ kW})$ 999.9 kW (10 V, 5 A min), $\pm(3\% + 10 \text{ digits})$

Watts AC	9.999 kW (10 V, 5 A min), $\pm(3\% + 10 \text{ digits})$ 99.99 kW (10 V, 5 A min), $\pm(3\% + 10 \text{ digits})$ 999.9 kW (10 V, 5 A min), $\pm(3\% + 10 \text{ digits})$
Power factor	-1.00 to 0.00 to +1.00, $\pm 3^\circ \pm 1 \text{ digit}$
Resistance	999.9 $\Omega$ , $\pm(1.0\% + 5 \text{ digits})$ 9.999 k $\Omega$ , $\pm(1.0\% + 3 \text{ digits})$ 99.99 k $\Omega$ , $\pm(1.0\% + 3 \text{ digits})$
Continuity	999.9 $\Omega$ , $\pm(1.0\% + 5 \text{ digits})$
Diode	0.40 V to 0.80 V, $\pm 0.1 \text{ V}$
Capacitance	3.999 $\mu\text{F}$ , $\pm(1.9\% + 8 \text{ digits})$ 39.99 $\mu\text{F}$ , $\pm(1.9\% + 8 \text{ digits})$ 399.9 $\mu\text{F}$ , $\pm(1.9\% + 8 \text{ digits})$ 3.999 mF, $\pm(1.9\% + 8 \text{ digits})$
Measuring rate	3 times per second
Meter Data	
Jaw opening	45 mm (1.77 in)
Bluetooth range	10 m (32 ft)
Category rating	CAT IV-600 V, CAT III-1000 V
Data recording	Available via METERLiNK App
Warranty	Limited Lifetime Warranty <a href="http://www.flir.com/testwarranty">www.flir.com/testwarranty</a>
Drop test	1.2 m (4 ft)
Certifications	
Certifications	UL, CE, FCC, IC, UKCA, CSAUS
Complies with Safety Standards	IEC 61010-1:2010, IEC 61010-2-032:2012, IEC 61010-2-033:2012
<b>(continued)</b>	

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).

For more information contact: [Sales@TeledyneFLIR.com](mailto:Sales@TeledyneFLIR.com)  
or to find your local support number, visit: [flir.com/contactsupport](http://flir.com/contactsupport)  
[www.teledyneflir.com](http://www.teledyneflir.com)

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.


For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2023 Teledyne FLIR, LLC. All rights reserved.

Revised 04/25/23  
FLIR\_CM85-2\_datasheet-LTR-23-0419

## SPECIFICATIONS, CONT.

EMC	FCC: 47 CFR Part 15 Subpart B CE: EN IEC 61326-1:2021 EN IEC 61326-2-2:2021 EN 301 489-1 V2.2.3 (2019-11) EN 301 489-17 V3.2.4 (2020-09) RF: ETSI EN 300 328 V2.2.2 EN 62479:2010 EN 50663:2017
<b>Power System</b>	
Power requirements	6 × 1.5 V AAA alkaline batteries
Battery life	50 hours with alkaline batteries (backlight, worklight, and Bluetooth off)
Auto power off	Approx. 30 minutes
<b>Environmental Data</b>	
Operating ambient temperatures and relative humidity	0°C to 10°C (32°F to 50°F) (non-condensing) 10°C to 30°C (50°F to 86°F) (≤80% RH) 30°C to 40°C (86°F to 104°F) (≤75% RH) 40°C to 50°C (104°F to 122°F) (≤45% RH)
Storage temperature and relative humidity	-10°C to 50°C (14°F to 122°F). 0 to 80% RH (batteries not fitted)
Temperature coefficient	0.2 × (specified accuracy)/° C, <18°C, >28°C.
Operating altitude	2000 m (6562 ft)
Pollution degree	2
Shock vibration	Random vibration per MIL-PRF-28800f Class 2 (5 to 55 Hz, 3 g maximum)
<b>Meter Physical Data</b>	
Weight	0.65 kg (1.43 lb), including batteries
Dimensions (L × W × H)	276 mm × 101 mm × 50 mm (10.87 in × 3.98 in × 1.97 in)

Specifications subject to change. For the most up-to-date specifications, please visit [flir.com](http://flir.com).



For more information contact: [Sales@TeledyneFLIR.com](mailto:Sales@TeledyneFLIR.com)  
 or to find your local support number, visit: [flir.com/contactsupport](http://flir.com/contactsupport)  
[www.teledyneflir.com](http://www.teledyneflir.com)

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact [exportquestions@flir.com](mailto:exportquestions@flir.com). ©2023 Teledyne FLIR, LLC. All rights reserved.

Revised 04/25/23  
 FLIR\_CM85-2\_datasheet-LTR-23-0419