

## Product Brief

# XMC4800 Microcontroller

## with integrated EtherCAT®

The XMC4800 offers the first EtherCAT® node integrated on an ARM® Cortex®-M controller with on-chip flash and analog/mixed signal capabilities. This unprecedented level of integration offers the EtherCAT® community a new – previously unimaginable – benchmark for ease of implementation.

The XMC4800 enables the most compact designs, eliminating the need for a dedicated EtherCAT® ASIC, external memory and crystal. Designers benefit from BOM cost and PCB space savings.

As a member of the XMC4000 microcontroller family with full pin and code compatibility, the XMC4800 is designed to the same high quality and reliability standards as the rest of the family. XMC4800 enables EtherCAT® applications in harsh environments with 125°C ambient temperatures. In addition, it will be available through 2027 or longer.

### Key Features

- EtherCAT® slave, 6 CAN nodes
- ARM® Cortex®-M4 CPU at 144MHz, with up to 2MB flash and 352KB RAM
- Qualified for 125°C automotive temperature range
- Long-term availability through 2027 or longer


### Key Benefits

- Most compact EtherCAT® design – no additional external components required
- Bill of Material (BOM) cost and PCB space savings
- Enablement of EtherCAT® technology in harsh environments with 125°C ambient temperatures

### Applications

- Factory automation
- Industrial motor control
- Robotics


### XMC Microcontroller Product Portfolio



# XMC4800 Microcontroller

## with integrated EtherCAT®

### XMC4800 Series Block Diagram



### XMC4800 Series Overview

Product Name	Feature Set	Compatibility
XMC4800-F100F1024; LQFP-100 -40°C – 85°C XMC4800-F100K1024; LQFP-100 -40°C – 125°C	EtherCAT®, 1 MB Flash/200 KB RAM, 6 CAN nodes	Pin compatibility with all XMC4000 devices in LQFP-100. Code compatibility with all XMC4000 devices.
XMC4800-F100F1536; LQFP-100 -40°C – 85°C XMC4800-F100K1536; LQFP-100 -40°C – 125°C	EtherCAT®, 1.5 MB Flash/276 KB RAM, 6 CAN nodes	
XMC4800-F100F2048; LQFP-100 -40°C – 85°C XMC4800-F100K2048; LQFP-100 -40°C – 125°C	EtherCAT®, 2 MB Flash/352 KB RAM, 6 CAN nodes	
XMC4800-F144F1024; LQFP-144 -40°C – 85°C XMC4800-F144K1024; LQFP-144 -40°C – 125°C	EtherCAT®, 1 MB Flash/200 KB RAM, 6 CAN nodes	Pin compatibility with all XMC4000 devices in LQFP-144. Code compatibility with all XMC4000 devices.
XMC4800-F144F1536; LQFP-144 -40°C – 85°C XMC4800-F144K1536; LQFP-144 -40°C – 125°C	EtherCAT®, 1.5 MB Flash/276 KB RAM, 6 CAN nodes	
XMC4800-F144F2048; LQFP-144 -40°C – 85°C XMC4800-F144K2048; LQFP-144 -40°C – 125°C	EtherCAT®, 2 MB Flash/352 KB RAM, 6 CAN nodes	
XMC4800-E196F1024; LFBGA-196 -40°C – 85°C XMC4800-E196K1024; LFBGA-196 -40°C – 125°C	EtherCAT®, 1 MB Flash/200 KB RAM, 6 CAN nodes	Upward pin compatibility with all XMC4000 devices in LFBGA-144. Code compatibility with all XMC4000 devices.
XMC4800-E196F1536; LFBGA-196 -40°C – 85°C XMC4800-E196K1536; LFBGA-196 -40°C – 125°C	EtherCAT®, 1.5 MB Flash/276 KB RAM, 6 x CAN Nodes	
XMC4800-E196F2048; LFBGA-196 -40°C – 85°C XMC4800-E196K2048; LFBGA-196 -40°C – 125°C	EtherCAT®, 2 MB Flash/352 KB RAM, 6 x CAN Nodes	

Published by  
Infineon Technologies AG  
85579 Neubiberg, Germany

© 2015 Infineon Technologies AG.  
All Rights Reserved.

Visit us:  
[www.infineon.com](http://www.infineon.com)

**Please note!**

THIS DOCUMENT IS FOR INFORMATION PURPOSES ONLY AND ANY INFORMATION GIVEN HEREIN SHALL IN NO EVENT BE REGARDED AS A WARRANTY, GUARANTEE OR DESCRIPTION OF ANY FUNCTIONALITY, CONDITIONS AND/OR QUALITY OF OUR PRODUCTS OR ANY SUITABILITY FOR A PARTICULAR PURPOSE. WITH REGARD TO THE TECHNICAL SPECIFICATIONS OF OUR PRODUCTS, WE KINDLY ASK YOU TO REFER TO THE RELEVANT PRODUCT DATA SHEETS PROVIDED BY US. OUR CUSTOMERS AND THEIR TECHNICAL DEPARTMENTS ARE REQUIRED TO EVALUATE THE SUITABILITY OF OUR PRODUCTS FOR THE INTENDED APPLICATION.

WE RESERVE THE RIGHT TO CHANGE THIS DOCUMENT AND/OR THE INFORMATION GIVEN HEREIN AT ANY TIME.

**Additional information**

For further information on technologies, our products, the application of our products, delivery terms and conditions and/or prices please contact your nearest Infineon Technologies office ([www.infineon.com](http://www.infineon.com)).

**Warnings**

Due to technical requirements, our products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by us in a written document signed by authorized representatives of Infineon Technologies, our products may not be used in any life endangering applications, including but not limited to medical, nuclear, military, life critical or any other applications where a failure of the product or any consequences of the use thereof can result in personal injury.