


-30V P+P-CHANNEL ENHANCEMENT MODE MOSFET

MAIN CHARACTERISTICS

I_D	-8.8A
V_{DSS}	-30V
R_{DS(on)-typ}(@V_{GS}=10V)	< 20mΩ(Type:16 mΩ)



APPLICATION

- ◆Lithium battery protection
- ◆Wireless impact
- ◆Mobile phone fast charging

Product Specification Classification

Part Number	Package	Marking	Pack
YFW4957S	SOP-8	YFW 4957S XXXXX	3000PCS/Tape

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Symbols	Value	Units
Drain-Source Voltage	V_{DS}	-30	V
Gate - Source Voltage	V_{GS}	±20	V
Continuous Drain Current, -V _{GS} @ -10V ¹ @T _A =25°C	I_D	-8.8	A
Continuous Drain Current, -V _{GS} @ -10V ¹ @T _A =70°C	I_D	-6.3	A
Pulsed Drain Current ²	I_{DM}	-32	A
Single Pulse Avalanche Energy ³	E_{AS}	81.2	mJ
Avalanche Current	I_{AS}	-42	A
Total Power Dissipation ⁴ @T _A =25°C	P_D	1.5	W
Storage Temperature Range	T_{STG}	-55 to +150	°C
Operating Junction Temperature Range	T_J	-55 to +150	°C
Thermal Resistance Junction-Ambient ¹	R_{θJA}	85	°C/W
Thermal Resistance Junction to Case ¹	R_{θJC}	25	°C/W

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{GS}=0V, I_D=-250\mu A$	BV_{DSS}	-30	-33	-	V
BVDSS Temperature Coefficient	Reference to 25°C, $I_D=-1mA$	$\Delta BV_{DSS}/\Delta T_J$	-	-0.022	-	V/°C
Static Drain-Source On-Resistance ²	$V_{GS}=-10V, I_D=-6A$	$R_{DS(on)}$	-	16	20	mΩ
	$V_{GS}=-4.5V, I_D=-4A$		-	25	35	
Gate -Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu A$	$V_{GS(th)}$	-1.0	-1.6	-2.5	V
$V_{GS(th)}$ Temperature Coefficient		$\Delta V_{GS(th)}$	-	4.6	-	mV/°C
Drain-Source Leakage Current	$V_{DS}=-24V, V_{GS}=0V, T_J=25^\circ C$	I_{DSS}	-	-	-1	μA
	$V_{DS}=-24V, V_{GS}=0V, T_J=55^\circ C$		-	-	-5	
Gate -Source Leakage Current	$V_{GS}=\pm 20V, V_{DS}=0V$	I_{GSS}	-	-	±100	nA
Forward Transconductance	$V_{DS}=-5V, I_D=-6A$	g_{fs}	-	17	-	S
Gate Resistance	$V_{DS}=0V, V_{GS}=0V, f=1MHz$	R_G	-	13	-	Ω
Total Gate Charge(-4.5V)	$V_{DS}=-15V$ $V_{GS}=-4.5V$ $I_D=-6A$	Q_g	-	12.6	-	nC
Gate-Source Charge		Q_{gs}	-	4.8	-	
Gate-Drain Charge		Q_{gd}	-	4.8	-	
Turn-on delay time	$V_{DD}=-15V$ $V_{GS}=-10V$ $I_D=-6A$ $R_G=3.3\Omega$	$t_{d(on)}$	-	4.6	-	ns
Rise Time		T_r	-	14.8	-	
Turn-Off Delay Time		$t_{d(OFF)}$	-	41	-	
Fall Time		t_f	-	19.6	-	
Input Capacitance	$V_{DS}=-15V$ $V_{GS}=0V$ $f=1MHz$	C_{iss}	-	1345	-	pF
Output Capacitance		C_{oss}	-	194	-	
Reverse Transfer Capacitance		C_{rss}	-	158	-	
Continuous Source Current ^{1,5}	$V_G=V_D=0V, \text{Force Current}$	I_S	-	-	-6.5	A
Pulsed Source Current ^{2,5}		I_{SM}	-	-	-26	A
Diode Forward Voltage ²	$V_{GS}=0V, I_S=-1A, T_J=25^\circ C$	V_{SD}	-	-	-1.2	V
Reverse Recovery Time	$I_F=-6A, dI/dt=100A/\mu s, T_J=25^\circ C$	t_{rr}	-	16.3	-	ns
Reverse Recovery Charge		Q_{rr}	-	5.9	-	nC

Note :

- 1、 The data tested by surface mounted on a 1 inch 2 FR-4 board with 20Z copper.
- 2、 The data tested by pulsed , pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
- 3、 The EAS data shows Max. rating . The test condition is $V_{DD}=-25V, V_{GS}=-10V, L=0.1mH, I_{AS}=-8.8A$
- 4、 The power dissipation is limited by 150°C junction temperature
- 5、 The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation

Ratings and Characteristic Curves

Typical Characteristics




Fig.1 Typical Output Characteristics




Fig.2 On-Resistance v.s. Gate-Source




Fig.3 Forward Characteristics of Reverse




Fig.4 Gate-Charge Characteristics




Fig.5 Normalized $V_{GS(th)}$ vs. T_J




Fig.6 Normalized $R_{DS(on)}$ vs. T_J

Ratings and Characteristic Curves




Fig.7 Capacitance




Fig.8 Safe Operating Area




Fig.9 Normalized Maximum Transient Thermal Impedance




Fig.10 Switching Time Waveform








Fig.11 Unclamped Inductive Switching Waveform

SOP-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270 (BSC)		0.050 (BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°



Recommended Minimum Pads