


40V N-CHANNEL ENHANCEMENT MODE MOSFET
MAIN CHARACTERISTICS

I_D	180A
V_{DSS}	40V
$R_{DS(on)-typ}(@V_{GS}=10V)$	< 2.0mΩ (Type: 1.5 mΩ)


Features

- ◆ Low RDS(on) & FOM
- ◆ Extremely low switching loss
- ◆ Excellent stability and uniformity
- ◆ Fast switching and soft recovery
- ◆ Invertors
- ◆ Synchronous-rectification applications
- ◆ YFW-SGT technology

Application

- ◆ Consumer electronic power supply
- ◆ Motor control
- ◆ Synchronous-rectification
- ◆ Isolated DC
- ◆ Synchronous-rectification applications

Product Specification Classification

Part Number	Package	Marking	Pack
YFWG180N04AT	TO-220AB	YFW 180N04AT XXXXX	1000PCS/Box
YFWG180N04AF	TO-220F	YFW 180N04AF XXXXX	1000PCS/Box
YFWG180N04AS	TO-263	YFW 180N04AS XXXXX	800PCS/Reel

Maximum Ratings at $T_c=25^\circ C$ unless otherwise specified

Characteristics	Symbols	Value	Units
Drain-Source Voltage	V_{DS}	40	V
Gate - Source Voltage	V_{GS}	± 20	V
Continuous Drain Current ¹⁾	I_D	180	A
Pulsed Drain Current ²⁾	$I_{D, pulse}$	390	A
Power Dissipation ³⁾	P_D	140	W
Single Pulse Avalanche Energy ⁴⁾	E_{AS}	300	mJ
Operation and storage temperature	T_J, T_{STG}	-55 to +150	°C
Thermal Resistance Junction-Case	$R_{\theta JC}$	0.89	°C/W
Thermal Resistance Junction-ambient ⁵⁾	$R_{\theta JA}$	62	°C/W

Maximum Ratings at T_c=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =250μA	BV _{DSS}	40	-	-	V
Gate -Threshold Voltage	V _{DS} =V _{GS} , I _D =250μA	V _{GS(th)}	1.3	*	2.5	V
Drain-source on-state resistance	V _{GS} =10V, I _D =55A	R _{DS(ON)}	-	1.5	2.0	mΩ
	V _{GS} =4.5V, I _D =55A		-	2.5	3.0	
Gate -Source Leakage Current	V _{GS} =20V	I _{GSS}	-	*	100	nA
	V _{GS} =-20V		-	-	-100	
Drain -Source Leakage Current	V _{DS} =40V , V _{GS} =0V	I _{DSS}	-	-	1	μA
Input Capacitance	V _{DS} =20V V _{GS} =0V f=100MHz	C _{iss}	-	6587.4	-	pF
Output Capacitance		C _{oss}	-	2537.3	-	
Reverse Transfer Capacitance		C _{rss}	-	178.8	-	
Turn-on delay time	V _{GS} =10V V _{DD} =20V R _G =2Ω I _D =20A	t _{d(on)}	-	26.6	-	ns
Rise Time		T _r	-	9.3	-	
Turn-Off Delay Time		t _{d(OFF)}	-	96	-	
Fall Time		t _f	-	39.3	-	
Total Gate Charge	I _D =20A V _{DS} =20V V _{GS} =10V	Q _g	-	96.8	-	nC
Gate-Source Charge		Q _{gs}	-	14.5	-	
Gate-Drain Charge		Q _{gd}	-	18.4	-	
Gate plateau voltage		V _{plateau}	-	2.7	-	
Diode forward current	V _{GS} <V _{th}	I _s	-	-	130	A
Pulsed source current		I _{SP}	-	-	390	
Diode Forward Voltage	V _{GS} =0V , I _s =20A	V _{SD}	-	-	1.3	V
Reverse recovery time	I _s =20 A, di/dt=100 A/μs	t _{rr}	-	205	-	ns
Reverse recovery charge		Q _{rr}	-	557.4	-	nC
Peak reverse recovery current		I _{rrm}	-	4.3	-	A

Note

- 1) Calculated continuous current based on maximum allowable junction temperature.
- 2) Repetitive rating; pulse width limited by max. junction temperature.
- 3) Pd is based on max. junction temperature, using junction-case thermal resistance.
- 4) VDD=30 V, RG=50 Ω, L=0.3 mH, starting Tj=25 °C.
- 5) The value of RθJA is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with Ta=25 °C.


Ratings and Characteristic Curves


Figure 1, Typ. output characteristics




Figure 2, Typ. transfer characteristics




Figure 3, Typ. capacitances




Figure 4, Typ. gate charge




Figure 5, Drain-source breakdown voltage




Figure 6, Drain-source on-state resistance

Ratings and Characteristic Curves




Figure 7, Forward characteristic of body diode

Figure 8, Drain-source on-state resistance




Figure 9, Safe operation area $T_C=25^\circ\text{C}$


Ratings and Characteristic Curves


Figure 1, Gate charge test circuit & waveform




Figure 2, Switching time test circuit & waveforms




Figure 3, Unclamped inductive switching (UIS) test circuit & waveforms





Figure 4, Diode reverse recovery test circuit & waveforms


Package Outline Dimensions Millimeters

TO-220AB



Dim.	Min.	Max.
A	10.15	10.35
B	2.65	2.95
C	3.70	3.90
D	28.5	29.5
E	1.30	1.45
F	6.35	6.55
G	2.9	3.3
H	15.0	16.0
I	0.38	0.42
J	4.45	4.55
K	1.25	1.35
L	Typ 5.08	
M	Typ 2.54	
N	3.1	3.3
O	0.76	0.84
All Dimensions in millimeter		


TO-220F



Dim.	Min.	Max.
A	9.95	10.25
B	2.95	3.25
C	1.25	1.45
D	12.95	13.25
E	0.50	0.65
F	3.1	3.3
G	1.30	1.45
H	Typ 2.54	
I	Typ 5.08	
J	4.60	4.75
K	2.50	2.65
L	6.35	6.55
M	15.4	16.0
N	2.75	3.05
O	0.48	0.52
P	0.76	0.84
All Dimensions in millimeter		

Package Outline Dimensions Millimeters

TO-263



Dim.	Min.	Max.
A	10.1	10.2
B	7.4	7.6
C	1.3	1.5
D	0.55	0.75
E	5.0	6.0
F	1.4	1.6
G	0.78	0.86
H	1.2	1.3
I	Typ2.54	
J	8.4	8.6
K	4.45	4.55
L	1.25	1.35
M	0.02	0.1
N	2.4	2.8
O	0.36	0.40

All Dimensions in millimeter