

600V N-CHANNEL ENHANCEMENT MODE MOSFET

MAIN CHARACTERISTICS


I_D	4A
V_{DSS}	600V
R_{DS(on)}-typ(@V_{GS}=10V)	<2.5Ω(Type:2.1 Ω)

Features

- ◆Fast Switching
- ◆Low ON Resistance
- ◆Low Gate Charge
- ◆100% Single Pulse avalanche energy Test
- ◆LeadfreeincomplywithEURoHS2011/65/EUdirectives

Echanical Data

- ◆Case: Molded plastic
- ◆Mounting Position: Any
- ◆Molded Plastic: UL Flammability Classification Rating 94V-0
- ◆Solder bath temperature275℃maximum,10s per JESD22-106



Product Specification Classification

Part Number	Package	Marking	Pack
YFW4N60AT	TO-220AB	YFW 4N60AT XXXXX	1000PCS/Box
YFW4N60AF	TO-220F(0.5mm)	YFW 4N60AF XXXXX	1000PCS/Box
YFW4N60AS-G	TO-263	YFW 4N60AS XXXXX	1000PCS/Box
YFW4N60AS	TO-263	YFW 4N60AS XXXXX	800PCS/Reel
YFW4N60AMJ	TO-251	YFW 4N60AMJ XXXXX	1000PCS/Box
YFW4N60AD	TO-252	YFW 4N60AD XXXXX	2500PCS/Reel

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Symbols	Value			Units
		220AB/263	220F	251/252	
Drain-Source Voltage	V_{DS}	600			V
Gate-Source Voltage	V_{GS}	±30			V
Continue Drain Current	I_D	4			A
		- Continuous(Tc=100°C)			
Pulsed Drain Current (Note1)	I_{DM}	16			A
Power Dissipation	P_D	75	30	51	W
		-Derate above 25°C			W/°C
Single Pulse Avalanche Energy (Note2)	E_{AS}	220			mJ
Avalanche Current (Note 1)	I_{AR}	4			A
Repetitive Avalanche Energy (Note 1)	E_{AR}	10			mJ
Operating Temperature Range	T_J	150			°C
Storage Temperature Range	T_{STG}	-55 to +150			°C
Thermal Resistance, Junction to Case	$R_{\theta JC}$	1.67	4.17	2.5	°C/W
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	62.5	62.5	85	°C/W

Maximum Ratings at Tc=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	$V_{GS} = 0 V, I_D = 250 \mu A$	BV_{DSS}	600	-	-	V
Drain-Source Leakage Current	$V_{DS} = 600 V, V_{GS} = 0 V$	I_{DSS}	-	-	1	uA
	$V_{DS}=480V, T_c=125^\circ C$		-	-	10	
Gate Leakage Current	$V_{GS} = \pm 30 V, V_{DS} = 0 V$	I_{GSS}	-	-	±100	nA
Gate-Source Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250 \mu A$	$V_{GS(th)}$	2	-	4	V
Drain-Source On-State Resistance	$V_{GS} = 10 V, I_D = 2 A$	$R_{DS(on)}$	-	2.1	2.5	Ω
Forward Transconductance	$V_{DS} = 40 V, I_D = 2 A$	g_{fs}	-	3.5	-	S
Input Capacitance	$V_{GS} = 0 V, V_{DS} = 25 V, f = 1 KHz$	C_{iss}	-	573	-	pF
Output Capacitance		C_{oss}	-	54	-	
Reverse Transfer Capacitance		C_{rss}	-	4	-	
Turn-on Delay Time	$I_D = 4 A, V_{DD} = 300 V, R_G = 25 \Omega (Note3,4)$	$td(ON)$	-	13	-	nS
Rise Time		tr	-	14	-	
Turn-Off Delay Time		$td(OFF)$	-	32	-	
Fall Time		tf	-	12	-	
Total Gate Charge	$I_D = 4 A, V_{DD} = 480 V, V_{GS} = 10 V (Note3,4)$	Q_G	-	14	-	nC
Gate to Source Charge		Q_{GS}	-	2.5	-	
Gate to Drain Charge		Q_{GD}	-	6.3	-	





Source-Drain Diode Characteristics at Ta=25°C unless otherwise specified

Characteristics	Test Condition	Symbols	Min	Typ	Max	Units
Maximum Continuous Drain-Source Diode Forward Current		I_S	-	-	4	A
Maximum Pulsed Drain-Source Diode Forward Current		I_{SM}	-	-	16	A
Drain-Source Diode Forward Voltage	I _{SD} = 4 A	V_{SD}	-	-	1.4	V
Reverse Recovery Time	I _{SD} = 4 A, V _{GS} = 0 V, dI _F / dt = 100 A/μs (Note3)	trr	-	242	-	nS
Reverse Recovery Charge		Qrr	-	0.97	-	uC





Note:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. I_{AS} = 4 A, V_{DD} = 50 V, L = 25mH, R_G = 25Ω, starting T_J = 25°C.
3. ulse test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2%.
4. Essentially Independent of Operating Temperature

Ratings and Characteristic Curves



Ratings and Characteristic Curves



Package Outline Dimensions Millimeters

TO-220AB

	Dim.	Min.	Max.
	A	10.15	10.35
	B	2.65	2.95
	C	3.70	3.90
	D	28.5	29.5
	E	1.30	1.45
	F	6.35	6.55
	G	2.9	3.3
	H	15.0	16.0
	I	0.38	0.42
	J	4.45	4.55
	K	1.25	1.35
	L	Typ 5.08	
	M	Typ 2.54	
N	3.1	3.3	
O	0.76	0.84	
All Dimensions in millimeter			

TO-220F

	Dim.	Min.	Max.
	A	9.95	10.25
	B	2.95	3.25
	C	1.25	1.45
	D	12.95	13.25
	E	0.50	0.65
	F	3.1	3.3
	G	1.30	1.45
	H	Typ 2.54	
	I	Typ 5.08	
	J	4.60	4.75
	K	2.50	2.65
	L	6.35	6.55
	M	15.4	16.0
	N	2.75	3.05
	O	0.48	0.52
P	0.76	0.84	
All Dimensions in millimeter			

Package Outline Dimensions Millimeters

TO-263

	Dim.	Min.	Max.
	A	10.1	10.2
	B	7.4	7.6
	C	1.3	1.5
	D	0.55	0.75
	E	5.0	6.0
	F	1.4	1.6
	G	0.78	0.86
	H	1.2	1.3
	I	Typ2.54	
	J	8.4	8.6
	K	4.45	4.55
	L	1.25	1.35
	M	0.02	0.1
N	2.4	2.8	
O	0.36	0.40	
All Dimensions in millimeter			

TO-252

	Dim.	Min.	Typ.	Max.
	A	2.10	-	2.50
	A2	0	-	0.10
	B	0.66	-	0.86
	B2	5.18	-	5.48
	C	0.40	-	0.60
	C2	0.44	-	0.58
	D	5.90	-	6.30
	D1	5.30REF		
	E	6.40	-	6.80
	E1	4.63	-	-
	G	4.47	-	4.67
	H	9.50	-	10.70
	L	1.09	-	1.21
	L2	1.35	-	1.65
V1	-	7°	-	
V2	0°	-	6°	
All Dimensions in millimeter				

Package Outline Dimensions Millimeters

TO-251

	Dim.	Min.	Max.
	A	2.2	2.4
	A2	0.95	1.15
	A3	0.45	0.65
	b	0.65	0.85
	c	0.45	0.55
	D	6.45	6.75
	D2	5.2	5.4
	E	5.8	6
	E2	0.95	1.25
	e	Typ 2.3	
	e1	Typ 4.6	
	L	4	4.2
	L1	1.2	1.5
All Dimensions in millimeter			