


**Trench MOS Barrier Schottky Rectifier**
**Reverse Voltage - 100 V**
**Forward Current - 15 A**
**FEATURES**

- ◆ Advanced trench technology
- ◆ Low forward voltage drop
- ◆ Low power losses
- ◆ High efficiency operation
- ◆ Lead free in comply with EU RoHS 2011/65/EU directives

**MECHANICAL DATA**

- ◆ Case: TO-277
- ◆ Terminals: Solderable per MIL-STD-750, Method 2026


**Maximum Ratings (Per Leg) at Ta=25°C unless otherwise specified**


| Parameter                                                                                    |           | Symbols         | Value      | Units |
|----------------------------------------------------------------------------------------------|-----------|-----------------|------------|-------|
| Maximum Repetitive Peak Reverse Voltage                                                      |           | $V_{RRM}$       | 100        | V     |
| Maximum RMS voltage                                                                          |           | $V_{RMS}$       | 100        | V     |
| Maximum DC Blocking Voltage                                                                  |           | $V_{DC}$        | 100        | V     |
| Maximum Average Forward Rectified Current                                                    | Per diode | $I_{F(AV)}$     | 15         | A     |
| Peak Forward Surge Current, 8.3ms Single Half Sine-wave superimposed on rated load per diode |           | $I_{FSM}$       | 280        | A     |
| Operating Temperature Range                                                                  |           | $T_J$           | -55 ~ +150 | °C    |
| Storage Temperature Range                                                                    |           | $T_{STG}$       | -55 ~ +150 | °C    |
| Typical Thermal Resistance Per diode(munted on FR-4 PCB)                                     | TO-277    | $R_{\theta JC}$ | 72         | °C/W  |

**Note1: Thermal resistance from Junction to case per leg mounted on heatsink.**
**Electrical Characteristics (Per Leg) unless otherwise specified**


| Characteristics                                                  |          | Symbols | Value      |            | Units |
|------------------------------------------------------------------|----------|---------|------------|------------|-------|
| Forward Voltage Drop(Note2)                                      |          | $V_F$   | <b>Typ</b> | <b>Max</b> | V     |
| at $I_F=5A$ Instantaneous forward voltage per diode              | TA=25°C  |         | 0.48       | -          |       |
|                                                                  | TA=125°C |         | 0.43       | -          |       |
| at $I_F=15A$ Instantaneous forward voltage per diode             | TA=25°C  |         | 0.68       | 0.75       |       |
|                                                                  | TA=125°C | 0.62    | -          |            |       |
| Instantaneous reverse current per diode at rated reverse voltage | TA=25°C  | $I_R$   | 20         | 200        | uA    |
|                                                                  | TA=125°C |         | -          | 30         | mA    |

**Note2: (1)Pulse test: 300 μs pulse width, 1 % duty cycle  
 (2) Pulse test: Pulse width ≤ 40 ms**


**RATINGS AND CHARACTERISTIC CURVES**




**Current Derating, Case**



**Typical Junction Capacitance**




**Typical Forward Voltage**



**Typical Reverse Current**

**Package Outline TO-277**


Plastic surface mounted package; 3 leads



| Dim | Min   | Max |
|-----|-------|-----|
| A   | 1.1   | 1.2 |
| A2  | 0.3   | 0.4 |
| b1  | 0.8   | 1   |
| b2  | 1.7   | 1.9 |
| D   | 3.9   | 4.1 |
| D1  | 3.054 |     |
| E   | 6.4   | 6.6 |
| e   | 1.84  |     |
| E1  | 5.3   | 5.5 |
| E2  | 3.549 |     |
| L   | 0.8   | 1   |
| L1  | 0.5   | 0.7 |
| W   | 1.1   | 1.4 |

unit:mm

**Mounting Pad Layout**



| Dim | Min |
|-----|-----|
| C   | 1.8 |
| G   | 0.9 |
| X   | 3.4 |
| X1  | 1.4 |
| Y   | 4.9 |
| Y1  | 1.4 |

unit:mm

**Summary of Packing Options**

| Package | Packing Description | Packing Quantity | Industry Standard |
|---------|---------------------|------------------|-------------------|
| TO-277  | Tape/Reel,13"reel   | 5000             | EIA-481-1         |