

16A 3Quadrants TRIACs

Product Summary


Symbol	Value	Unit
$I_{T(RMS)}$	16	A
$V_{DRM} V_{RRM}$	600/800	V
V_{TM}	1.55	V

Features

With high ability to withstand the shock loading of large current, With high commutation performances, 3quadrants products especially recommended for use on inductive load.

Application

Washing machine, vacuums, massager, solid state relay, AC Motor speed regulation and so on.



Order Information

Part Number	Package	Marking	Packing	Packing Quantity
BTB16Q	TO-263	BTB16 600BW XXXX	Tape	800PCS/Reel

Absolute maximum ratings ($T_a=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Value	Unit
Repetitive peak off-state voltage	V_{DRM}	600/800	V
Repetitive peak reverse voltage	V_{RRM}	600/800	V
RMS on-state current	$I_{T(RMS)}$	16	A
Non repetitive surge peak on-state current (full cycle, $F=50\text{Hz}$)	I_{TSM}	160	A
I^2t value for fusing ($t_p=10\text{ms}$)	I^2t	140	A^2s
Critical rate of rise of on-state current ($I_G=2 \times I_{GT}$)	di_T/dt	I - II -III 50	A/us
Peak gate current	I_{GM}	4	A
Average gate power dissipation	$P_G (AV)$	1	W
Junction Temperature	T_J	$-40 \sim +125$	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	$-40 \sim +150$	$^{\circ}\text{C}$

Electrical characteristics (TA=25°C, unless otherwise noted)

Parameter	Symbol	Test Condition	Value		Unit
			CW	BW	
Gate trigger current	I_{GT}	$V_D=12V$ $R_L=33\Omega$ $T_j=25^\circ C$	≤ 35	≤ 50	mA
Gate trigger voltage	V_{GT}	I-II-III	≤ 1.3		V
Gate non-trigger voltage	V_{GD}	$V_D = V_{DRM}$ $T_j=125^\circ C$	≥ 0.2		V
latching current	I_L	$I_G = 1.2I_{GT}$	≤ 50	≤ 70	mA
			≤ 60	≤ 80	
Holding current	I_H	$I_T = 500mA$	≤ 30	≤ 50	mA
Critical-rate of rise of commutation voltage	dV_D/dt	$V_D=2/3V_{DRM}$ Gate Open $T_j=125^\circ C$	≥ 500	≥ 1000	V/us


STATIC CHARACTERISTICS

Forward "on" voltage	V_{TM}	$I_{TM} = 23A$ $t_p=380us$	≤ 1.55	V
Repetitive Peak Off-State Current	I_{DRM}	$V_D=V_{DRM}$ $V_R=V_{RRM}$	≤ 5	UA
Repetitive Peak Reverse Current	I_{RRM}		≤ 1	mA

THERMAL RESISTANCES

Thermal resistance	$R_{th(j-c)}$	Junction to case(AC)	1.2	°C/W
	$R_{th(j-a)}$	Junction to ambient	45	°C/W

Ordering Information



Typical Characteristics

FIG.1: Maximum power dissipation versus RMS on-state current (full cycle)




FIG.2: RMS on-state current versus case temperature (full cycle)




FIG.3: Surge peak on-state current versus number of cycles




FIG.4: On-state characteristics (maximum values)




FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10ms$





FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature (typical values)



Package Information

TO-263

