



**VOLTAGE RANGE: 4000 - 5000V**  
**CURRENT: 0.2 A**

### Features

- Low cost
- Low leakage
- Low forward voltage drop
- High current capability
- Easily cleaned with alcohol, Isopropanol and similar solvents

### Mechanical Data

- Case: DO-15, Molded Plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: Cathode Band
- Weight: 0.40 grams (approx.)
- Mounting Position: Any
- Marking: Type Number



| DO-15                |       |       |
|----------------------|-------|-------|
| Dim                  | Min   | Max   |
| A                    | 25.40 | —     |
| B                    | 5.50  | 7.62  |
| C                    | 0.686 | 0.889 |
| D                    | 2.60  | 3.60  |
| All Dimensions in mm |       |       |

### Maximum Ratings and Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.


| Characteristic   | Symbol             | R4000F          | R5000F | Unit |
|--|--------------------|-----------------|--------|------|
| Maximum recurrent peak reverse voltage   | V <sub>RRM</sub>   | 4000            | 5000   | V    |
| Maximum RMS voltage  | V <sub>RMS</sub>   | 2800            | 3500   | V    |
| Maximum DC blocking voltage  | V <sub>DC</sub>    | 4000            | 5000   | V    |
| Maximum average forward rectified current<br>9.5mm lead length, @T <sub>A</sub> =75°C                          | I <sub>F(AV)</sub> | 0.2             |        | A    |
| Peak forward surge current<br>8.3ms single half-sine-wave<br>superimposed on rated load @T <sub>J</sub> =125°C | I <sub>FSM</sub>   | 30.0            |        | A    |
| Maximum instantaneous forward voltage<br>@ 0.2A  | V <sub>F</sub>     | 6.5             |        | V    |
| Maximum reverse current @T <sub>A</sub> =25°C<br>at rated DC blocking voltage @T <sub>A</sub> =100°C           | I <sub>R</sub>     | 5.0             | 100.0  | μA   |
| Maximum reverse recovery time (Note1)  | t <sub>rr</sub>    | 500             |        | ns   |
| Typical junction capacitance (Note2)   | C <sub>J</sub>     | 15              |        | pF   |
| Operating junction temperature range   | T <sub>J</sub>     | - 55 ---- + 150 |        | °C   |
| Storage temperature range  | T <sub>STG</sub>   | - 55 ---- + 150 |        | °C   |

NOTE: 1. Measured with I<sub>F</sub>=0.5A, I<sub>R</sub>=1A, I<sub>rr</sub>=0.25A.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.


AVERAGE FORWARD RECTIFIED CURRENT  
AMPERES

**FIG.1 – FORWARD DERATING CURVE**




PEAK FORWARD SURGE CURRENT  
AMPERES


**FIG.2 – PEAK FORWARD SURGE CURRENT**



**FIG.3 – TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC**



NOTES: 1. RISE TIME = 7ns MAX. INPUT IMPEDANCE = 1MΩ, 22pF.  
2. RISE TIME = 10ns MAX. SOURCE IMPEDANCE = 50 Ω.



SET TIME BASE FOR 50/100 ns/cm